

TORO®

ULTRA BUGGY® e2500-TS

MATERIAL HANDLING

The electric swivel Ultra Buggy e2500-TS gives crews the flawless precision needed to transform jobsites. Operators can unload sand, gravel, concrete and other heavy materials along a 180-degree radius for ultimate precision from any angle. And it's all powered by Toro's patented HyperCell® battery technology that delivers up to eight hours of quiet runtime without sacrificing power. Crews will still enjoy the same 2,500-lb carrying capacity of gas models to reduce physical strain and accelerate efficiency on indoor or outdoor jobs.

KEY FEATURES

2,500-lb. Carrying Capacity – Save time and energy while greatly reducing physical strain and fatigue.

Powered by HyperCell – Toro's proprietary battery technology offers reduced noise, zero engine exhaust emissions and all-day runtime.

Precision Placement – The smooth slew drive operation makes it easy for users to dump material anywhere along the 180-degree radius.

Auto-Return Dump – Quickly return the tub to resting position while moving on to the next load — operators won't miss a beat.

Intuitive Controls – Move materials in minutes with controls designed for smooth handling.

Narrow Design – At 31.5", the e2500-TS easily maneuvers in tight spaces and can fit through standard doorways and gates.





ULTRA BUGGY® e2500-TS

MATERIAL HANDLING

KEY SPECIFICATIONS

Electric Ultra Buggy Swivel (model 68140)

Battery Capacity Chemistry	13 kWh Lithium Ion
Dimensions (LxWxH)	100.7"x31.5"x52.1" (255.7 x 80.0 x 132.3 cm)
Platform down	87.9"x31.5"x52.1"
Platform up	(223.2 x 80.0 x 132.3 cm)
Weight	2,080 lbs (943.4 kg)
Tub Volume	14 ft³ (0.4 m³)
Max Load Capacity	2,500 lbs (1,136 kg)
Speed	5 mph (8.04 km/h) forward 3 mph (4.82 km/h) reverse
Run Time	Up to 8 hours
Charging Type	100-240 Volt, on-board
Charging Time	80% in 4 hours at 240V 100% in 6 hours at 240V
Discharge Height	17.8" (45.2 cm)
Distributed Floor Pressure	
Unloaded	1.05 PSI
Loaded	1.55 PSI

