

GRANDSTAND®

STAND-ON MOWERS

SEE PAGE 2 FOR BATTERY

REVOLUTION SERIES OPTIONS

STAND UP TO ANY TERRAIN.



BUMPY PATCHES AND CHALLENGING TERRAIN ARE ALL IN A DAY'S WORK—but feeling them doesn't need to be. GrandStand® combines the speed and comfort of a zero-turn rider with the on-and-off ease of a walk-behind for speed and maneuverability.

IMPROVE PRODUCTIVITY with easy access on and off the machine—up to 10.5 gallons of fuel capacity on 48", 52", 60" and 72" models—to mow longer with fewer stops.

GAIN SPEED AND PERFORMANCE with a new max forward ground speed of up to 12 mph and responsive solid drive linkage. *(Select models only.)*

SAVE MAINTENANCE AND TIME with no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access. The fuel tank can also be removed without draining for easy service access to the transmission and controls.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE



GrandStand® Series helps you save time, money and trailer space with multi-season flexibility and a foldable operator platform.

2.6–5.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers back down when it's time to ride, saving time and trailer space.



POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.



HIGHER HORSEPOWER

Effortlessly tackle demanding jobs with an upgraded 35 hp* Kawasaki FX1000 999cc engine. (Models 72507 and 72512)

	72504		72518		72505		72519		72513		72509		72520		HDX 72506	
POWER SYSTEM	71504 CARB				71505 CARB								NEW			
Commercial Engines at 3600 RPM*	22 hp Kawasaki FX (726cc)		▶ 23 hp Kohler [®] Command PRO [®] EFI (747cc)		22 hp Kawasaki FX (726cc)		▶ 25 hp Kohler Command PRO EFI (747cc)				23.5 hp Kawasaki FX730V (726cc)		Briggs 28 HP (883cc)		31 hp Kawasaki FX921 (999cc)	
Starter							FX (726cc)								Electric	
Heavy-Duty Canister Air Cleaner							▶ Standard								▶ Standard	
Drive Tires							▶ 20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)								▶ 24" x 9.5" – 12" Turf (61 x 24.1 – 30.5 cm)	
Caster Tires							11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)								13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	
Fuel/Capacity							Gas/10.5-Gal (39.7 L)								Gas/10.5-Gal (39.7 L)	
Digital Hour Meter							Standard								Standard	
Hydraulic Drive System							▶ Unitized Pumps & Wheel Motors								▶ Unitized Pumps & Wheel Motors	
Pump							10cc/rev								13cc/rev	
Wheel Motor							10 cir								13cc/rev	
Maximum Forward Speed							▶ 10 mph (16.1 km/h)								▶ 12 mph (19.3 km/h)	
Throttle Control							Manual								▶ Electronic	
Clutch							Electromagnetic								Electromagnetic	
MOWING DECKS																
Deck Size	▶ 48" (121.9 cm)		48" (121.9 cm)		▶ 52" (132.1 cm)		52" (132.1 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		52" (132.1 cm)	
Cutting Deck							7-Gauge TURBO FORCE*								7-Gauge TURBO FORCE*	
Bullnose Bumper							Standard								Standard	
Adjustable Discharge Baffle							Standard								Standard	
Rubber Discharge Chute							Standard								Standard	
Deck Lift Design							▶ Extension Spring								▶ Extension Spring	
Spindle Housings							9 3/8" (23.8 cm) Diameter Cast Aluminum								9 3/8" (23.8 cm) Diameter Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft							Standard								Standard	
Spindle Bearings							Maintenance-Free								Maintenance-Free	
Cutting Height							▶ 1.5" – 5.0" (3.8 – 12.7 cm)								▶ 1.5" – 5.0" (3.8 – 12.7 cm)	
Blades							.204" (.5 cm) Heat-Treated Steel								.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed							18,500+ ft/min								18,500+ ft/min	
Belt Construction							Aramid Fiber V-Belt								Aramid Fiber V-Belt	
Anti-Scalp Rollers			▶ Optional						▶ Standard						Standard	
Carrier Frame Construction							3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)								3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)	
FEATURES																
Steering Controls							Twin Lever								Twin Lever	
Operator Platform							Foldable Operator Platform with Suspension								Foldable Operator Platform with Suspension	
WEIGHTS AND MEASUREMENTS																
Weight	890 lbs.	403.7 kg	881 lbs.	399.6 kg	898 lbs.	407.3 kg	895 lbs.	406 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	1061 lbs.	481.3 kg
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	50.25"	127.6 cm
Deck Clearance Width	49.5"	125.7 cm	49.5"	125.7 cm	53.5"	135.9 cm	53.5"	135.9 cm	61.5"	156.2 cm	61.5"	156.2 cm	61.5"	156.2 cm	N/A	N/A
Deflector Width	63.5"	161.3 cm	63.5"	161.3 cm	67.5"	171.5 cm	67.5"	171.5 cm	75.5"	191.8 cm	75.5"	191.8 cm	75.5"	191.8 cm	53.5"	135.9 cm
Length (Platform Up)	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	65"	165.1 cm	65"	165.1 cm	65"	165.1 cm	71"	180.3 cm
Length (Platform Down)	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	79"	200.7 cm	79"	200.7 cm	79"	200.7 cm	85.5"	217.2 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature

	HDX 72510		HDX 72514		HDX 72517		HD+ 72507		HD+ 72512		HDM 74534		HDM 74532		HDM 74535	
POWER SYSTEM							NEW		NEW		79534 CARB		NEW		NEW	
Commercial Engines at 3600 RPM*	31 hp Kawasaki FX921 (999cc)		37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		35 hp Kawasaki FX1000 (999 cc)		15 hp Kawasaki® FS (603cc)		18.5 hp Kawasaki FS600V (603 cc)					
Starter	Electric		Electric		Electric		Electric		Electric		Electric		Electric		Electric	
Heavy-Duty Canister Air Cleaner	▶ Standard		▶ Standard		▶ Standard		▶ Standard		N/A		▶ Standard		▶ Standard		▶ Standard	
Drive Tires	▶ 24" x 12" - 12" Turf (61 x 30.5 - 30.5 cm)		▶ 24" x 12" - 12" Turf (61 x 30.5 - 30.5 cm)		▶ 24" x 12" - 12" Turf (61 x 30.5 - 30.5 cm)		20 in. x 10.5 in. - 8 in. (50.8 cm x 26.7 cm - 20.3 cm)		18" x 8.5" - 8" (45.7 x 21.6 - 20.3 cm)		18" x 8.5" - 8" (45.7 x 21.6 - 20.3 cm)		21 in. x 7 in. - 10 in. (53.3 cm x 17.7 cm - 25.4 cm)		21 in. x 7 in. - 10 in. (53.3 cm x 17.7 cm - 25.4 cm)	
Caster Tires	13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		11" x 4" - 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 - 12.7 cm)		11" x 4" - 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 - 12.7 cm)		11" x 4" - 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 - 12.7 cm)		9 in. x 4.5 in. - 5 in. Semi-Pneumatic (22.8 cm x 11.4 cm - 12.7 cm)		9 in. x 4.5 in. - 5 in. Semi-Pneumatic (22.8 cm x 11.4 cm - 12.7 cm)	
Fuel/Capacity	Gas/10.5-Gal (39.7 L)		Gas/10.5-Gal (39.7 L)		Gas/10.5-Gal (39.7 L)		Gas/10.5-Gal (39.7 L)		Gas/10.5-Gal (39.7 L)		Gas/7.8-Gal (29.5 L)		Gas/5-Gal (18.9 L)		Gas/5-Gal (18.9 L)	
Digital Hour Meter	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Hydraulic Drive System	▶ Unitized Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors		Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors	
Pump	13cc/rev		13cc/rev		13cc/rev		10 cc/rev		10 cc/rev		10cc/rev		13cc/rev		13cc/rev	
Wheel Motor	13cc/rev		13cc/rev		13cc/rev		10 cc/rev		10 cc/rev		10 cir		13cc/rev		13cc/rev	
Maximum Forward Speed	▶ 12 mph (19.3 km/h)		▶ 12 mph (19.3 km/h)		▶ 12 mph (19.3 km/h)		▶ 12 mph (19.3 km/h)		▶ 12 mph (19.3 km/h)		8 mph (12.9 km/h)		7.5 mph (12.0 km/h)		7.5 mph (12.0 km/h)	
Throttle Control	▶ Electronic		▶ Electronic		▶ Electronic		▶ Electronic		▶ Electronic		Manual		▶ Electronic		▶ Electronic	
Clutch	Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic	
MOWING DECKS																
Deck Size	60" (152.4 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		52" (132.1 cm)		60" (152.4 cm)		36" (91.4 cm)		32" (81.2cm)		36" (91.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™		7-Gauge TURBO FORCE™	
Bullnose Bumper	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Adjustable Discharge Baffle	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Rubber Discharge Chute	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Deck Lift Design	▶ Extension Spring		▶ Extension Spring		▶ Extension Spring		▶ Extension Spring		▶ Extension Spring		Compression Spring		▶ Extension Spring		▶ Extension Spring	
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum		9 3/8" (23.8 cm) Diameter Cast Aluminum		9 3/8" (23.8 cm) Diameter Cast Aluminum		9 in / 22.9 cm Diameter Cast Aluminum		9 in / 22.9 cm Diameter Cast Aluminum		Cast Iron		7.75 in/19.7cm Dia Cast Aluminum		7.75 in/19.7cm Dia Cast Aluminum	
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard		Standard		Standard		Standard		Standard		Standard		Standard		Standard	
Spindle Bearings	Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free		Maintenance-Free	
Cutting Height	▶ 1.5" - 5.0" (3.8 - 12.7 cm)		▶ 1.5" - 5.0" (3.8 - 12.7 cm)		▶ 1.5" - 5.0" (3.8 - 12.7 cm)		▶ 1.5" - 5.0" (3.8 - 12.7 cm)		▶ 1.5" - 5.0" (3.8 - 12.7 cm)		1.0" - 5.0" (2.5 - 12.7 cm)		1.0" - 4.5" (2.54 - 11.4 cm)		1.0" - 4.5" (2.54 - 11.4 cm)	
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.25" (.6 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel	
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min		18,500+ ft/min	
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt		Aramid Fiber V-Belt	
Anti-Scalp Rollers	Standard		Standard		Standard		Optional		Standard		N/A		Rear Only - Standard		Rear Only - Standard	
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3" x 1.5" x 10-Gauge (7.6cmx3.8cmx10-Gauge)		3" x 1.5" x 10-Gauge (7.6cmx3.8cmx10-Gauge)	
FEATURES																
Steering Controls	Twin Lever		Twin Lever		Twin Lever		Twin Lever		Twin Lever		Twin Lever		Twin Lever		Twin Lever	
Operator Platform	Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension	
WEIGHTS AND MEASUREMENT																
Weight	1091 lbs.	494.9 kg	1100 lbs.	499.0 kg	1193 lbs.	541.1 kg	949 lb	430 kg	1004 lb	455 kg	833 lbs.	377.8 kg	702 lbs	318.4 kg	779 lbs	353.3 kg
Height	50.25"	127.6 cm	50.25"	127.6 cm	50.25"	127.6 cm	48"	122 cm	48"	122 cm	48"	121.9 cm	47.3"	120.1 cm	47.3"	120.1 cm
Deck Clearance Width	N/A	N/A	N/A	N/A	N/A	N/A	54"	137 cm	62"	158 cm	37.6"	95.5 cm	N/A	N/A	N/A	N/A
Deflector Width	61.5"	156.2 cm	61.5"	156.2 cm	73.75"	187.3 cm	68"	172 cm	76"	193 cm	51.6"	131.1 cm	44.9"	114 cm	48.0"	122 cm
Length (Platform Up)	73.5"	186.7 cm	61.5"	156.2 cm	73.75"	187.3 cm	61"	145 cm	65"	164 cm	61"	154.9 cm	58.1"	147.5 cm	58.1"	147.5 cm
Length (Platform Down)	88.0"	223.5 cm	75.25"	190.5 cm	87.75"	222.9 cm	75"	191 cm	79"	201 cm	74"	188 cm	N/A	N/A	N/A	N/A

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.