TRX TRENCHERS

WALK-BEHIND TRENCHERS

Efficient Trenching in Tight Spaces

When installing irrigation, utilities, or lighting, Toro TRX trenchers help crews dig efficiently where access is limited. Tracked maneuverability supports steady movement in tight corridors, while easy to learn controls keep operators focused on the trench. Designed to reduce adjustments and downtime, TRX trenchers help crews maintain momentum, deliver clean results, and complete trenching work efficiently from layout to backfill.



TRX 300 | model 22984



STAYS ON LINE

Controlled trenching helps operatirs follow the desired path with fewer corrections.



CONFIDENT STEERING

Streamlined controls support smooth operation in tight corridors.



WORKS WHERE SPACE IS TIGHT

Tracked design supports maneuverability where access is limited.

TRX TRENCHERS

WALK-BEHIND TRENCHERS

	TRX WALK-BEHIND TRENCHER SPECIFICATIONS		
	TRX-16 MODEL 22972	TRX-250 MODEL 22983	TRX-300 MODEL 22984
POWER SYSTEM			
Engine	Kawasaki® FS481V 16 hp (11.7 kW)	Toro® V-Twin 24.5 hp (18.3 kW)	Kohler® PS-ECV749-3077 26.5 hp (19.8 kW)
Torque	32.1 ft-lbs	37.5 ft-lbs	40.9 ft-lbs
Fuel Type	Gasoline	Gasoline	Gasoline
Fuel Tank Capacity	1.97 gal. (7.44 L)	4.8 gal. (19.52 L)	4.8 gal. (19.52 L)
Start Method	Recoil	Electric	Electric
HYDRAULIC SYSTEM			
Trencher Hydraulic Flow	10.4 gpm	13.2 gpm	13.2 gpm
Hydraulic Reservoir Capacity	6 gal. (22.7 L)	6 gal. (22.7 L)	6 gal. (22.7 L)
TRACKS			
Track Type	Rubber w/ Polyester/ Nylon fabric	Rubber w/ Polyester/ Nylon fabric	Rubber w/ Polyester/ Nylon fabric
Wheelbase	23.5 in. (59.7 cm)	23.5 in. (59.7 cm)	23.5 in. (59.7 cm)
Track Width	5.9 in. (15 cm)	5.9 in. (15 cm)	5.9 in. (15 cm)
DIMENSIONS			
Ground Clearance	4.4 in. (11.2 cm)	4.3 in. (10.9 cm)	4.3 in. (10.9 cm)
Overall Dimensions With 2' Boom (L×W×H)	82.5 x 33.2 x 45.5 in. (209.6 x 84.3 x 115.6 cm)	82.5 x 33.2 x 45.5 in. (209.6 x 84.3 x 115.6 cm)	82.5 x 33.2 x 45.5 in. (209.6 x 84.3 x 115.6 cm)
Ground Speed (Forward/Reverse)	3.3 mph (5.3 kph) / 1.1 mph (1.8 kph)	3.7 mph (6 kph) / 1.5 mph (2.4kph)	3.7 mph (6 kph) / 1.5 mph (2.4kph)
Weight (no boom / with 3' boom)	1,017 lbs (461.4 kg) / 1,274 lbs (577.8 kg)	1,036 lbs (470 kg) / 1,293 lbs (586.4 kg)	1,037 lbs (470 kg) / 1,293 lbs (586.4 kg)
Ground Pressure (no boom / with 3' boom)	4.1 psi / 4.3 psi	4.1 psi / 4.3 psi	4.1 psi / 4.3 psi
BOOM OPTIONS			
Depths	2' boom: 24 in. (61.0 cm) 3' boom: 36 in. (91.4 cm) 4' boom: 48 in. (121.9 cm)	2' boom: 24 in. (61.0 cm) 3' boom: 36 in. (91.4 cm) 4' boom: 48 in. (121.9 cm)	2' boom: 24 in. (61.0 cm) 3' boom: 36 in. (91.4 cm) 4' boom: 48 in. (121.9 cm)
Chain Widths	4 or 6 in. (10.2 cm or 15.2 cm), no kit for 8" wide 48 inch chains	4, 6, 8 in. chains (10.2, 15.2, or 20.3 cm)	4, 6, 8 in. chains (10.2, 15.2, or 20.3 cm)

©2026 The Toro Company Part No. 226-018 | toro.com
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.