STX-26 & STX-38

WALK-BEHIND STUMP GRINDERS

Turn Stumps Into Chips Faster

When stumps slow down a job, Toro STX stump grinders help crews remove them efficiently and move on. Built for tree care, landscape, and rental applications, they are easy to learn and comfortable to operate. Tracked stability supports confident work on uneven terrain and tight access areas, helping crews clear sites faster, reduce downtime between jobs, and maintain steady productivity throughout the day.



STX-38 | model 23214



FAST STUMP REMOVAL

Efficient grinding helps crews clear stumps quickly and move on to the next job.



SIMPLE, CONFIDENT CONTROL

Intuitive controls help operators focus on the cut, not the machine.



STABLE ON UNEVEN GROUND

Tracked stability supports confident work on uneven and tight terrain.

STX-26 & STX-38

WALK-BEHIND STUMP GRINDERS

	STX STUMP GRINDER SPECIFICATIONS	
	STX-26 MODEL 23208	STX-38 MODEL 23214
POWER SYSTEM		
Engine	Kawasaki® FX730V 23.5 hp (17.5 kW)	Kohler® ECV980 34.8 hp (26 kW)
Torque	39.9 ft-lbs	53 ft-lbs
Start Method	Key Start	Key Start
Fuel Type	Gasoline	Gasoline
Fuel Tank Capacity	4.8 gal (19.9 L)	5 gal (18.93 L)
HYDRAULIC SYSTEM		
Grinder Hydraulic Flow	13.2 gpm	19.1 gpm
Hydraulic Tank Capacity	6 gal (22.7 L)	10 gal (37.9 L)
TRACKS		
Track Type	Rubber w/ Polyester/Nylon fabric	Rubber w/ Nylon fabric and Aramid Corde
Wheelbase	23.5 in. (59.7 cm) (right track frame offset 2.5 in. back)	34 in. (86.4 cm)
Track Width	5.9 in. (15 cm)	5.9 in. (15 cm)
DIMENSIONS		
Ground Clearance	4.3 in. (10.9 cm)	4.6 in. (11.7 cm)
Overall Dimensions (L×W×H) with Trencher Down	89.5 x 33.2 x 44.8 in. (227.3 x 84.3 x 113.8 cm)	With Shield: 105.8 x 33.2 x 51.3 in (268.7 x 84.3 x 130.3 cm) Without Shield: 105.8 x 33.2 x 44.8 in (268.7 x 84.3 x 113.8 cm)
Cutting Wheel	Hyd drive 19 inches with 12 x 3 position cutting bits	Hyd drive 22.25 inches with 16 x 3 position cutting bits
Cutter Depth	12.5 in (31.8 cm)	18 in (45.7 cm)
Cutter Height	33 in (83.8 cm)	35 in (88.9 cm)
Head Swing / Arc Length	47 in. (119. 4 cm) straightline / 90 degrees	52 inches (132.1 cm) straightline / 60 degrees
Ground Speed (Forward/Reverse)	3 mph (4.8 kph) / 0.9 mph (1.4 kph)	3.7 mph (6 kph) / 1.5 mph (2.4 kph)
Weight	1,249 lbs (566.4 kg)	1,874 lbs (850 kg)
Ground Pressure	4.6 psi	4.7 psi

©2026 The Toro Company Part No. 2026-0017 | toro.com
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.