eDINGO® TX 750

TRACKED COMPACT UTILITY LOADER

ELECTRIC POWERED

Electric Performance Built for Indoors

When interior demolition and construction demand more capability in tight spaces, the eDingo TX 750 is built for the work. Electric operation produces no engine exhaust emissions, making it suitable for indoor jobsites. Designed for heavier daily use, it helps crews stay productive, reduce fatigue, and keep the job moving as they remove flooring, handle debris, and move materials through doorways and corridors with control and confidence.

Key Specifications

- 750 lb ROC
- 106.6” hinge pin height
- Up to 8 hours of continuous runtime
- 31.5” width (22230)





READY FOR INTERIOR WORK

Electric operation produces no engine exhaust emissions, making it suitable for interior jobsites.



HANDLES TOUGH INDOOR JOBS

Designed for demanding interior tasks that require reliable performance day after day.



IMPROVES JOB FLOW

Helps crews move debris and materials smoothly through doorways and corridors.

eDINGO® TX 750

TRACKED COMPACT UTILITY LOADER

ELECTRIC POWERED

eDINGO® TX 750 SPECIFICATIONS

	NARROW TRACK MODEL 22230	WIDE TRACK MODEL 22231
BATTERY		
Chemistry	Toro HyperCell® Lithium Ion	
Capacity	22 kWh	
Fuel Type	Electric	
Run Time[1]	Up to 8 hours	
CHARGING		
Charging Type	3.3 kW with 240V	
Charging Time (80%, 100%)	5.33 hours, 8 hours	
HYDRAULIC SYSTEM		
Hydraulic Pressure	3045 psi	
Auxiliary Flow (high/low)	11.3 gpm / 9.3 gpm	
Auxiliary Pressure	3,190 psi	
Reservoir Capacity	6.8 gal (25.7 L)	
TRACKS		
Track Type	Rubber w/steel core and belt	
Wheelbase	44.8 inches (113.8 cm)	
Track Width	5.9 inches (15 cm)	9.1 inches (25 cm)
Tread Pattern	B Tread Pattern	Turf-Friendly
WEIGHTS AND MEASUREMENTS		
Ground Clearance	5.8 inches (14.7 cm)	
Dimensions, without Bucket Platform Up (L×W×H)	66.0 x 31.5 x 54.5 in. (167.6 x 80.0 x 138.4 cm)	66.0 x 37.2 x 54.5 in. (167.6 x 94.5 x 138.3 cm)
Dimensions, without Bucket Platform Down (L×W×H)	79.7 x 31.5 x 54.5 in. (202.4 x 80 x 138.4 cm)	79.7 x 37.2 x 54.5 in. (202.4 x 94.5 x 138.4 cm)
Hinge Pin Height	106.6 in. (270.8 cm)	
Dump Height	61 in. (154.9 cm)	
Reach, Fully Raised and Dumped	21.2 in. (53.8 cm)	
Ground Speed, Platform Up (Forward/Reverse)	Platform Up: 3.7 mph (5.9 kph) / 3.7 mph (5.9 kph) Platform Down: 3.7 mph (5.9 kph) / 1.5 mph (2.4 kph)	
Weight	Without Bucket: 2,572 lbs (1,166.6 kg) With Bucket: 2,712 lbs (1,230.1 kg)	Without Bucket: 2,654 lbs (1,203.8 kg) With Bucket: 2,794 lbs (1,267.3 kg)
Distributed Floor Pressure	Without Bucket: 1.0 psi, With Bucket: 1.1 psi	Without Bucket: 0.9 psi, With Bucket: 0.95 psi
Tipping Capacity (Platform Up/ Platform Down)	1,822 lbs (826.4 kg) / 2,221 lbs (1,107.4 kg)	1,872 lbs (849.1 kg) / 2,195 lbs (995.6 kg)
Rated Operating Capacity[2] (ROC)	Platform Up: 640 lbs (290.3 kg) Platform Down: 750 lbs (340.19 kg)	Platform Up: 658 lbs (298.5 kg) Platform Down: 750 lbs (340.19 kg)

[1]Run time may vary based upon conditions and attachment being used. [2]Per ISO 14397-1

©2026 The Toro Company Part No. 2026-0007 | toro.com
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.