

# Z MASTER<sup>®</sup>

2000 SERIES



# WORK FAST. WORK RIGHT.



**HORIZON360**  
CONTRACTOR BUSINESS SOFTWARE

**COMPATIBLE**

The commercial-grade yet civilian-friendly Z Master 2000 gives you plenty of time and energy back with superbly capable, get-it-done-right productivity. Z Master 2000 is constructed to work and work and work, while not working you over. Using top-grade materials and engineering for both all-job toughness and all-rider ease, you will go fast, powerfully, comfortably, and be the master of your domain.

## WORK FAST, WORK RIGHT

Step on it with speeds up to 10 MPH (miles per hour), and sacrifice nothing in quality. Power-packed engines deliver 25 HP\* for clear-cut efficiency. Productivity rolls on traction-happy 24" rear tires. Our high-strength steel TURBO FORCE<sup>®</sup> cutting deck stands up to every challenge, pass after pass, day after day, year after year.

## HIGHLY ENGINEERED BRUTE FORCE

This machine is built on a full tubular frame of 7-Gauge high-strength steel for rock-solid durability. Strong, tough cast aluminum forms our spindle housing for long-flying service. Our bullnose bumper is engineered with no-BS toughness.

## SMOOTH OPERATOR

Our suspension seats are fully adjustable forward and backward, and customizable to your weight. Save your back and bones with MyRIDE<sup>®</sup> Suspension System (upgrade). Enjoy human-friendly seats with lumbar support, and perks like a USB port, cup holder and phone holder.

## QUICK CARRY SYSTEM



### TRIPLE THREAT UTILITY KIT

(145-3691) Attach tools and accessories directly to the mower with innovative tool-mounting brackets. Includes Bucket Holder Kit (147-63445), Universal Mount (147-6346) and Trimmer Mount (147-2665). *Sold separately.*



### TURBO FORCE DECK

With heavy-duty cast aluminum spindle housings and the bullnose bumper, you get the master of all-conditions mowing muscle. Pro models available with flat-free semi-pneumatic caster tires.



### CONFIDENTLY COMFORTABLE

Easily adjust the seat and ideal seat suspension to your preference. Customize your ride: Lights, Bucket Holder Kit (147-6345), Trimmer Mount (144-2662), Baggers, Mounts, and top 20 attachments.



### MyRIDE<sup>®</sup> SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.

	HD								HDX MyRIDE® SUSPENSION SYSTEM				PRO		
	77281		77283		77285		77292		77291 HDX		77294 HDX		77288		
<b>POWER SYSTEM</b>															
Commercial Engines at 3600 RPM*	Toro® 24.5 hp w/ HDAC						23.5 hp Kawasaki FX (726cc)		23.5 hp Kawasaki FX (726cc)				▶ 28 hp Briggs & Stratton® Vanguard EFI (810cc)		
Starter	Electric								Electric				Electric		
Heavy-Duty Donaldson® Canister-Style Air Cleaner	Standard								Standard				Standard		
Drive Tires	Voodoo Trac 24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	▶ Voodoo Trac 24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)		▶ Voodoo Trac 24" x 12" - 12" (61 x 30.5 - 30.5 cm)				Voodoo Trac 24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	▶ Voodoo Trac 24" x 12" - 12" (61 x 30.5 - 30.5 cm)		Voodoo Trac 24" x 12" - 12" (61 x 30.5 - 30.5 cm)				
Caster Tires	13" x 6.5" - 6" Pneumatic (33 x 16.5 - 15.2 cm)								13" x 6.5" - 6" Pneumatic (33 x 16.5 - 15.2 cm)				▶ 13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		
Fuel/Capacity	Gas/7-Gal (26.5 L)								Gas/7-Gal (26.5 L)				Gas/7-Gal (26.5 L)		
Digital Hour Meter	Standard								Standard				Standard		
Hydraulic Drive System	ZT-3400 Integrated Pumps & Wheel Motors								ZT-3400 Integrated Pumps & Wheel Motors				ZT-3400 Integrated Pumps & Wheel Motors		
Maximum Forward Speed	10 mph (16.1 km/h)								10 mph (16.1 km/h)				10 mph (16.1 km/h)		
Clutch	Electromagnetic								Electromagnetic				Electromagnetic		
<b>MOWING DECKS</b>															
Deck Size	48" (121.9 cm)		▶ 52" (132.1 cm)		▶ 60" (152.4 cm)				52" (132.1 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		
Cutting Deck	7-Gauge TURBO FORCE®								7-Gauge TURBO FORCE®				7-Gauge TURBO FORCE®		
Bullnose Bumper	Standard								Standard				Standard		
Rubber Discharge Chute	Standard								Standard				Standard		
Deck Lift Design	Lift Assist Spring								Lift Assist Spring				Lift Assist Spring		
Spindle Housings	8" (20.3 cm) Dia. Aluminum								8" (20.3 cm) Dia. Aluminum				8" (20.3 cm) Dia. Aluminum		
1" (2.5 cm) Spindle Shaft	Standard								Standard				Standard		
Spindle Bearings	Maintenance-Free								Maintenance-Free				Maintenance-Free		
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5" in .25" increments (3.8 - 12.7 cm in .6 cm increments)								Standard, 1.5" - 5" in .25" increments (3.8 - 12.7 cm in .6 cm increments)				Standard, 1.5" - 5" in .25" increments (3.8 - 12.7 cm in .6 cm increments)		
Deck Depth	5.5" (14.0 cm)								5.5" (14.0 cm)				5" (12.7 cm)		
Blades	.204" (.5 cm) Heat-Treated Steel								.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel		
Blade Tip Speed	18,500+ ft/min								18,500+ ft/min				18,500+ ft/min		
Belt Construction	Aramid Fiber V-Belt								Aramid Fiber V-Belt				Aramid Fiber V-Belt		
<b>FEATURES</b>															
<b>MyRIDE® Suspension System</b>									▶ MyRIDE Suspension System						
Comfort Platform	N/A		N/A		N/A		N/A						N/A		
Platform Travel	N/A		N/A		N/A		N/A		3.0" (7.6 cm)				N/A		
Shocks	N/A		N/A		N/A		N/A		1 center / 2 rear				N/A		
Seat	N/A		N/A		N/A		N/A		Deluxe Comfort				N/A		
Adjustability	N/A		N/A		N/A		N/A		5 Detents, Infinite Adjustability				N/A		
2" Hitch Receiver	Standard		Standard		Standard		Standard		Standard				Standard		
Steering Controls	1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened								1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened				1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened		
Operator Seat	Deluxe Suspension								Deluxe Comfort				Deluxe Suspension		
Folding ROPS	Standard								Standard				Standard		
Tool-Mounting Capability	Side Console / Rear Guard Ready								Side Console / Rear Guard Ready				Side Console / Rear Guard Ready		
Adjustable Turbo Force Baffles	Optional								Optional				Optional		
LED Lights	Standard								Standard				Optional		
USB Port	N/A								▶ Standard				N/A		
Step Through Floorpan	Standard								Standard				Standard		
Electric Deck Lift Assist	Optional								Optional				Optional		
Warranty**	4-Year 1000-Hour Limited								4-Year 1000-Hour Limited				4-Year 1000-Hour Limited		
<b>WEIGHTS AND MEASUREMENTS</b>															
Weight	870 lbs.	394.6 kg	890 lbs.	403.7 kg	920 lbs.	417.3 kg	1,036 lbs.	470 kg	1,012 lbs.	459 kg	1,036 lbs.	470 kg	920 lbs.	417.3 kg	
ROPS Height (Folded)	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	
Deck Clearance Width	53"	134.6 cm	56.75"	144.1 cm	63.5"	161.3 cm	64"	162.5 cm	56"	142.2 cm	64"	162.5 cm	63.5"	161.3 cm	
Deflector Width	63.25"	160.7 cm	67.25"	170.8 cm	75.25"	191.1 cm	75.23"	191.1 cm	68"	172.7 cm	75.23"	191.1 cm	75.25"	191.1 cm	
Length	82"	208.3 cm	82"	208.3 cm	83"	210.8 cm	82"	208.3 cm	84.25"	214 cm	82"	208.3 cm	83"	210.8 cm	

\* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. \*\*See your local Toro dealer or consult owners manual for complete warranty details.