



# TORO® DINGO® TX 427

COMPACT UTILITY LOADERS

The original tracked compact utility loaders, the Toro Dingo TX 427 delivers durability and reliability pros and do-it-yourselfers trust, combined with powerful performance and incredible versatility. For operators who are frequently switching tasks or moving things out of the way, these walk-behind models provide greater productivity due to the ability to walk up to the machine and go. In addition, with a walk-behind Dingo, operators don't feel the bumps when going over rough terrain.

## FEATURES

### LOW-IMPACT FOOTPRINT

Long-lasting, Kevlar® reinforced tracks disperse weight evenly for a light footprint on turf, while delivering better traction in sandy or wet ground conditions.



### HIGH-PERFORMANCE HYDRAULICS

The 4-pump hydraulic system directs power right where you need it. Operate the loader, bucket, traction and auxiliary drives at the same time for increased operator efficiency.

### EXCLUSIVE TX CONTROLS

Three simple controls let operators get to work fast:

- 1** Curl, dump or float the bucket while raising or lowering the loader arms with one hand using the joystick.
- 2** Grab the one-handed traction drive from any angle for effortless control.
- 3** Activate the auxiliary circuit control lever to power the attachments instantly.



# TORO® DINGO® TX 427

## SPECIFICATIONS

<b>TX 427 NARROW TRACK (MODEL 22321)</b>		
<b>ENGINE</b>	Engine	Kohler® Command Pro® 25 HP* (18.6 kw)
	Air Filter	Two-stage, heavy-duty, remote
	Cooling System	Air Cooled
	Fuel Tank	6.0 gallons (23 liters)
	Oil Capacity	2.0 quarts (2.95 liters)
<b>HYDRAULIC SYSTEM</b>	Hydraulic Pressure	3,000 PSI (20,684 kPa)
	Hydraulic Flow	Traction: 16.9 gpm (each pump) Auxiliary: 11.4 gpm
	Reservoir Capacity	10 gallons (37.8 liters)
<b>TRACKS</b>	Standard	Sprocket-drive, 10 road wheels per side
	Traction	Dual hydrostatic pump
<b>DIMENSIONS</b>	Track Dimensions	96.6" x 5.9" (245.3 cm x 14.9 cm)
	Wheelbase	31.2" (79.2 cm)
	Ground Clearance	4.6" (11.6 cm)
	Overall Dimensions (WxLxH) With Bucket	33.7" x 92" x 46.1" (85.5 x 233.6 x 117.0 cm)
	Overall Dimensions (WxLxH) Without Bucket	33.7" x 70.7" x 46.1" (86.5 x 179.5 x 117.0 cm)
	Maximum Operating Height	90.1" (228.8 cm)
	Hinge Pin Height	65.8" (167.1 cm)
	Dump Height	46.1" (117.0 cm)
	Dump Angle	38-degrees
	Reach - Fully Raised	21.8" (55.3 cm)
	Ground Speed	Fwd: 0–4.5 mph (0–7.2 km/h) Rev: 0–2.0 mph (0–3.2 km/h)
	Weight	1,882 lbs (853.6 kg)
	Rated Operating Capacity (35% of Tip Capacity)*	535 lbs. (242.6 kg)
	Ground Pressure	5.1 PSI

\*Per ISO 14397-1

