The comprehensive Toro product line-up has expanded with the addition of the 28-inch hydraulic drive brush cutter. This versatile machine is ideal for the rental industry, as performance, durability and usability are key elements in its design. The commercial grade, self-propelled brush cutter allows operators to level brush, tall weeds, saplings and heavy vegetation with ease. The Toro hydro drive brush cutter, featuring a pivoting deck, can handle brush up to six feet tall and saplings up to two inches in diameter.

FEATURES

QUALITY PERFORMANCE

- Larger fuel tank capacity combined with the 28 inch cutting deck increases operator productivity
- The flail blade can handle the toughest of jobs with increased cutting performance
- The pivoting deck makes for easy maneuvering over uneven terrain
- The standard hour meter keeps your machine up-to-date on service needs and back to work

DURABLE AND POWERFUL

- Superior product design, including a high-strength steel deck, 1 3/8 inch spindle shaft and large diameter pulleys optimizes the longevity of the machine
- Sealant-filled, aggressive tread tires provide effective traction for brush removal projects on slopes, ditches or culverts
- Standard electric start and a powerful 14.5 hp* Toro engine
- Improved electric clutch design holds-up against the force of blade impacts

EASY-TO-USE

- Simple, intuitive traction controls ensures both professional and novice operators alike will be able to master
- Two-step blade engagement, coupled with a parking brake enhances usability for the operator
- Knuckle guards and durable rubber deck flaps give added protection during brush removal
- Maneuver this powerful machine in both forward and reverse with one-hand control feature



SPECIFICATIONS

| | BRC-28 (23522) |
|--------------------|---|
| Cutting Width | 28" (71.1 cm) |
| Cutting Height | 3-3/4" (9.5 cm) |
| Engine* | Toro 14.5 hp* |
| Electric Start | Standard |
| Fuel Capacity | 1 gallon (3.7 L) |
| Deck | 50 ksi high strength steel Pivoting +/- 10 degrees w/spring return |
| Spindle Diameter | 1-3/8" (3.5 cm) |
| Transaxle | Hydrogear T2 |
| Dimensions (WxLxH) | 30" x 89" x 42" (76.2x 226.0 x 106.6 cm) |
| Weight | 375 lbs (170.0 kg) |

Brush cutter products are CARB exempt meeting EPA regulations

*The gross horsepower of this engine was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual horsepower on this class of product will be significantly lower.