

Z MASTER®

6000 SERIES

SEE PAGE 2 FOR BATTERY

REVOLUTION SERIES OPTIONS

OWN THE MOWER THAT OWNS EVERY JOB.



COMPATIBLE



The Z Master 6000 Series is one of our most advanced and most comfortable zero turn mowers.

6.3–7.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.



MYRIDE® SUSPENSION SYSTEM

The MyRIDE Suspension System features a rear shock adjustable operator platform that isolates bumps and vibrations.

Models 72967 and 72968 only. See pages 8-9 for details.



HORIZON™ TECHNOLOGY

Choose the performance mode to increase productivity and reduce fuel consumption.

Models 72969, 72946 and 72947 only.
See page 10 for details.



PRO RESULTS EVERY TIME

TURBO FORCE® 5.5" deep cutting decks feature 18,500+ ft./min. blade tip speed and nearly 1/4" thick heat-treated steel blades.



DECK LIFT ASSIST

Standard deck lift assist foot pedal allows operator to adjust the deck height quickly and easily.

ZMASTER® 6000 SERIES

	72926		72960		72965		72967		72946		72928		72961		72968		72947		72980		72982	
POWER SYSTEM																						
Commercial Engines at 3600 RPM*	26.5 hp Kohler® Command PRO EFI (747cc)		▶ 31 hp Kawasaki® FX (999cc)		▶ 38 hp Kohler Command PRO EFI (999cc)		26.5 hp Kohler Command PRO EFI (747cc)		▶ 38 hp Kohler Command PRO EFI (999cc)		31 hp Kawasaki FX (999cc)		▶ 38 hp Kohler Command PRO EFI (999cc)		▶ 37 hp Vanguard Oil Guard (993cc)							
Electric Start	Standard																					
Heavy-Duty Canister Air Cleaner	Standard																					
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)		▶ 24" x 12" – 12" Micheil® Tweels (61 x 30.5 – 30.5 cm)								24" x 12" – 12" (61 x 30.5 – 30.5 cm)								Super Turf 24" x 12" – 12" (61 x 30.5 – 30.5 cm)			
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)																					
Fuel/Capacity	Gas/12-Gal (45.4 L)																					
Hour Meter	Smart Hour Meter		Standard		▶ Horizon Technology		Smart Hour Meter		Standard		▶ Horizon Technology		Standard									
Hydraulic Drive System	Unitized Pumps & Wheel Motors																					
Pump	16cc/rev																					
Wheel Motor	17.1 cir																					
Maximum Forward Speed	11.5 mph (18.5 km/h)																					
Clutch	Electromagnetic																					
MOWING DECKS																						
Deck Size	60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		72" (182.9 cm)		72" (182.9 cm)		72" (182.9 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)	
Cutting Deck	7-Gauge TURBO FORCE®																					
Bullnose Bumper	Standard																					
Adjustable Discharge Baffle	Standard, Tools-Free																					
Rubber Discharge Chute	Standard																					
Deck Lift Design	Extension Spring																					
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum																					
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard																					
Spindle Bearings	Maintenance-Free																					
Cutting Height	1.0" – 5.5" (2.5 cm – 14 cm)																					
Blades	.204" (.5 cm) Heat-Treated Steel																					
Blade Tip Speed	18,500+ ft/min																					
Belt Construction	Aramid Fiber V-Belt																					
Anti-Scalp Rollers	4 Standard, 1 Optional																					
Carrier Frame Construction	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm)																					
FEATURES																						
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened																					
Operator Seat	Deluxe Suspension w/ 3-D Isolation Mounts		▶ MyRIDE Suspension System		Deluxe Suspension w/ 3-D Isolation Mounts		▶ MyRIDE Suspension System		Deluxe Suspension w/ 3-D Isolation Mounts													
Armrests	Standard																					
Seat Suspension System	Standard																					
Folding ROPS	Standard																					
Storage Compartment	Standard																					
Foot Pedal Deck Lift	Standard																					
Z Stand	Optional																					
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access																					
WEIGHTS AND MEASUREMENTS																						
Weight	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,370 lbs.	621.4 kg	1,289 lbs.	584.7 kg	1,350 lbs.	612.3 kg	1,334 lbs.	605.1 kg	1,440 lbs.	653.2 kg	1,369 lbs.	621 kg	1,447 lbs.	656 kg	1,644 lbs.	746 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	73.6"	186.9 cm	73.6"	186.9 cm	73.6"	186.9 cm	73.6"	186.9 cm	61.7"	156.7 cm	73.6"	186.9 cm
Deflector Width	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	87.6"	222.5 cm	87.6"	222.5 cm	87.6"	222.5 cm	87.6"	222.5 cm	75.7"	192.3 cm	87.6"	222.5 cm
Length	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	86.1"	218.7 cm	86.1"	218.7 cm	86.1"	218.7 cm	86.1"	218.7 cm	83.1"	211.1 cm	86.1"	218.7 cm

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.