ULTRA BUGGY® e2500-TS

TRACKED SWIVEL MATERIAL BUGGY

ELECTRIC POWERED

Electric Precision for Tight Job Sites

For interior and exterior jobs where placement accuracy matters, the Ultra Buggy e2500-TS helps crews move and dump materials with control. Electric operation produces no engine exhaust emissions, making it suitable for indoor environments. The swivel tub supports precise placement while the compact footprint fits doorways and tight paths, helping crews reduce rework, maintain flow, and complete material handling tasks efficiently.

Key Specifications

- 2,500 lbs carrying capacity
- 14 cu. ft. tub volume
- 180° dump radius
- Up to 8 hours of continuous runtime
- 31.5" width





INTERIOR-READY POWER

Electric operation eliminates engine exhaust, noise, and fuel smell, making it well-suited for indoor environments.



PRECISE MATERIAL DUMPING

Swivel placement helps crews dump accurately with less hand finishing.



FITS TIGHT PATHS

Compact footprint supports movement through doorways and narrow access paths.

ULTRA BUGGY® e2500-TS

TRACKED SWIVEL MATERIAL BUGGY

ELECTRIC POWERED

ULTRA BUGGY e2500-TS SPECIFICATIONS

MODEL 68140

BATTERY

Chemistry	Toro® HyperCell® Lithium Ion
Capacity	13.2 kWh
Fuel Type	Electric
Run Time[1]	up to 8 hours

CHARGING

Charging Type	3.3 kW at 240 V Optional 120V cord available.[2]
Charging Time (80%, 100%)	3.2 hrs at 240 Vac, 5.5 hrs at 240 Vac

TRACKS

Track Type	Rubber w/ Nylon fabric and Aramid Corde
Wheelbase	35 in. (88.9 cm)
Track Width	5.9 in. (15 cm)

DIMENSIONS

Dimensions, Platform Down (L×W×H)	100.7 x 31.5 x 52.2 in. (255.8 x 80 x 132.5 cm)
Dimensions, Platform Up (L×W×H)	87.7 x 31.5 x 52.2 in. (222.8 x 80 x 132.5 cm)
Tub Volume	14 cu. ft. (0.4 m^3)
Max Load Capacity, Standard Dump Height	2,500 lbs (1,134 kg)
Ground Speed, Platform Down (Forward/Reverse)	5 mph (8 kph) / 3.1 mph (5 kph)
Ground Speed, Platform Up (Forward/Reverse)	2.6 mph (4.2 kph) / 1.5 mph (2.4 kph)
Weight	2,107 lbs (955.6 kg)
Distributed Floor Pressure (Loaded/Unloaded)	1.45 psi / 0.66 psi
Discharge Height	15 in. (38.1 cm)

[1]Run time may vary based upon conditions.
[2]Charging time will double with the use of the 120 V cord.

©2026 The Toro Company Part No. 2026-0012 | toro.com
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.