

**TORO**

# TURF RENOVATION EQUIPMENT



# AERATORS

STAND-ON



## BUILT FOR PRODUCTIVITY.

---

Toro's stand-on aerators ensure your customers have the right tool for their aeration task. From the unibody frames to the high-carbon, heat-treated spring steel blades, every product is built tough for heavy rental use.



### 30" STAND-ON AERATOR

The 30" stand-on model boasts a Kawasaki V-Twin engine and a hydraulic system that can be finely tuned to pull any length of plug on the fly. Electronic foot pedal controls also allow the operator to raise and lower the tines instantly for quick zero-turn maneuvers. And the floating operator platform isolates the operator from vibrations for an exceptionally smooth ride.

- 30" width at speeds up to 7.5 mph
- Raise and lower tines with foot pedal
- Fuel capacity extends operating time

### 24" STAND-ON AERATOR

Designed with a focus on maneuverability, the 24" model fits through standard 36-inch gates, making quick work of any size aeration project for rental store customers. Reaching ground speeds of up to 6.5 mph, the new 24-inch stand-on aerator optimizes power and hydraulics to ensure consistent core depths regardless of terrain.



# SLIT SEEDER

HYDRAULIC



## DURABLE AND EASY TO MANEUVER.

The 20" hydraulic slit seeder is the perfect tool for landscape contractors or homeowners with user-friendly controls, durable construction, and maneuverability to make overseeding an easy task.

- Solid, high-carbon, heat-treated spring steel blades can handle abuse without chipping or bending and effectively verticut into the top thatch layer to improve turf health and ensure seed-to-soil contact.
- Larger seed hoppers and seed flow that can be adjusted on the fly ensure productivity and ease-of-use in any application.



### 20" HYDRAULIC SLIT SEEDER

Durable, lightweight and easy to use, Toro slit seeders handle like a self-propelled push mower. Operators can make a tight turn — even on hills — with one hand. And the variable-speed drive system operates in forward and reverse. For maximum durability, they're constructed of solid 11-gauge steel with high-carbon, heat-treated spring steel blades.



### DURABLE CUTTING BLADES.

Blades are made of high-carbon, heat-treated spring steel that can handle abuse without chipping or bending.



The seed flow rate can be adjusted on the fly for different applications and seed types.

# POWER BROOM



## INNOVATIVE AND MULTI-PURPOSE.

From brushing away snow to clearing debris and dethatching grass, this multi-purpose, walk-behind broom has you covered for year-round use. Its innovative features allow for the high performance and ease of use that you expect from Toro.

- Patented commercial power steering offers effortless maneuverability with the pull of a trigger
- Variable speed technology - 6 forward and 2 reverse speeds with shift-on-the-fly transmission
- Independent control levers allow simultaneous engagement of ground drive and broom for easy handling
- Kohler® Command Pro Multi Season engine - air intake rotates at 180 degrees for multi-season use





## BRUSH CUTTER

### HANDLE THE TOUGHEST OF JOBS WITH INCREASED CUTTING PERFORMANCE.

The comprehensive Toro product line-up has expanded with the addition of the 28-inch hydraulic drive brush cutter. This versatile machine is ideal for the rental industry, in addition to landscape contractors, as performance, durability and usability are key elements in its design. The commercial grade, self-propelled brush cutter allows operators to level brush, tall weeds, saplings and heavy vegetation with ease. The Toro hydro drive brush cutter, featuring a pivoting deck, can handle brush up to six feet tall and saplings up to two inches in diameter.

#### QUALITY PERFORMANCE

- The flail blade can handle the toughest of jobs with increased cutting performance
- Larger fuel tank capacity combined with the 28 inch cutting width increases operator productivity

#### DURABLE AND POWERFUL

- Standard electric start and a powerful 14.5 hp Toro engine\*
- Superior product design, including a high-strength steel deck, 1 3/8 inch spindle shaft and large diameter pulleys optimizes the longevity of the machine

#### EASY-TO-USE

- Simple, intuitive traction controls ensures both professional and novice operators alike will be able to master

\*The gross horsepower of this engine was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual horsepower on this class of product will be significantly lower.

Your local Toro dealer offers a complete selection of Toro equipment,  
as well as genuine Toro parts and service from knowledgeable technicians.



MODEL	24" STAND-ON AERATOR	30" STAND-ON AERATOR
Engine	Kohler® CH440	Kawasaki FS541V, V-Twin
Fuel Capacity	1.85 gallons (7 L)	5 gallons (19 L)
Working Width	24" (60.9 cm)	30" (76.2 cm)
Depth	Up to 5" (12.7 cm)	Up to 5" (12.7 cm)
Width	35.5" (90.2 cm)	48" (121.9 cm)
Height	51" (129.5 cm)	53" (134.6 cm)
Length	68.6" (174.2 cm)	65" (165.1 cm)
Weight	856 lbs (388.2 kg)	1,015 lbs (460.3 kg)
Ground Speed	Up to 6.8 mph (10.9 km/h)	7.5 mph (12.0 km/h) fwd 2.2 mph (3.5 km/h) rev
Coverage (Per Hour)	1.7 Acre	2.1 Acre
Tines	36	48

MODEL	20" HYDRAULIC SLIT SEEDER
Engine	Subaru® EX27
Fuel Capacity	1.6 gallons (6.0 L)
Working Width	20" (50.8 cm)
Depth	Up to 1" (2.5 cm)
Width	30" (76.2 cm)
Height	28" (handle folded) 45" (handle working)
Length	27" (71.1 cm) handle folded 52" (114.3 cm) handle working
Weight	260 lbs (117.9 kg)
Ground Speed	3 mph (4.8 km/h) fwd 2.2 mph (3.5 km/h) rev
Seed Hopper Capacity	40 lbs (18.1 kg)
Blades	10 verticutting blades

MODEL	36" WALK-BEHIND POWER BROOM
Transmission	Friction disc
Steering	Power steering with clutch left & right hand
Fuel Capacity	1.05 gallons (4 L)
Broom Angle	40° total - 20° left /20° right
Broom Width	36" (91.4 cm) with 18 wafers
Broom Diameter	25" (63.5 cm)
Broom Sped	200 RPM
Broom Drive	Direct
Weight	350 lbs (158.7 kg)
Starter	Recoil
Tires	15" x 5" (38.1 cm x 12.7 cm)

All walk-behind machines comply with ANSI safety standards: B71.4 for commercial turf care equipment or B71.8 for OPE walk-behind ground-engaging equipment. Core and cutting depth vary depending on ground conditions.

MODEL	BRUSH CUTTER BRC-28
Cutting Width	28" (71.1 cm)
Cutting Height	3.75" (9.5 cm)
Engine*	Toro 14.5 hp
Electric Start	Standard
Fuel Capacity	1 gallon (3.7 L)
Deck	50 ksi high strength steel Pivoting +/- 10 degrees w/ spring return
Spindle Diameter	1.375" (3.5 cm)
Transaxle	Hydrogear T2
Dimensions (WxLxH)	30" x 89" x 42" (76.2 x 226.0 x 106.6 cm)
Weight	375 lbs (170.0 kg)

Brush cutter products are CARB exempt meeting EPA regulations



toro.company



TheToroCompany



TheToroCompany



youtube.com/toro

toro.com / toro.ca

490-0094\_rev2

© 2023 The Toro Company, Bloomington, MN 55420  
All rights reserved. Printed in the USA.

\*The gross horsepower of this engine was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual horsepower on this class of product will be significantly lower.  
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.

SPECIFICATIONS