

TURF RENOVATION

SPRAYMASTER



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE



MAXIMUM OF
4.0 Acres
COVERED PER HOUR



Get the job done better, faster
and easier with the Stand-On SprayMaster.

The updated design creates more stability and
balance resulting in less turf tear up and the flip up
hopper allows for easy maintenance. Maximize ground
coverage and reduce fill-up stops with two spray tanks
with up to 60-gallon capacity, 250-pound hopper and
5-gallon fuel tank.

	LEAN-TO-STEER SPREADER/SPRAYER	SPRAYMASTER 24 GALLON STAND-ON	SPRAYMASTER 40 GALLON STAND-ON	SPRAYMASTER 60 GALLON STAND-ON
	34230	34246	34242	34240
POWER AND DRIVE SYSTEM				
Engine*	Kohler® 9.5 hp	16 hp Twin Vanguard	▶ 21 hp Twin Vanguard	
Engine Orientation	Horizontal			
Fuel Capacity	Gas/1.85 Gal (7 L)		5 Gal (18.9 L) w/fuel gauge	
Electric Start	Yes	Yes	Yes	Yes
Transmission	Hydrostatic			
Maximum Forward Speed	5.5 mph (8.6 km/h)	7 mph (11.3 km/h)	▶ 10 mph (16.1 mph)	10 mph (16.1 mph)
SPREADER SYSTEM				
Hopper Size	175 lbs (79.4 kg)	150 lbs (68.0 kg)	▶ 250 lbs (113.4 kg)	250 lbs (113.4 kg)
Fertilizer Capacity	225 lbs (102.1 kg)		2 Rear Boxes - 50 lbs (22.7 kg) each	
Spread Width	Adjustable from 4'-22' (1.2 - 6.7 m)		Adjustable from 3'- 25' (0.9 - 7.6 m)	
Deflector Shield	Molded Plastic	Molded Plastic	Molded Plastic	Molded Plastic
Spinner Motor	Electric	Electric	Electric	Electric
SPRAY SYSTEM				
Pump Capacity	5 GPM		5.3 GPM	
Spray Capacity	20 Gal	24 Gal (2 - 12 Gal)	▶ 40 Gal (2 - 20 Gal)	▶ 60 Gal (2 - 30 Gal)
Spray Width	4 or 10 ft (1.2 or 3.0 m)		2, 4, 6 or 8 ft (0.6, 1.2, 1.8 or 2.4 m)	▶ 2, 4, 6, 8 or 10 ft (0.6, 1.2, 1.8, 2.4 or 3.0 m)
Boom	N/A		3-Section, Bi-Directional Breakaway Wings	
Spot Spray Hose	15 ft (4.6 m) Coil Hose	15 ft (4.6 m) Coil Hose	▶ 75 ft (22.9 m) Hose Reel	
WEIGHTS AND MEASUREMENTS				
Weight	500 lbs. (226.8 kg)	698 lbs. (316.7 kg)	896 lbs. (406.4 kg)	912 lbs. (413.7 kg)
Height	51.5" (130.8 cm)	48" (121.9 cm)	50" (127.0 cm)	50" (127.0 cm)
Width	35.5" (90.2 cm)	36" (91.4 cm)	46" (116.8 cm)	52" (132.1 cm)
Length	67.5" (171.5 cm)	70.5" (179.1 cm)	73" (185.4 cm)	72" (182.9 cm)

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature



FILL UP HOPPER.
Maintenance is a breeze
with the flip up hopper
that provides easy
access to the engine.



LARGE CAPACITY.
Maximize ground
coverage and reduce
fill-up stops with two
spray tanks that hold up
to 60 gallons, 250-pound
hopper capacity, and a
5-gallon fuel tank.



RIDE IN STYLE.
The new design allows
for increase balance and
stability and features
larger wheels, improved
hopper cover, and custom-
stitched knee pad.

GET TWICE THE PRODUCTIVITY of a 21" walk-behind aerator with the new 24" stand-on model. Built for the demands of busy landscape contractors, it packs the power of a larger model in a smaller footprint so you can maneuver with ease. Now you can reach areas that could previously only be accessed by a walk-behind unit, saving time on projects both large and small.

MANEUVER IN TIGHT SPACES with a compact design that fits through a standard 36" gate.

NAVIGATE WITH EASE with intuitive controls that function a lot like a mower, saving time.

GET A SMOOTH RIDE with the floating operator platform that isolates vibrations.

KEEP CONTROL EASY with a foot pedal to raise and lower tines.

VARY PLUG LENGTH ON THE FLY by finely tuning the hydraulic system. It applies up to 1,200 lbs of down pressure on the tines to pull up to 5" cores.



TURF RENOVATION

24" & 30" STAND-ON AERATOR

HEALTHY TURF STARTS HERE.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE



CONSISTENT POWER

Electronic depth control optimizes power and hydraulics, ensuring consistent core depths on any terrain. Hydraforce valve adjusts operator weight.



INTUITIVE CONTROLS

All necessary functions are at the operator's fingertips, including depth control with supervisor maximum-depth lockout, maintenance reminders and tine activation lockout.



CONVENIENT SERVICE

Engine and other common service components are easy to access for quick maintenance.

	24" Stand-On Aerator (61 cm)	30" Stand-On Aerator (76.2 cm)		
	39514†	39521†		
POWER SYSTEM				
Engine	Kohler® CH 440	▶ Kawasaki® FS541V V-Twin		
Fuel/Capacity	Gas/1.85 Gal (7 L)	▶ Gas/5 Gal (18.9 L)		
Maximum Forward Speed	Up to 6.8 mph (11.3 km/h) fwd, 2.2 mph (3.5 km/h) rev	▶ Up to 7.5 mph (12.1 km/h) fwd, 2.2 (3.5 km/h) mph rev		
CAPACITIES				
Coverage (Per Hour)	1.5 Acres	▶ 2.0 Acres		
Working Width	24" (60.9 cm)	▶ 30" (76.2 cm)		
Tines	36	▶ 48		
Aerating Width	24" (60.9 cm)	▶ 30" (76.2 cm)		
WEIGHT AND MEASUREMENTS				
Weight	856 lbs.	388 kg	1,015 lbs.	460.4 kg
Height	51.02"	129.6 cm	53"	134.6 cm
Width	35.5"	90.2 cm	48"	121.9 cm
Length	68.62"	174.3 cm	65"	165.1 cm

[†]CARB compliant model.

▶ = Step Up Feature