Multi Pro® WM

200-GALLON SPRAYER ACCESSORY
WORKMAN HD SERIES

FEATURES

- **Six Diaphragm Pump** – *An Industry Exclusive – this oversized pump satisfies the highest spray rates while simultaneously supplying generous agitation flow*

- **200 gal (757 L) Elliptical Chemical Tank** – *Thoughtfully designed polyethylene tank has no shelves or corners for chemical to stick on, which helps ensure a 99% spray out.*

- **Sprayer Control Console** – *InfoCenter,™ pressure gauge and sprayer control switches are all located in a unique console featuring Toro's exclusive 'Quick Find™' feature which intuitively helps the operator find boom and actuator switches on the console without looking at them.*

- **Rugged Triangular Spray Boom** – *Standard three section, 18.5' (5.6 m) boom width provides fore and aft breakaway on impact while protecting nozzles. Raises into a crisscross position for storage and transportation. Optional 20.5' (6.25 m) boom width extension kit available.*

Precise spray control for a Workman® vehicle.

The Multi Pro WM spray system for Toro's Workman® HD Series utility vehicles leverages the advanced spray system capability of Toro's Multi Pro line and combines functionality with cutting-edge and intuitive sprayer controls. The result is the most advanced, efficient and accurate 200-gallon bed-mounted sprayer accessory for a utility vehicle on the market. Aggressive agitation, faster response times, consistent and accurate application rates, and intuitive rate set up, makes this the sprayer that has it all.



©2026 The Toro Company. All rights reserved. Rev. 11/26

Call your Toro distributor at 800-803-8676

Multi Pro® WM – 200-Gallon Sprayer Specifications*

	SPRAYER SPECIFICATIONS
SOLUTION TANK	High-density, impact-resistant polyethylene with large 16" (41 cm) fill opening, tapered bottom and sump with drain.
RATED CAPACITY	200 gallons (757 liters).
SPRAY PUMP	Hardi 364/10.0, 6-diaphragm positive displacement pump w/1" (2.5 cm) input shaft; input speed 0~540 rpm; Flow rate 45 gpm (170.3 lpm) @ 40 psi (540 rpm).
AGITATOR	4, side- mounted jet agitation nozzles for full tank agitation.
CONTROLS	Spray pump control switch, agitator jet switch, rate switch, individual boom On/Off switches, boom actuator switches, indicator lights on pump, agitation and boom switches, throttle lock.

	OPEN BOOMS (STANDARD)
BOOM ASSEMBLY	18.5' (5.6 m) three section, triangular truss style open booms. Optional 20.5' (6.25 m) booms available.
BOOM ACTUATORS	Heavy Duty hydraulic lift actuators with nitro-steel plated shafts; 1-3/4" Bore x 10.06" Stroke.
SPRAY NOZZLES	Eleven nozzle turrets, triple turret-mount, quick-disconnect with diaphragm check valves. Twelve nozzle turrets with optional kit.



	MULTI PRO WM ACCESSORIES
PRO FOAM™ MARKING KIT	Foam dollops ensure accurate parallel path tracking. Select foam for either boom or both.
PRO FOAM	1 gallon (3.8 L) bottle of Pro Foam Concentrate.
CLEANLOAD™ EDUCTOR KIT	This on-board mixing station allows rapid and safe loading of any chemical without the need to first mix into a slurry Incorporates a built-in bottle wash nozzle and has an optional suction lance to pull in powdered or liquid products from their container. Stores within the width of the machine.
FRESH WATER RINSE KIT	Simplifies and automates the triple-rinse process, saving hours and hours of clean up time.
ELECTRIC HOSE REEL KIT	150' (45.7 m) of hose for hand or walk spraying applications. Convenient electric powered rewind. Spray gun has an adjustable nozzle from stream to fan.
PRO FOAM™ MARKING KIT	Foam dollops ensure accurate parallel path tracking. Select foam independently or both simultaneously.
ULTRA SONIC BOOM™ KIT	New sonar sensors automatically maintain proper spray height over undulating turf.
COVERED BOOM KIT	Extends 12" (30.5 cm) below the boom to minimize chemical drift in breezy conditions while retaining full boom system functionality.
AIR INDUCTION TURBO TWIN JET NOZZLES	Exclusive to Toro in the 0.8 gpm (3.02 lpm), 1.0 gpm (3.79 lpm) and 1.5 gpm (5.68 lpm) sizes, for exceptional contact coverage.
CONTACT & SYSTEMIC NOZZLES	Select the right nozzle for your application by using the new **Multi Pro Nozzle Selection Brochure** - available via Toro.com

WARNING
THE WORKMAN® IS AN OFF-HIGHWAY VEHICLE, AND IS NOT DESIGNED, EQUIPPED, OR MANUFACTURED FOR USE ON PUBLIC STREETS, ROADS OR HIGHWAYS.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual Products offered for sale may vary in use, design, requirements and safety features. Consult your local Toro Distributor. "Cushman" is a registered trademark of Ransomes.

GeoLink® Spray Specifications*

	TOPCON AGS-2 RECEIVER
DIMENSIONS (H x W x D)	2.1" (53 mm) x 5.2" (130.5 mm) x 5.4" (136.5 mm)
POSITIONING SYSTEM	Real-time Kinematic (RTK). Optional PPP (Precise Point Positioning) as fallback for RTK
CONSTELLATIONS	GPS, GLONASS, GALILEO, BeiDou, QZSS
POWER	9-28 VDC
COMPLIANCE	J1939 and ISO11783
WEATHER RESISTANCE	Achieved IP69K rating

	TOPCON XD+ DISPLAY
DISPLAY	12.1" (307mm) 1280 x 800 px. TFT Color Graphic LCD with LED backlight
DIMENSIONS	8.4" x 13" (214 mm x 330 mm)
POWER	9V - 36V input (voltage and polarity protected).
OPERATING SYSTEM	Linux with icon-based GeoLink Spray software. NXP I.MX6®, quad core, 1GHz processor, Mass storage: 8GB, RAM: 1GB
FEATURES	Machine-to-machine communication, multiple inclusion zones, easy and standard modes, configurable with multi-view capabilities, interactive keypad, on-demand mini views and expandable views, 28 languages, rear-facing speaker, multiple application control, ISO UT ready, remote capable.
WEATHER RESISTANCE	Achieved IP67 rating

	ACCESSORIES
GEOLINK® STEER	GeoLink Spray reference Exclusively available for the Multi Pro 5800 (Model 41394) with GeoLink Spray. GeoLink Steer enables autosteer, ensuring the optimal next pass is followed and providing the most efficient use of your sprayer. Antenna kit.

Key Benefits of GeoLink Spray:

- Universal CL-55 cellular modem, capable of connecting to multiple cellular providers
- Use multiple machines for a single job with Machine-to-Machine communication
- Software for turf, not agriculture
- Repeatable sub-inch location accuracy
- Flexible, customizable and easy to use
- Intuitive icon-based menus
- Multiple inclusion zones – group like areas into a single job
- Improved consistency – less dependence on operator skill level

RTK: Real Time Kinematic (RTK) satellite correction is a technique used to enhance the precision of position data derived from satellite-based positioning systems, being usable in conjunction with all positioning platforms.





GeoLink Spray individual nozzle control saves time and money.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.