

# Z MASTER<sup>®</sup>

6000 SERIES

SEE PAGE 2 FOR BATTERY  
REVOLUTION SERIES OPTIONS

# OWN THE MOWER THAT OWNS EVERY JOB.



**HORIZON360**  
CONTRACTOR BUSINESS SOFTWARE

**COMPATIBLE**



ZMASTER <sup>®</sup> 6000 SERIES														
MyRIDE <sup>®</sup> SUSPENSION SYSTEM														
	72926		72960		72965 <i>LIMITED QUANTITY</i>		72967		72968		72928		72961	
<b>POWER SYSTEM</b>														
Commercial Engines at 3600 RPM*	26.5 hp Kohler <sup>®</sup> Command PRO EFI (747cc)				▶ 31 hp Kawasaki <sup>®</sup> FX (999cc)				26.5 hp Kohler Command PRO EFI (747cc)				31 hp Kawasaki FX (999cc)	
Electric Start	Standard													
Heavy-Duty Canister Air Cleaner	Standard													
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)				▶ 24" x 12" – 12" Michelin <sup>®</sup> Tweets (61 x 30.5 – 30.5 cm)				24" x 12" – 12" (61 x 30.5 – 30.5 cm)					
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)													
Fuel/Capacity	Gas/12-Gal (45.4 L)													
Hour Meter	Standard													
Hydraulic Drive System	Unitized Pumps & Wheel Motors													
Pump	16cc/rev													
Wheel Motor	17.1 cir													
Maximum Forward Speed	12 mph (19.3 km/h)													
Clutch	Electromagnetic													
<b>MOWING DECKS</b>														
Deck Size	60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		72" (182.9 cm)		72" (182.9 cm)		72" (182.9 cm)	
Cutting Deck	7-Gauge TURBO FORCE <sup>®</sup>													
Bullnose Bumper	Standard													
Adjustable Discharge Baffle	Standard, Tools-Free													
Rubber Discharge Chute	Standard													
Deck Lift Design	Extension Spring													
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum													
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard													
Spindle Bearings	Maintenance-Free													
Cutting Height	1.0" – 5.5" (2.5 cm – 14 cm)													
Blades	.204" (.5 cm) Heat-Treated Steel													
Blade Tip Speed	18,500+ ft/min													
Belt Construction	Aramid Fiber V-Belt													
Anti-Scalp Rollers	4 Standard, 1 Optional													
Carrier Frame Construction	3" x 1.5" – 10-Gauge (7.6 x 3.8 cm)													
<b>FEATURES</b>														
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened													
Operator Seat	Deluxe Suspension w/ 3-D Isolation Mounts				▶ MyRide <sup>®</sup> Suspension System				Deluxe Suspension w/ 3-D Isolation Mounts					
Armrests	Standard													
Seat Suspension System	Standard													
Folding ROPS	Standard													
Storage Compartment	Standard													
Foot Pedal Deck Lift	Standard													
Z Stand	Optional													
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access													
Flip Up Seat	Standard													
Warranty	5 Years or 1,400 Hours													
<b>WEIGHTS AND MEASUREMENTS</b>														
Weight	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,254 lbs.	568.8 kg	1,370 lbs.	621.4 kg	1,289 lbs.	584.7 kg	1,350 lbs.	612.3 kg	1,334 lbs.	605.1 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	64"	162.5 cm	64"	162.5 cm	61.7"	156.7 cm	64"	162.5 cm	76"	193.0 cm	76"	193.0 cm	76"	193.0 cm
Deflector Width	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	88"	223.5 cm	87.6"	222.5 cm	87.6"	222.5 cm
Length	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	86"	218.4 cm	86.1"	218.7 cm	86.1"	218.7 cm



### MYRIDE® SUSPENSION SYSTEM

The MyRIDE Suspension System features a rear shock adjustable operator platform that isolates bumps and vibrations.

Models 72967 and 72968 only. See pages 8-9 for details.



### HORSEPOWER OPTIONS

Choose the level of power in your machine with high horsepower and engine options.



### PRO RESULTS EVERY TIME

TURBO FORCE® 5.5" deep cutting decks feature 18,500+ ft./min. blade tip speed and nearly 1/4" thick heat-treated steel blades.



### DECK LIFT ASSIST

Standard deck lift assist foot pedal allows operator to adjust the deck height quickly and easily.

ZMASTER® 6000 SERIES								
	72976		72977		72981		72983	
<b>POWER SYSTEM</b>								
Commercial Engines at 3600 RPM*	▶ 38 hp Kohler Command PRO EFI (999cc)				▶ 37 hp Vanguard EFI (993cc) ETC Oil Guard			
Electric Start					Standard			
Heavy-Duty Canister Air Cleaner					Standard			
Drive Tires	24" x 12" – 12" (61 x 30.5 – 30.5 cm)				Super Turf 24" x 12" – 12" (61 x 30.5 – 30.5 cm)			
Caster Tires					13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)			
Fuel/Capacity					Gas/12-Gal (45.4 L)			
Hour Meter					Standard			
Hydraulic Drive System					Unitized Pumps & Wheel Motors			
Pump					16cc/rev			
Wheel Motor					17.1 cir			
Maximum Forward Speed					12 mph (19.3 km/h)			
Clutch					Electromagnetic			
<b>MOWING DECKS</b>								
Deck Size	60" (152.4 cm)		▶ 72" (182.9 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)	
Cutting Deck					7-Gauge TURBO FORCE®			
Bullnose Bumper					Standard			
Adjustable Discharge Baffle					Standard, Tools-Free			
Rubber Discharge Chute					Standard			
Deck Lift Design					Extension Spring			
Spindle Housings					9" (22.9 cm) Diameter Cast Aluminum			
1" (2.5 cm) Heavy-Duty Spindle Shaft					Standard			
Spindle Bearings					Maintenance-Free			
Cutting Height					1.0" – 5.5" (2.5 cm – 14 cm)			
Blades					.204" (.5 cm) Heat-Treated Steel			
Blade Tip Speed					18,500+ ft/min			
Belt Construction					Aramid Fiber V-Belt			
Anti-Scalp Rollers	4 Standard, 1 Optional				▶ 6 Standard, 1 Optional			
Carrier Frame Construction					3" x 1.5" – 10-Gauge (7.6 x 3.8 cm)			
<b>FEATURES</b>								
Steering Controls					1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened			
Operator Seat					Deluxe Suspension w/ 3-D Isolation Mounts			
Armrests					Standard			
Seat Suspension System					Standard			
Folding ROPS					Standard			
Storage Compartment					Standard			
Foot Pedal Deck Lift					Standard			
Z Stand					Optional			
Floor Pan					Pierced, Extruded Tread; No-Tools Deck Access			
Flip Up Seat					Standard			
Warranty					5 Years or 1,400 Hours			
<b>WEIGHTS AND MEASUREMENTS</b>								
Weight	1,440 lbs.	653.2 kg	1,369 lbs.	621 kg	1,447 lbs.	656 kg	1,644 lbs.	746 kg
ROPS Height (Folded)	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm	46.8"	118.9 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	64"	162.5 cm	76"	193.0 cm	61.7"	156.7 cm	76"	193.0 cm
Deflector Width	76"	193.0 cm	87.6"	222.5 cm	75.7"	192.3 cm	87.6"	222.5 cm
Length	83"	210.8 cm	86.1"	218.7 cm	83.1"	211.1 cm	86.1"	218.7 cm

\* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.