

# Z MASTER<sup>®</sup>

5000 SERIES  
REAR DISCHARGE

SEE PAGE 2 FOR BATTERY  
**REVOLUTION** SERIES OPTIONS

**NEED A PRODUCTIVITY EDGE?**  
Our rear discharge models let operators trim on either side of the deck while keeping sidewalks and flowerbeds clipping-free.

**SAVE TIME AND CLEANUP** with the rear discharge deck design that drops clippings within the path of the mower.

**GAIN FUEL EFFICIENCY** with Kohler<sup>®</sup> Command PRO<sup>®</sup> engines featuring electronic fuel injection (EFI).

 **HORIZON360<sup>®</sup>**  
CONTRACTOR BUSINESS SOFTWARE

**COMPATIBLE**



## **MICHELIN<sup>®</sup> TWEELS<sup>®</sup> AIRLESS RADIAL TURF TIRES**

No maintenance, no compromise, no downtime. Compatible with many models - now including CASTER options!



## 5.5–6.5 MAXIMUM ACRES PER HOUR

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



### REAR DISCHARGE

Two blades rotate clockwise and one blade rotates counter-clockwise to spread clippings evenly through the rear discharge tunnel, saving time and cleanup.



### ANTI-SCALPING SYSTEM

Durable, adjustable side bumpers protect the mower while enhancing deck flotation over uneven surfaces.



### RUGGED PERFORMANCE

Highly productive in taller grass and weed conditions.

Products shown are for representation only. Model year 2021 Z-Master 5000 Rear Discharge units come standard with Michelin® Tweel turf tires.

## ZMASTER® 5000 SERIES

	72907†	72921† LIMITED QUANTITY	72922†	72923†	72953†	72956
<b>POWER SYSTEM</b>	<b>NEW</b>			<b>NEW</b>	<b>NEW</b>	<b>NEW</b>
Commercial Engines at 3600 RPM*	25 hp Kohler Command PRO EFI (747cc)	25 hp Kohler Command PRO EFI (747cc)	26.5 hp Kohler Command PRO EFI (747cc)	25 hp Kohler Command PRO EFI (747cc)	25 hp Kohler Command PRO EFI (747cc)	26.5 hp Kohler Command PRO EFI (747cc)
Starter	Electric	Electric	Electric	Electric	Electric	Electric
Heavy-Duty Canister Air Cleaner	Standard	Standard	Standard	Standard	Standard	Standard
Drive Tires	23" x 9.5" – 12" Turfmaster (58.4 x 24.1 – 30.5 cm)	24" x 12" – 12" Michelin® Tweels (61 x 30.5 – 30.5 cm)	24" x 12" – 12" Michelin® Tweels (61 x 30.5 – 30.5 cm)	24" x 12" – 12" Michelin® Tweels (61 x 30.5 – 30.5 cm)	24" x 12" – 12" Turfmaster (61 x 30.5 – 30.5 cm)	24" x 12" – 12" Turfmaster (61 x 30.5 – 30.5 cm)
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)
Fuel/Capacity	Gas/12-Gal (45.4 L)	Gas/12-Gal (45.4 L)	Gas/12-Gal (45.4 L)	Gas/12-Gal (45.4 L)	Gas/12-Gal (45.4 L)	Gas/12-Gal (45.4 L)
Hour Meter	Smart Hour Meter	Smart Hour Meter	Smart Hour Meter	Smart Hour Meter	Smart Hour Meter	Smart Hour Meter
Hydraulic Drive System	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors	Unitized Pumps & Wheel Motors
Pump	12cc/rev (shock valves)	12cc/rev (shock valves)	12cc/rev (shock valves)	12cc/rev (shock valves)	12cc/rev (shock valves)	12cc/rev (shock valves)
Wheel Motor	14.6 cir	14.6 cir	14.6 cir	14.6 cir	14.6 cir	14.6 cir
Maximum Forward Speed	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)	10 mph (16.1 km/h)
Clutch	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic	Electromagnetic
<b>MOWING DECKS</b>						
Deck Size	52" (132.1 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)	60" (152.4 cm)	60" (152.4 cm)	52" (132.1 cm)
Cutting Deck	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE Rear Discharge	7-Gauge TURBO FORCE Rear Discharge	7-Gauge TURBO FORCE Rear Discharge	7-Gauge TURBO FORCE	7-Gauge TURBO FORCE
Bullnose Bumper	Standard	Standard	Standard	Standard	Standard	Standard
Deck Lift Design	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring	Extension Spring
Spindle Housings	9" (22.9 cm) Diameter Cast Aluminum	9" (22.9 cm) Diameter Cast Aluminum	9" (22.9 cm) Diameter Cast Aluminum	9" (22.9 cm) Diameter Cast Aluminum	9" (22.9 cm) Diameter Cast Aluminum	9" (22.9 cm) Diameter Cast Aluminum
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard	Standard	Standard	Standard	Standard	Standard
Spindle Bearings	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free	Maintenance-Free
Cutting Height	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)	1.0" – 5.5" (2.5 – 14 cm)
Blades	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel	.204" (.5 cm) Heat-Treated Steel
Blade Tip Speed	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min	18,500+ ft/min
Belt Construction	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt	Aramid Fiber V-Belt
Anti-Scalp Rollers	2 Side Bumpers/4 Rollers	2 Side Bumpers/4 Rollers	2 Side Bumpers/4 Rollers	2 Side Bumpers/4 Rollers	2 Side Bumpers/4 Rollers	2 Side Bumpers/4 Rollers
Carrier Frame Construction	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)	3" x 1.5" x 10-Gauge (7.6 cm x 3.8 cm x 10-Gauge)
<b>FEATURES</b>						
Steering Controls	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened	1-5/8" (4.1 cm) Diameter Grips; Adjustable, Dampened
Operator Seat	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	Deluxe Suspension with 3-D Isolation Mounts	MyRide® Suspension System	MyRide® Suspension System
Armrests	Standard	Standard	Standard	Standard	Standard	Standard
Seat Suspension System	Standard	Standard	Standard	Standard	Standard	Standard
Folding ROPS	Standard	Standard	Standard	Standard	Standard	Standard
Storage Compartment	Standard	Standard	Standard	Standard	Standard	Standard
Foot Pedal Deck Lift	Standard	Standard	Standard	Standard	Standard	Standard
Z Stand	Optional	Optional	Optional	Optional	Optional	Optional
Floor Pan	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access	Pierced, Extruded Tread; No-Tools Deck Access
<b>WEIGHTS AND MEASUREMENTS</b>						
Weight	1,335 lbs. 605.5 kg	1,335 lbs. 605.5 kg	1,335 lbs. 605.5 kg	1,335 lbs. 605.5 kg	1,335 lbs. 605.5 kg	1,335 lbs. 605.5 kg
ROPS Height (Folded)	46.8" 118.9 cm	46.8" 118.9 cm	46.8" 118.9 cm	46.8" 118.9 cm	46.8" 118.9 cm	46.8" 118.9 cm
ROPS Height (Upright)	70.5" 179.1 cm	70.5" 179.1 cm	70.5" 179.1 cm	70.5" 179.1 cm	70.5" 179.1 cm	70.5" 179.1 cm
Deck Clearance Width	78.3" 198.9 cm	78.3" 198.9 cm	78.3" 198.9 cm	78.3" 198.9 cm	78.3" 198.9 cm	78.3" 198.9 cm
Deflector Width	N/A N/A	N/A N/A	N/A N/A	N/A N/A	N/A N/A	N/A N/A
Length	87.3" 221.7 cm	87.3" 221.7 cm	87.3" 221.7 cm	87.3" 221.7 cm	87.3" 221.7 cm	87.3" 221.7 cm

\* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.  
†CARB compliant model or model available. ▶ = Step Up Feature