

BUILT TOUGH AND DEPENDABLE FOR EVEN THE MOST EXTREME CONDITIONS.

Take control of big snow jobs this winter with the speed and ease of Power Max® and Power Max® HD.

IDEAL FOR Larger driveways that can hold 6-14 parked cars and 6-20" / 15-50 cm of snow at a time

MODEL	CORE		PREMIUM	
	POWER MAX® 724 OE	POWER MAX® 824 OE	POWER MAX® 826 OAE	POWER MAX® 826 OHAE
	37807	37798	37799	37805
CLEARING WIDTH	24" / 61.0 cm	24" / 61.0 cm	26" / 66.0 cm	26" / 66.0 cm
SNOW CUT DEPTH	20" / 50.8 cm	20" / 50.8 cm	20" / 50.8 cm	20" / 50.8 cm
ENGINE	212cc Toro Premium OHV	252cc Toro Premium OHV	252cc Toro Premium OHV	252cc Toro Premium OHV
DRIVE SYSTEM	Self-Propelled	Self-Propelled	Triggerless Steering	Triggerless Steering
STARTING	Electric	Electric	Electric	Electric
THROWING DISTANCE*	Up to 40' / 12.2 m	Up to 45' / 13.7 m	Up to 45' / 13.7 m	Up to 45' / 13.7 m
AUGER SYSTEM	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging
AUGER DIAMETER	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm
IMPELLER DIAMETER	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm	11" / 27.9 cm
AUGER GEARBOX	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required
HANDLE	Standard	Standard	Standard	Heavy-Duty
DEFLECTOR	Single	Single	Single	Single
CHUTE CONTROL	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®
TIRES	15" / 38.1 cm	15" / 38.1 cm	15" / 38.1 cm	15" / 38.1 cm
HAND WARMERS	–	–	–	✓
LED LIGHT	–	–	✓	✓
WARRANTY**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited

*Throw distance and clearing capacity will vary with conditions. ***See retailer for complete warranty details.

POWER MAX® HD 828

- 28" / 71 cm Clearing Width
- 252cc Toro Premium OHV Engine
- Commercial-Grade Auger Gear Box
- All-Steel Construction
- Anti-Clogging System
- 16" / 40.6 cm Never-Flat Tires



POWER MAX® HD 1230

- 30" / 76 cm Clearing Width
- 302cc Toro Premium OHV Engine
- Commercial-Grade Auger Gear Box
- All-Steel Construction
- Hand Warmers Standard
- Anti-Clogging System
- 16" / 40.6 cm Never-Flat Tires



POWER MAX® 826 OAE

- 26" / 66 cm Clearing Width
- 252cc Toro Premium OHV Engine
- Triggerless Steering
- Anti-Clogging System



POWER UP

Optimal performance and years of dependable use with the 252cc Toro premium 4-cycle OHV engine.



TRIGGERLESS STEERING

No triggers to pull or levers to break! Turn the machine and the wheel intelligently disengages to assist you through for effortless turns.



CHUTE CONTROL

Quickly change the chute and deflector direction with a single, smooth motion thanks to the Quick Stick® chute control.



IDEAL FOR Larger driveways that can hold up to 20 parked cars and 9-21" / 23-53 cm of snow at a time

MODEL	PREMIUM		COMMERCIAL-GRADE			
	POWER MAX® HD 824	POWER MAX® HD 828	POWER MAX® HD 1230	POWER MAX® HD 1232	POWER MAX® HD 1428 OHXE	POWER MAX® HD 1432 OHXE
	39960	39961	39962	39963	38843	38844
CLEARING WIDTH	24" / 61 cm	28" / 71 cm	30" / 76 cm	32" / 81 cm	28" / 71 cm	32" / 81 cm
SNOW CUT DEPTH	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm	21" / 53.3 cm
ENGINE	252cc Toro Premium OHV	252cc Toro Premium OHV	302cc Toro Premium OHV	375cc Toro Premium OHV	420cc Toro Premium OHV	420cc Toro Premium OHV
DRIVE SYSTEM	Triggerless Steering	Triggerless Steering	Triggerless Steering	Triggerless Steering	Power Steering	Power Steering
STARTING	Electric	Electric	Electric	Electric	Electric	Electric
THROWING DISTANCE*	Up to 45' / 13.7 m	Up to 45' / 13.7 m	Up to 49' / 14.9 m	Up to 57' / 17.4 m	Up to 60'+ / 18.3 m+	Up to 60'+ / 18.3 m+
AUGER SYSTEM	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging	Power Max Anti-Clogging
AUGER DIAMETER	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm
IMPELLER DIAMETER	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm	14" / 35.6 cm
AUGER GEARBOX	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required	Commercial-Grade, No Shear Pins Required
HANDLE	Heavy-Duty	Heavy-Duty	Heavy-Duty	Heavy-Duty	Commercial	Commercial
DEFLECTOR	Single	Single	Single	Double	Double	Double
CHUTE CONTROL	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®	Quick Stick®
TIRES	16" / 40.6 cm Never-Flat	16" / 40.6 cm Never-Flat	16" / 40.6 cm Never-Flat	16" / 40.6 cm Never-Flat	16" / 40.6 cm	16" / 40.6 cm
HAND WARMERS	–	–	✓	✓	✓	✓
LED LIGHT	✓	✓	✓	✓	✓	✓
WARRANTY**	3-Year Limited	3-Year Limited	3-Year Limited	3-Year Limited	5-Year Limited / 1-Year Commercial	5-Year Limited / 1-Year Commercial

Throw distance and clearing capacity will vary with conditions. *See retailer for complete warranty details.



NO SHEAR PINS!

No need to replace shear pins in the cold with Toro's hardened gears and commercial-grade auger gearbox.



PRECISION MOVES

Smooth, tight turns are a snap with power steering.



TORO DOUBLE DEFLECTOR ADDED RANGE OF MOTION

STANDARD
DEFLECTOR

DOUBLE CHUTE DEFLECTOR

Place the snow with greater precision, such as right next to your fence line, or throw the distance with a double deflector.