

Evolution™ Series Controller



Learn more at

toro.com

- 4- to 16-Stations
- Computer Programmable
- Indoor and Outdoor
- Modular

Introducing the next generation in controllers!

With an intuitive interface and exclusive features for "smart" control, the new $Toro^*$ EvolutionTM is an easy choice for residential and light-commercial applications.



Features & Benefits

Revolutionary Interface

The Evolution™ controller's user interface was designed with the customer in mind. Shortcut buttons provide quick access to standard functions while the advanced menu leverages the experience and knowledge of the irrigation professional, all shown on a graphics display that navigates similar to many modern consumer electronic devices.

Easy Upgrade to Integrated Smart Control


An optional Smart Connector™ plugs into the timing mechanism, enabling it to wirelessly communicate directly with a number of add-on devices—including a weather sensor, handheld remote, and up to three soil sensors.

Computer-programmable with USB Drive

Simple-to-use software allows you to program everything at a computer. Use a standard USB drive to transfer programming to one or more controllers in a matter of seconds. The USB drive also provides controller logging functionality to save an operation log for diagnostic purposes.









New Product Contest
Landscape & Golf Winner

12-station configuration with (2) 4-station modules

16-station configuration with (1) 12-station module







Controller Interface

The Evolution controller's interface is a system of informative yet easy-to-understand screens that are quickly accessible using the controller's shortcut buttons.



Standard Functions










The **Standard** menu gives the basic user access to the most fundamental functions of the controller, such as manual watering, setting watering days and start times for a single schedule, and adjusting the amount of irrigation, all directly accessible through dedicated shortcut buttons.



For example, the **Water Now Screen** allows the user to begin watering with as few as just two button presses, with the option of starting a specific schedule, specific zone, or watering all zones in series.




Another example is the **Review Screen**, which is an at-a-glance summary showing which days the controller is going to water in the next seven days for the schedule you select.

Advanced Functions



The **Advanced** menu gives the experienced user access to the full power of the Evolution controller, including the ability to set up multiple irrigation and auxiliary schedules, create custom grow-in schedules, and configure any "smart" add-on devices - all operations that may otherwise overwhelm a basic user.



For example, the **Apply Sensors Screen** allows the user to easily view and configure all the sensors available to the controller, including rain, ET, and soil.



The **Grow In Screen** allows the user to set up a grow-in schedule for a user-defined period of time (up to 90 days), after which the controller will default back to its normal irrigation schedule(s).

Other Examples



The **Home Screen** displays the current time and date, what zones are scheduled to water next, or if currently watering, what zone(s) are currently watering and how much time is remaining, as well as any alerts – in the absence of any alerts, the screen will display "SYSTEM OK."



The **Local Service Message Screen** allows the contractor to input a custom message with their name and contact information into the controller from the software via a USB drive so it is visible to the homeowner when they press the "Help" button.

Smart Connect[™] Add-On Devices

Simply plugging the Smart Connector $^{\text{\tiny{M}}}$ into the Evolution controller allows it to communicate wirelessly with a number of add-on devices, providing a great opportunity to upgrade with a number of different water-saving and time-saving options.



Evolution™ Series Software

Simple programming made even easier!

The Evolution™ programming software makes the already easy-to-program Evolution™ series controller even easier to program by allowing you to set up irrigation and auxiliary schedules at your computer and transfer everything to the controller in seconds using a standard USB drive. Managing multiple controllers for different installation locations is a much more manageable task with this powerful tool, allowing you to create a "homeowner" database of schedules for an unlimited number of controllers.



Features & Benefits

An Even Easier Way to Program

Whether you're at your desk or in your truck on a laptop, the optional Evolution software allows you to program the Evolution controller using the power of a PC on most Windows-based operating systems (XP, or Windows* 7 or 8).

Quick Uploading with USB

Once you're done programming on the computer, transferring the information to the controller is easy with a USB drive—making it simple to create, save, and load different schedules for multiple controllers – there's no limit!

Standard and Advanced Modes

Just like the Evolution controller itself, the Evolution software can tailor itself to your needs and be only as advanced as you want it to be. Standard mode covers the basics for a single schedule while advanced mode provides additional scheduling options, such as ET-based programming and creating more than one schedule.

Backup & Troubleshooting

The Evolution software gives you the ability to store programming for multiple controllers on your computer, making field changes as easy as emailing updated programming to your customer. The Evolution system also provides controller logging functionality that saves an operation log to the USB drive for later analysis and troubleshooting via the software.



Expanded Customization

The software also allows you to enter custom names for schedules and zones (such as "Shrubs" or "Front Yard" instead of "Zone 1"), as well as contact information that the homeowner can access in the "contractor message screen" any time they press the "Help" button on the controller.



Zones Screen

In advanced mode, this screen is where you enter the characteristics of each of the zones on the system, including the type of plant, soil, sprinkler, slope, and amount of sun exposure, to create the most efficient irrigation schedule possible. You also have the option of loading custom photos to represent each zone.



Review Screen

Similar to the review screen in the controller itself, this "at-a-glance" view of upcoming irrigation events graphically displays on a calendar when watering is scheduled to occur and for how long. You can zoom in and out on any section of the calendar and click on a segment of any schedule to see details of which zone is scheduled to water at that time.



Simple Setup

A simple wizard walks you through the schedule setup process step-by-step, allowing you to select the different features specific to each zone on the system. This data is then used to create a fully customized and optimized irrigation schedule for the controller.

Evolution™ Series Controller

Dimensions

- 286mm x 197mm x 114 mm (11¼"x 7¾" x 4½")
 W x H x D
- Weight: 2,0 kg (4.5 lbs.)

Electrical Specifications

- Electrical input power:
 - 220/240 VAC, 50 Hz
 - 30 VA (internal and external plug-in type transformer)
 - CE compliant
- Station output power:
 - 24 VAC
 - 0.75 amps per station maximum
 - 0.75 amps pump/master valve
 - 1.0 amps total load
- Surge Protection:
 - 6,0 KV common mode; 1,0 KV normal mode

Operating Specifications

- 4 to 16 stations, Modular
 - 4 Stations Fixed in base unit
 - 4- and 12-station hot-swappable modules
- One irrigation schedule in the default "standard" mode
- Up to six schedules in "advanced" mode
 - Three irrigation schedules, four start times per schedule
 - · One fixed output auxiliary schedule
 - Two virtual auxiliary schedules for wireless control
- Three scheduling choices:
 - · Seven-day calendar
 - 1 to 30-day interval with up to seven day exclusions
 - Odd/even days with up to seven day exclusions
- Station run times from one minute to twelve hours
- Cycle and soak by station
- Simultaneous operation of up to three zones
- Monthly season adjust by schedule
- Programmable "no irrigation" water restrictions
- Automatic split cycle when season adjust >100%
- Grow-in schedule settable up to 90 days
- Station-delay from 1 second to 60 minutes
- Pump start delay from 1 to 60 seconds
- Master valve on/off by zone
- Timed water off from 1 to 14 days
- Quick select 30, 60, or 90 second manual run times

Operating Specifications (continued)

- Compatible with normally closed rain sensors
- · Review feature to show planned irrigation
- · Customizable zone and schedule names
- Automatic short detection for circuit protection
- · Advanced diagnostics and alerts including current draw
- Operation of two solenoids per station
- Non-volatile memory does not require battery and holds programming for up to five years
- · Status LED provides rapid indication of alerts
- 9V battery-powered timing mechanism for "armchair" programming
- Smart Connector™ upgrades controller for wireless smart or handheld remote control
- Evolution software lets users program on a computer and transfer programming via a USB drive
- Outdoor key-lock cabinet manufactured out of durable UVresistant plastic
- Indoor model includes internal transformer with wall plug piqtail

Warranty

· Five years

Evo	lution Series Model List
Model	Description
• EVO-4ID-EU • EVO-40D-EU	4-station Indoor Controller, 220V, Europe 4-station Outdoor Controller, 220V, Europe

Ado	Add-ons and Accessories	
Model	Description	
• EMOD-4 • EMOD-12 • EVO-SC-EU • PSS-SEN-EU • EVO-WS-EU • EVO-HH-EU	4-station Expansion Module 12-station Expansion Module Smart Connect® Precision™ Soil Sensor Probe ET/Weather Sensor Maintenance Remote	

Specifying Information

EVO-4 <u>XX-YY</u> - <u>ZZ</u> -SC-EU								
Description	Cabinet Type	Power	Module	Connector Options				
EVO-4	XX	<u>YY</u>	ZZ	-SC-EU				
EVO-4 – Evolution Controller, 4-station Base	ID – Indoor OD – Outdoor	Blank – 120V/60Hz EU – 220V/50Hz	00 – No Modules 04 – One 4-station Module 44 – Two 4-station Modules 12 – One 12-station Module	SC-EU – Smart Connector™ Europe, 868 mHz				

toro.com

Worldwide Headquarters The Toro Company 8111 Lyndale Ave. So. Bloomington, MN 55420 U.S.A. Phone: (1) 952 888 8801 Fax: (1) 952 887 8258











twitter.com/TheToroCompany youtube.com/ToroCompanyEurope

