ULTRA BUGGY® e2500

WHEELED MATERIAL BUGGY

ELECTRIC POWERED

Electric Hauling for Interior Workflows

For crews moving heavy materials through buildings and tight work zones, the Ultra Buggy e2500 keeps transport simple and efficient. Electric operation produces no engine exhaust emissions, making it ideal for occupies spaces and modified flooring where distruption must be minimized. The compact footprint and tight turning radius supports smooth acces through doorways, elevators, and confined paths. Built to reduce manual hauling, it helps teams move concrete, debris, and supplies with fewer trips and less fatigue.

Key Specifications

- 2,500 lbs carrying capacity
- 14 cu. ft. tub volume
- Up to 8 hours of continuous runtime
- 31.5” width





INTERIOR MATERIAL MOVER

Electric operation produces no engine exhaust emissions for interior material transport.



HANDLES HEAVY LOADS

Moves heavy materials efficiently with fewer trips and less fatigue.



EASY INTERIOR ACCESS

Compact size supports movement through doorways and tight interior paths.

ULTRA BUGGY® e2500

WHEELED SWIVEL MATERIAL BUGGY

ELECTRIC POWERED

	ULTRA BUGGY e2500 SPECIFICATIONS MODEL 68037
BATTERY	
Chemistry	Toro® HyperCell® Lithium Ion
Capacity	13.2 kWh
Fuel Type	Electric
Run Time[1]	up to 8 hours
CHARGING	
Charging Type	1.2 kW @ 120V
Charging Time (80%, 100%)	4.5 hrs, 6.5 hrs
WHEELS	
Front Tire Type	18" in. Non-Marking
Rear Tire Type	16" in. Non-Marking
Front/Rear Wheel Type	Mild Steel / Weldable Grade B Carbon Steel
Wheelbase	41 in. (104.1 cm)
DIMENSIONS	
Dimensions, Platform Down (L×W×H)	111 x 31.7 x 55 in. (281.9 x 80.5 x 139.7 cm)
Dimensions, Platform Up (L×W×H)	95 x 31.7 x 55 in. (241.3 x 80.5 x 139.7 cm)
Tub Volume	14 cu. ft. (0.39 m^3)
Max Load Capacity	2,500 lbs (1,134 kg)
Ground Speed (Forward/Reverse)	5.5 mph (8.8 kph) / 3.6 mph (5.8 kph)
Weight	1,530 lbs (694 kg)
Distributed Floor Pressure (Loaded/Unloaded)	1.15 psi / 0.45 psi
Discharge Height	6.5 in. (16.5 cm)

[1]Run time may vary based upon conditions.

©2026 The Toro Company Part No. 2026-0015 | toro.com
Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.