

The Toro logo is a red rounded rectangle with the word "TORO" in white, bold, sans-serif capital letters.

Workman® GTX Lithium

UTILITY VEHICLE

F E A T U R E S

- **Power** – An improved power to weight ratio provides the capacity and productivity you need to do more, every day!
- **Cargo Capacity** – At 800 lbs. (363.8 kg), the GTX Lithium-Ion provides a large cargo capacity.
- **Maintenance-Free** – Lithium-Ion battery packs require no maintenance which allows you to spend less time checking batteries and more time checking tasks off your to-do list.
- **Extended Battery Life** – Lithium-Ion battery packs give you the power for long days and reduced charging time for short nights.
- **Onboard Charger** – No need to keep track of your charger, it's onboard and ready to be connected to any standard power outlet anytime, anywhere.
- **Reduced Weight** – The GTX Lithium is 26% lighter than a traditional electric vehicle, and offers an additional 3 inches (7.6 cm) of ground clearance, making it nimble while still packing plenty of all-day power.
- **Choose Your Power** – Option to add an additional battery for those looking for more power during the most demanding all-day jobs.

Lithium-Ion Power.

HyperCell® lithium-ion technology powering the Workman GTX Lithium is built to deliver hours of reliable performance. The GTX Lithium provides a large cargo capacity, so it can handle big jobs. At nearly 400 pounds (181.4 kg) lighter than traditional Workman GTX models, it makes a big impression on productivity without leaving a big impression on turf. The lithium-ion power packs are maintenance-free and have a long lifespan, so the machine is always ready to get to work.

toro.com/gtx



WORKMAN GTX (LITHIUM-ION BATTERY), 07433LT / 07433TC					
POWER SYSTEM	Lithium-Ion batteries with integrated Battery Management System (BMS)				
ENERGY CAPACITY	4.32 kWh standard, 6.48 kWh optional. 55V nominal; 63V Max				
ELECTRIC MOTOR	Brushless high-torque AC Induction motor with 5.0kW continuous power.				
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter.				
TURNING RADIUS	Turning clearance circle: 20.7' (6.3 m), inside turning radius: 60.25" (153 cm).				
BRAKES	Front and rear wheel hydraulic disc brakes.				
SUSPENSION	Front - Modified MacPherson Strut. Rear - Articulating Swing Arm. Adjustable coil over shocks at all four wheels.				
SUSPENSION TRAVEL	Front Suspension Travel: 3.5" Rear Suspension Travel: 4".				
GROUND SPEED	16 mph (25.6 km/h), adjustable.				
TRANSAXLE	11.47:1 Forward, 14.35:1 Reverse.				
GROUND CLEARANCE	Front: 12" (30.4 cm), Rear: 7" (17.8 cm).				
TIRES	22 x 9.5-12, 4-ply. Or alternate 4-ply/6-ply.				
WHEELS	12" (30.5 cm) aluminum.				
CONTROLLER	375 amps max with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.				
CHARGER	On-board high efficiency 900W smart charger. •AC Input Voltage: 100-240 VAC •AC Input Frequency: 50/60 Hz •Max AC Input Current: 10 A				
INSTRUMENTS/DASH	Hour meter, battery level indicator, USB power port, headlight switch, on/off ignition key switch, and parking brake lever. Two cup holders, radio holder, three in-dash storage compartments, speedometer, gear indicator, estimated charge time, and diagnostic/fault codes.				
STARTING	Pedal start.				
DIMENSIONS	Vehicle Configuration 2-Seat with Bed (GTX Lifted)	Width 47" (119.3 cm)	Length 119" (302 cm)	Height: 53.2" (135 cm)	Wheel Base 77.8" (197 cm)
CAB DIMENSIONS INSTALLED	Height: 82" (208 cm) Width: 56" (142 cm)				
CANOPY DIMENSIONS INSTALLED	Height: 78.2" (199 cm) Width: 54.3" (138 cm)				
WEIGHT	Vehicle Configuration: 2-Seat with Plastic Cargo Bed		Weight: 980 lbs (445 kg)		
CARGO BED	Width: 38.5" (97.8 cm)	Length: 40" (101.6 cm)	Height: 11" (27.9 cm)	Capacity: 800 lbs (363 kg)	
VEHICLE CAPACITY	2-seat with bed 1,200 lbs. (544 kg)				
TOWING CAPACITY	1,500 lbs. (680 kg) Class 1 – 1.25" receiver standard.				
OPTIONAL ACCESSORIES	Canopy, solid folding windshield, storage box, trash can mount, bed racking, electric bed lift, brush guard, 12V outlet, Brake/tail/signal lights, ROPS certified hard cab, back up alarm kit, parking brake alarm kit, 2-post ROPS kit, range cage, and glass windshield.				
WARRANTY	Two-year or 1500 hour limited warranty. Refer to the Operator's manual for further details. Battery Warranty: 5-year, unlimited hour.				

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

