GROUNDSMASTER[®] 3200/3300 SERIES



ACCESSORY GUIDE

Groundsmaster® 3200/3300 Series

The Groundsmaster 3200/3300 delivers unparalleled productivity. Featuring a powerful 36.8 HP (27.5 kW) or 24.7 HP (18.4 kW) engine, CrossTrax® all-wheel drive and legendary Groundsmaster decks, the Groundsmaster 3200/3300 makes quick work in even the toughest terrain while delivering an exceptional quality of cut.



©2023 The Toro Company. All rights reserved. Specifications subject to change. Please contact your Toro distributor for details. Rev. 1/23









60" (152 cm) / 72" (183 cm) Side Discharge Cutting Deck Accessories

- Recycler kit Semi-pneumatic (flat-free) front
- castor wheels standard • Low, Medium, or High sail blade options
- Atomic mulching blade

60" (152 cm) / 72" (183 cm) Rear Discharge Cutting Deck Accessories

- Recycler kit
- Semi-pneumatic (flat-free) front castor wheels standard
- Low, Medium, or High sail blade options
- Atomic mulching blade

60" (152 cm) Flail Cutting Deck

- Out-front PTO-driven flail attachment
- 4" (100mm) Rear Roller for superb contour following and striped finish
- 32x TEMPEST™ paddle-style flail blades



 Optional Accessories: LED Cab Light Kit, Cab Beacon Light Kit

• GM3310 comes standard with a cab equipped with air conditioning and heat



Snow Thrower (Erskine)

- This is the perfect blizzard battler, with 53" (134 cm) clearing width
- 270 degree hydraulically adjustable discharge chute rotation
- Mechanically-driven snow thrower



Rotary Broom (M–B)

- The 60" (152 cm) wide mechanically-driven rotary broom cleans and clears snow, dirt, debris and grass during any season
- Hydraulic swing capable of 20° left or right of center
- Choice of poly or combination poly/wire brooms



BOSS® Straight-Blade Plow

- BOSS snowplows are engineered to perform in the worst winter conditions. 60" (152 cm) clearing width
- Fully hydraulic lift and angle adjustment to deliver maximum efficiency

Groundsmaster[®] 3200/3300 Series Accessories

General Accessories



Pro Force® Debris Blower

- Driven from PTO shaft off engine
- Nozzle Rotation 245°
- Great visibility out front of machine



Standard Seat



LED Beacon Kit • Mounts to ROPS or cab frame

Slow Moving Vehicle Kit • Mounts to top of the engine hood



Universal Sunshade Red or White

- Stay cool and productive when mowing with a canopy
- Optional Accessories: Sunshade LED Work Lights, Operator Cooling Fan (shown above), Sunshade Beacon Light



Mechanical Suspension Seat

Measures slope – includes visual indicator

• Dual charging ports for phones and other

• Optional hydraulic kit for front attachments

Optional electrical control kit for front attachments

Slope Sensor Kit

and audible alarm

electronic devices Storage Box Kit • Storage compartment Auxiliary Hydraulic Kit

Accessory Control Kit




LED Road Light Kit

• Includes headlights and front & rear flashers – available for cab and non-cab models




Air-Ride Suspension Seat



Recycler Kit (Rear Discharge Decks)

• Deflectors inside chambers redirect clippings so they are cut and recut

• Includes 4 LED worklights – available for Cab and non-cab



Recycler Kit (Side Discharge Decks)

• Front baffles with kickers and side discharge plate close cutting chambers for recycling and mulching

Parts & Services

LED Work Light Kit

models (not for on-road use)



Blades

High Sail Blade

conditions

- Provides the best quality
 of cut in most grass
 Low noise level
 lower power co
 - s Lower power consumption

Flat Blade

- Reduced discharge velocity
- Provides improved air flow of clippings

Low/Meduim Sail Blade Atomic Blade

- Provides a better quality
 of cut
 while mulching
- of cut of cut while mulching • Better overall performance • Preferred blade for in most conditions mulching applications



myTurf[®] Wireless System • Wireless Hourmeter

- Base Station
- Repeater
- External Antenna

Parts Kits

- 400-Hour Filter MVP Kits
- Blade and Belt Kits

Specifications subject to change. Please contact your Toro distributor for details. Rev. 1/23