

TORO

Groundsmaster® 5900/5910

LARGE AREA ROTARY MOWER

FEATURES

- 192 in. (488 cm) width of cut, mows up to 20.9 acres (8.5 hectares) per hour*
- 3.3 L Yanmar® EPA Tier 4 Final and EU Stage IV emissions compliant turbo-diesel engine
- Full-time, bi-directional 4WD
- Smart Power® and HybridDrive™ cutting deck system - work together providing optimal power to the cutting blades
- CrossTrax® all-wheel drive system offers increased cross wheel traction control
- 0" uncut circle in turns
- Onboard InfoCenter™ with advisories and diagnostics for maximum uptime
- SmartCool® auto-reversing cooling fans
- 24-volt electrical system powers cooling system
- 4-way adjustable seat and Air Ride Suspension
- All-season safety cab with air conditioning and heat (5910)

More Parks & More Rec.

Tasked with maintaining more parks and sports fields with no additional workers or budget? The Groundsmaster® 5900 Series mowers can mow over 20.9 acres/hour (8.5 hectares/hour)* using only one operator! And to match the 16' (4.88 m) wide mowing brawn and a more fuel-efficient EPA Tier 4 Final and EU Stage IV emissions compliant Yanmar® 3.3 L engine, the Groundsmaster 5900 series is loaded with intelligence. Smart Power® allows the operator to effortlessly maintain the correct speed for optimal cutting, while the SmartCool® system prevents overheating with auto-reversing the cooling fans. An onboard InfoCenter™ gives the operator a quick read on all systems and even provides assistance at the right moment. When the comfort and safety of an all season cab, the incredibly nimble handling, and tough Toro durability are added in, the Groundsmaster 5900 series proves beyond doubt that increased efficiency and ease of operation lead to higher productivity.

*Groundsmaster® 5900**Groundsmaster® 5910***SMARTPOWER**

*Assumes max mow speed and 100% efficiency. Actual mowing rates may vary depending on operator and conditions.

©2022 The Toro Company. All rights reserved. Rev. 2/22

Call your Toro distributor at 800-803-8676

Groundsmaster® 5900/5910 Specifications*

| GROUNDMASTER 5900, MODEL 31698 / GROUNDMASTER 5910, MODEL 31699 | |
|---|---|
| ENGINE | Yanmar 3.3L, EPA Tier 4 Final and EU Stage IV emissions compliant, turbocharged diesel with direct injection and electronic high-pressure common rail. 72 HP (53.7 kW) @ 2500 rpm, Torque: 206 ft.-lbs. (279 Nm) @ 1625 rpm Displacement: 202 cu. in. (3.3 L). |
| COOLING SYSTEM | 24V dual electric fan banks for separate engine radiator and hydraulic oil cooling; fan banks are variable speed, with auto-reverse feature (SmartCool®, based on coolant and oil temps), radiator is cross flow, 3 rows, 9 fins per in. (FPI). Hydraulic oil cooler is crossflow, 6 FPI. Cooling fan banks tilt away for fast, easy cleaning. |
| FUEL SYSTEM | Uses ultra-low sulfur diesel fuel only. Biodiesel compatible up to B20. |
| CAPACITIES | Fuel: 35 gal.(132L) Hydraulic: 19 gal (71.9 L). Engine Oil w/ filter: 11 qt. (10.4 L). Coolant: 13.5 qt. (12.7 L) (Model 31698), 18 qt. (17 L) (Model 31699) |
| HYDRAULIC SYSTEM | Capacity: 19 gallons (71.9 L) reservoir, Remote spin-on charge filter, Oil: Toro premium all season hydraulic fluid |
| TIRES/WHEELS | Front: 29x12.00-15, 6 ply rating, 32 psi; Rear: 23x10.50-12, 6 ply rating, 30 psi |
| INSTRUMENTATION | Onboard LCD (InfoCenter™) display shows customizable gauges, service reminders, advisories/faults and troubleshooting assistance. Indicates fuel level, coolant temp, hydraulic oil temp, engine glow plug, low oil pressure, air cleaner restriction, 12 and 24 volt alternator voltage output, engine hours and rpm, and engine DPF regeneration. |
| POWERTRAIN | Full time automatic forward and reverse 4WD in low (mow) range. Front wheel drive in transport. Parallel hydrostatic, closed loop with cross wheel traction (CrossTrax™) design; traction drive pump: variable displacement piston, servo control. Front drive: 2-speed, fixed displacement high torque, low speed radial piston motors. Rear drive: single speed, fixed displacement, high torque, low speed radial piston motors. Smart Power® feature controls traction speed to maintain optimal cutting blade speed. |
| ELECTRICAL SYSTEM | Main: 12 volt system; Alternator: 12V, 80 amp, supplied w/ engine Battery: 1380 CCA (2x 690 CCA), Cooling Fans, Engine/Hydraulic cooling: 24 volt system; Alternator: 24V, 105 amp w/ remote sense; Battery: 350 CCA; Disconnect ON/OFF switch for 12 & 24 volt service safety. |
| BRAKES | Service: Dynamic, hydrostatic 4WD in low range. Front wheel drive braking in high range. Parking: Electrohydraulic controlled via double-motion rocker switch. Spring applied, hydraulic released. Internal to front wheel motors. Automatically applies with engine OFF or key OFF Manual override from operator platform for servicing |
| PRODUCTIVITY | Infinitely variable speed. Forward speeds: mow: 0-10.8 mph (17.4 km/h) Transport: 0-20 mph (0-32.2 km/h). Reverse speeds: mow 0-5.7 mph (0-9.2 km/h), transport: 0-10.5 mph (0-16.9 km/h) transport. Speed control: Electronic, limits max speed. Mowing capacity: 20.9 acres/hr. (8.5 ha/hr)**; NOTE: For EU countries complying to ISO 5395, all speeds and mow rates should be reduced by 12%. |
| CONTROLS | Control arm, right armrest, travels with seat and suspension. Deck lift/lower, electrohydraulic switches. Throttle; electronic, variable. Traction pedal, electronic. Park brakes: double-motion switch. Steering; hydrostatic load sensing. Other: High/low range, PTO, cruise control, lights, horn, key switch, wing deck transport latches (manual). |
| OPERATOR STATION | Operator platform: isolated rubber mounted. Seat: 4 way adjustable with vinyl (31698) or cloth (31699) cushions standard. Suspension: air-ride with 3 in. (7.6 cm) of adjustability. Steering: power and adjustable tilt. Traction Pedal: adjustable angle uses position sensor. Storage box, cup holder, and 12 volt power outlet, double USB port, standard. |
| STEERING | Uncut circle - 0" diameter. Turning radius - 86" (218 cm) |
| CAB (5910) | ROPS certified cab with heat, AC and the following standard features: climate system pressurized cab, heavy-duty pantograph front windshield wiper and washer, front windshield has 38" of visibility, interior mirror, fold away exterior side mirrors, molded front fenders, right and left doors and rear window have tinted (50%) glass, front and rear windows open, quick release window latches act as emergency exit, rubber sound isolator cab mounts and upholstered interior panels and headliner, textured neoprene floor mat, interior dome light. Power provided for optional aftermarket audio accessories. Optional rotating beacon for cab units (31509), additional turn signals and work lights available. |
| SAFETY AND LIGHTING | Standard (31698 & 31699): LED headlights, brake lights, tail lights, and amber turn signals and flashers). Disconnect ON/OFF switch for 12 & 24-volt service safety. |
| CERTIFICATION | Meets or exceeds EU Machinery Directive (2006/42/EC); ISO 5395-2013 and ANSI B71.4-2012; ISO 21299 and SAE J1194; OSHA 29CFR1910.95 (SAEJ1175, European Directive 2000/14/EC, ISO 5395-2013); EN 55012:2007 and CISPR12. Model 31698 meets or exceeds ANSI/ASAE S279.12 (Lighting and Marking of Agricultural Equipment on Highways). Model 31699 air conditioning system meets SAE J1503, Section 8. |
| WARRANTY | Two year limited warranty. |
| VEHICLE WEIGHT (W/ FULL FLUIDS) | 6,710 lbs. (3043 kg) (31698), 7,304 lbs. (3313 kg) (31699) |
| GROUND CLEARANCE | 10.3 in. (26.1 cm) |
| DIMENSIONS | WIDTH: Transport: 99 in. (251 cm), Mow: 199 in. (505 cm) LENGTH: 174 in. (442 cm) HEIGHT: 85 in. (216 cm) (31698), 95 in. (241 cm) (31699) WHEELBASE: 77 in. (196 cm) |

| CUTTING DECKS | |
|------------------------|---|
| TYPE | Three rear discharge rotary decks |
| CUTTING WIDTH | All three decks: 192 in. (488 cm), One wing: 57 in. (145 cm), center deck: 92 in. (234 cm), center deck + one wing: 144 in. (366 cm). |
| HEIGHT OF CUT | 1-6" in (2.5 - 15 cm) in 0.5 in. (1.3 cm) increments. |
| CONSTRUCTION | 11-gauge high-strength steel. 7-gauge, reinforcements, bullnose bumpers. |
| PROTECTION | 2-way shock absorption on wing decks. |
| DECK DRIVE | HybridDrive™ - Hydraulic motor to spindle, remaining spindle(s), driven by "B" section v-belts. |
| TENSIONING | Automatic, spring loaded idlers. |
| SPINDLES | Shaft: 1.25" (3.2 cm) hardened steel. Housing: 9" (22.9 cm) ductile iron. Bearings: Greaseable tapered roller. |
| STANDARD BLADES | 20" (50.8 cm), heat-treated steel blades. |
| OPTIONAL BLADES | Atomic™ mulching blades, flat blades. |
| SKIDS | 4 reversible polymeric, 2 reversible steel |

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

**Assumes max mow speed and 100% efficiency. Actual mowing rates may vary depending on operator and conditions.





Groundsmaster® 5900/5910 Accessories*



| | SNOWTHROWER ERSKINE MODEL 2000 |
|------------------------------------|--------------------------------------|
| STAGE | 2 |
| CLEARING WIDTH | 85" (216 cm) |
| SNOW CUT DEPTH | 29" (74 cm) |
| CUTTING EDGE | 3/8" x 3" (9.5 mm x 7.62 cm) bolt-on |
| SKID SHOES | Adjustable |
| AUGER DIAMETER | 16" (41 cm) open flight |
| FAN DIAMETER | 20" (51 cm) 4-blade |
| CHUTE ROTATION | Hydraulic, 270° |
| SHEAR PROTECTION | Pressure relief |
| THROWING DISTANCE | Up to 30' (9.4 m) |
| APPROXIMATE SHIPPING WEIGHT | 850 lbs. (386 kg) |
| HOSES | Included |

| TORO ACCESSORIES AND PARTS | |
|----------------------------|--|
| Model/Part # | Description |
| 30669 | Universal Mount Sunshade – White |
| 30671 | Universal Mount Sunshade –Red |
| 138-2700 | Work Lights for Sunshade |
| 31672 | Additional Turn Signals for ROPS/Sunshade |
| 31590 | Work Lights for GM5910 |
| 31671 | Additional Turn Signals for GM5910 |
| 119-7719 | Backrest Extension Kit – Fabric for GM5910 |
| 119-7718 | Backrest Extension Kit – Vinyl for GM5900 |
| 31604 | Leaf Mulching Kit |
| 93-5973 | 10" Foam Filled Caster Tire Assembly |
| 31609 | MVP Maintenance Kit (oil/fuel) |
| 31512 | Back-up Alarm Kit |
| 119-8256 | Rotating Beacon Kit for GM5900 |
| 31509 | Rotating Beacon Kit for GM5910 |



| | ROTARY BROOM M-B MODEL SHL |
|-------------------|---|
| TYPE | Windrow type, front mounted hydraulic broom with dual motors. Electric/hydraulic angling, 30° left and right. |
| BROOM SIZE | 32" (81 cm) diameter x 60" (153 cm) wide. |
| BRUSH | Sectional brush with combination polypropylene/wire radial segments. |
| OPTIONS | Dirt Deflector, Storage Stands. |

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor. Information regarding non-Toro (Allied Vendor) products is included in the Toro Golf and Grounds Equipment Guide as a convenience to Toro customers. Toro does not warrant, endorse or support any products purchased from Allied vendors. Additionally, Toro shall not be responsible for any personal injury or property damage, whether direct or consequential, caused by such Allied products. Toro does not certify fit up, compatibility or functionality of Allied products.

NOTE: The Toro Company does not manufacture or sell the snow thrower, rotary broom, nor does Toro guarantee these accessories in any manner whatsoever.

