

Z MASTER®

4000 SERIES

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS



BUILT TO DOMINATE. READY TO REIGN.

Show up big, bad, and fearless. The Z Master 4000 is the durability king, providing a royal ride with MyRIDE® suspension system and grass-kicking TURBO FORCE® deck with a bold, dominating look. It's going to cut a path that you know will be noticed.



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

	HD		HDX MyRIDE® SUSPENSION SYSTEM							
	74050 LIMITED QUANTITY	74054 LIMITED QUANTITY	74052 HDX LIMITED QUANTITY	74059 HDX PRO XL	74058 HDX PRO XL					
POWER SYSTEM										
Commercial Engines at 3600 RPM*	25.5 Kawasaki FX801V (852cc)		▶ 31 hp Kawasaki FX921V (999cc)		▶ 35 hp Kawasaki FX1000V (999cc)					
Starter	Electric		Electric							
Heavy-Duty Canister Air Cleaner	Standard		Standard							
Drive Tires	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)						
Caster Tires	15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)		15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)							
Fuel/Capacity	Gas/10-Gal (37.9 L)		Gas/10-Gal (37.9 L)							
Digital Hour Meter	Standard		Standard							
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors		ZT-4400 Integrated Pumps & Wheel Motors	ZT-5400 Integrated Pumps & Wheel Motors						
Maximum Forward Speed	12 mph (19.3 km/h)		12 mph (19.3 km/h)							
Clutch	Electromagnetic		Electromagnetic							
MOWING DECKS										
Deck Size	52" (132.1 cm)	▶ 60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	▶ 60" (152.4 cm)					
Cutting Deck	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE							
Deck Lift Design	Extension Spring		Standard							
Spindle Housings	9" (22.9 cm) Dia. Aluminum		9" (22.9 cm) Dia. Aluminum							
1" (2.5 cm) Spindle Shaft	Standard		Standard							
Spindle Bearings	Maintenance-Free		Maintenance-Free							
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)		Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)							
Deck Depth	5.5" (14 cm)		5.5" (14 cm)							
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel							
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min							
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt							
Adjustable Deck Baffles	Standard		Standard							
FEATURES										
MyRIDE® Suspension System			▶ MyRIDE Suspension System							
Comfort Platform	N/A		3.0" (7.62 cm)							
Platform Travel	N/A		1 center / 2 rear							
Shocks	N/A		High-Back Comfort							
Seat	N/A		5 Detents, Infinite Adjustability							
Adjustability	N/A		Standard							
2" Hitch Receiver	Standard		Standard							
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened							
Operator Seat	Deluxe Suspension with Armrests		Deluxe Comfort with Armrests							
LED Lights	Standard		Standard							
Step-Through Floorpan	Standard		N/A							
Electric Deck Lift Assist	Optional		▶ Standard	Optional						
Smart Hour Meter & USB	Standard		Standard							
Triple Bagger and Dump from Seat Bagger Capable	No		No							
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit		5-Year 1250-Hour 2-Year No Hour Limit							
WEIGHTS AND MEASUREMENTS										
Weight	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,317 lbs.	597.4 kg
Deck Clearance Width	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	66"	167.6 cm	65"	165.1 cm
Deflector Width	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm
Length	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	86"	218.4 cm	85"	215.9 cm

PRIDE CUT IN EVERY PASS

Constructed with high-strength materials and engineered with proven technologies, the TURBO FORCE cutting deck is built from 100 years of experience and over 100 million unrelenting hours of real-world results.

A BEAST FOR BEAUTY

Every Z Master 4000 is loaded with a heavy-duty front-end design, TURBO FORCE deck with bullnose bumper, and pro-grade engine transforming a battlefield of brutal vegetation into a pristine pro cut. All Z Master 4000 models now standard with adjustable baffles to leave all grass types with a superior finished cut look.

GET COMFORTABLE CRUSHING IT

Keep mowing full blast in full-time comfort with a deluxe suspension seat. Or get battle-ready with the MyRIDE® Suspension System.

	PRO				HDX PRO	HDX PRO XL												
	74000	74002	74005 PRO XL	74036 PRO XL	74010 HDX PRO	74016 HDX PRO XL	74020 HDX PRO XL	74022 HDX PRO XL	74024 HDX PRO XL									
POWER SYSTEM																		
Commercial Engines at 3600 RPM*	24.5 Kawasaki® FX751 (852cc)	▶ 25.5 Kawasaki FX801V (852cc)	▶ 26.5 hp Kohler Command Pro EFI (747cc)		▶ 31 hp Kawasaki FX921V (999cc)			▶ 35 hp Kawasaki FX1000 (999cc)										
Starter	Electric				Electric													
Heavy-Duty Canister Air Cleaner	Standard				Standard													
Drive Tires	24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)		24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	▶ 24" x 12" - 12" (61 x 30.5 - 30.5 cm)	▶ Super Turf 26" x 12" - 12" (66 x 30.5 - 30.5 cm)		▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)									
Caster Tires	13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)				13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		▶ 15" x 6.5" - 6" Flat-Free Semi-Pneumatic (38.1 x 16.5 - 15.2 cm)											
Fuel/Capacity	Gas/10-Gal (37.9 L)				Gas/10-Gal (37.9 L)													
Digital Hour Meter	Standard				Standard													
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors				▶ ZT-5400 Integrated Pumps & Wheel Motors													
Maximum Forward Speed	10 mph (16.1 km/h)				▶ 12 mph (19.3 km/h)													
Clutch	Electromagnetic				Electromagnetic													
MOWING DECKS																		
Deck Size	48" (121.9 cm)	▶ 52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)	▶ 72" (182.9 cm)									
Cutting Deck	7-Gauge TURBO FORCE				7-Gauge TURBO FORCE													
Deck Lift Design	Extension Spring				Extension Spring													
Spindle Housings	9" (22.9 cm) Dia. Aluminum				9" (22.9 cm) Dia. Aluminum													
1" (2.5 cm) Spindle Shaft	Standard				Standard													
Spindle Bearings	Maintenance-Free				Maintenance-Free													
Adjustable Height of Cut	Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)				Standard, 1.5" - 5.5" in .25" increments (3.8 - 12.7 cm in .6 cm increments)													
Foot Pedal																		
Deck Depth	5.5" (14 cm)				5.5" (14 cm)													
Blades	.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel													
Blade Tip Speed	18,500+ ft/min				18,500+ ft/min													
Belt Construction	Aramid Fiber V-Belt				Aramid Fiber V-Belt													
Adjustable Deck Baffles	Standard				Standard													
FEATURES																		
MyRIDE® Suspension System									▶ MyRIDE Suspension System									
Comfort Platform	N/A				N/A				3.0" (7.62 cm)									
Platform Travel	N/A				N/A				1 center / 2 rear									
Shocks	N/A				N/A				High-Back Comfort									
Seat	N/A				N/A				5 Detents, Infinite Adjustability									
Adjustability	N/A				N/A				N/A									
2" Hitch Receiver	Standard				Standard				N/A									
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened				1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened													
Operator Seat	Deluxe Suspension with Armrests				Deluxe Suspension with Armrests				Deluxe Comfort with Armrests									
LED Lights	Optional				Optional													
Step-Through Floorpan	▶ Standard				Standard													
Electric Deck Lift Assist	Optional				Optional													
Smart Hour Meter & USB	Standard				Standard													
Triple Bagger and Dump from Seat Bagger Capable	No		Yes		Yes													
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit				▶ 5-Year 1500-Hour 2-Year No Hour Limit													
WEIGHTS AND MEASUREMENTS																		
Weight	1,048 lbs.	475.4 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,360 lbs.	616.9 kg	1,300 lbs.	589.7 kg	-	-
Deck Clearance Width	55"	139.7 cm	59"	149.8 cm	65"	165.1 cm	65"	165.1 cm	59"	149.8 cm	65"	165.1 cm	65.5"	166.4 cm	75.6"	192.0 cm	75.6"	192.0 cm
Deflector Width	63.6"	161.5 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.3"	191.3 cm	87.6"	222.5 cm	87.6"	222.5 cm
Length	86"	218.4 cm	86"	218.4 cm	86"	218.4 cm	86"	218.4 cm	86"	218.4 cm	86"	218.4 cm	86.5"	219.7 cm	89.3"	226.8 cm	89.3"	226.8 cm

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.

▶ = Step Up Feature



NOW AVAILABLE

Triple/DFS bagger
for Pro XL, HDX XL and HDX Pro XL models

PERFECT ONE-PASS CUTTING

The TURBO FORCE® Cutting Deck: enhances the after-cut appearance through dual capture anti-scalp rollers, adjustable baffles, rubber discharge chute, a clear sight-line to rear tires and the offset 7-gauge steel deck.

4.4-6.6 Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



NO MESSING AROUND

Pairing the durable rugged I-beam front end, along with the TURBO FORCE deck's bullnose bumper and heavy-duty cast aluminum spindle housings, durability is king.



MyRIDE® SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.



MOW ON AND ON

4000s come with conveniences like the optional electronic deck lift assist, to front step thru deck, and USB ports.