



TORO® DINGO® TX 700

COMPACT UTILITY LOADERS

Designed to give you more power in a compact package, the Toro® Dingo® TX 700 expands labor savings beyond just homeowner projects. This no-nonsense workhorse packs 764 lbs of rated operating capacity and a 24.5 hp diesel engine, in a smaller footprint, so it's ideal for projects where homeowners and contractors are working in confined spaces. It also features patented Dingo TX 1000 traction controls that are easy to use, and a dedicated stand-on platform for increased operator comfort and visibility. And with dozens of compatible attachments, it's a versatile machine you can utilize for a wider range of jobs. With just the features you need, plus the familiarity and comforts of a Toro Dingo, it's an excellent solution to tackle projects big and small and increase labor savings.

FEATURES



COMPACT DESIGN

Great for homeowners and contractors who need to access smaller spaces

TRACK SYSTEM

The Dingo TX 700 trap-tracked system, offers peace of mind and comes with either an aggressive narrow track or turf-friendly wide track option

EASY-TO-USE CONTROLS

Effortless traction controls are easy to use for all-day productivity



STAND-ON PLATFORM

A dedicated platform on a compact frame. Plus, the spring loaded auxiliary foot pedal increases foot space

TORO® DINGO® TX 700

SPECIFICATIONS

		DINGO TX 700 NARROW TRACK (MODEL 22351)	DINGO TX 700 WIDE TRACK (MODEL 22352)
ENGINE	Engine	24.5 HP (18 kW) Yanmar 3TNV80F	
	Air Filter	Remote single element	
	Cooling System	Combo downflow radiator and oil cooler	
	Fuel Tank	5.5 gallons (20.8 liters)	
	Oil Capacity	3.6 quarts (3.4 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI	
	Hydraulic Flow	Traction: 14.5 gpm (each pump) Auxiliary: 13.7 gpm	
	Reservoir Capacity	10 gallons (37.9 liters)	
TRACKS	Standard	Camso B-Tread	Camso Turf Friendly
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Dimensions	5.4" x 126.6" (13.7 cm x 321.6 cm)	9.1" x 126.6" (23.1 cm x 321.5 cm)
	Wheelbase	39" (99.0 cm)	
	Ground Clearance	5.25" (13.3 cm)	
	Overall Dimensions (WxLxH) With Bucket	34.2" x 102.8" x 55.3" (86.9 x 261.1 x 140.5 cm)	41.4" x 102.8" x 55.3" (105.2 x 261.1 x 140.5 cm)
	Overall Dimensions (WxLxH) Without Bucket	34.2" x 82" x 55.3" (86.9 x 208.3 x 140.5 cm)	40.2" x 82" x 55.3" (102.1 x 208.3 x 140.5 cm)
	Maximum Operating Height	97" (246.4 cm)	
	Hinge Pin Height	73.5" (186.7 cm)	
	Dump Height	52.9" (134.4 cm)	
	Dump Angle	42-degrees	
	Reach - Fully Raised	31" (78.7 cm)	
Ground Speed	4.5 mph (7.2 km/h)		
Weight	2,514 lbs (1,140.3 kg)	2,602 lbs (1,180.2 kg)	
Tip Capacity	2,182 lbs (989.7 kg)	2,182 lbs (989.7 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	764 lbs (346.5 kg)	764 lbs (346.5 kg)	
Ground Pressure	6.4 PSI	4.8 PSI	

*Per ISO 14397-1

