

TURF RENOVATION

SPRAYMASTER



COMPATIBLE



MAXIMUM OF
4.0 Acres
COVERED PER HOUR



Get the job done better, faster and easier with the Stand-On SprayMaster.

The updated design creates more stability and balance resulting in less turf tear up and the flip up hopper allows for easy maintenance. Maximize ground coverage and reduce fill-up stops with two spray tanks with up to 60-gallon capacity, 250-pound hopper and 5-gallon fuel tank.

	LEAN-TO-STEER SPREADER/SPRAYER 34230	SPRAYMASTER 24 GALLON STAND-ON 34246	SPRAYMASTER 40 GALLON STAND-ON 34242	SPRAYMASTER 60 GALLON STAND-ON 34240
POWER AND DRIVE SYSTEM				
Engine*	Kohler® 9.5 hp	16 hp Twin Vanguard	▶ 21 hp Twin Vanguard	
Engine Orientation	Horizontal			
Fuel Capacity	Gas/1.85 Gal (7 L)	5 Gal (18.9 L) w/fuel gauge		
Electric Start	Yes	Yes	Yes	Yes
Transmission	Hydrostatic			
Maximum Forward Speed	5.5 mph (8.6 km/h)	7 mph (11.3 km/h)	▶ 10 mph (16.1 mph)	10 mph (16.1 mph)
SPREADER SYSTEM				
Hopper Size	175 lbs (79.4 kg)	150 lbs (68.0 kg)	▶ 250 lbs (113.4 kg)	250 lbs (113.4 kg)
Fertilizer Capacity	225 lbs (102.1 kg)	2 Rear Boxes - 50 lbs (22.7 kg) each		
Spread Width	Adjustable from 4'-22' (1.2 - 6.7 m)	Adjustable from 3' - 25' (0.9 - 7.6 m)		
Deflector Shield	Molded Plastic	Molded Plastic	Molded Plastic	Molded Plastic
Spinner Motor	Electric	Electric	Electric	Electric
SPRAY SYSTEM				
Pump Capacity	5 GPM	5.3 GPM		
Spray Capacity	20 Gal	24 Gal (2 - 12 Gal)	▶ 40 Gal (2 - 20 Gal)	▶ 60 Gal (2 - 30 Gal)
Spray Width	4 or 10 ft (1.2 or 3.0 m)	2, 4, 6 or 8 ft (0.6, 1.2, 1.8 or 2.4 m)		▶ 2, 4, 6, 8 or 10 ft (0.6, 1.2, 1.8, 2.4 or 3.0 m)
Boom	N/A	3-Section, Bi-Directional Breakaway Wings		
Spot Spray Hose	15 ft (4.6 m) Coil Hose	15 ft (4.6 m) Coil Hose	▶ 75 ft (22.9 m) Hose Reel	
WEIGHTS AND MEASUREMENTS				
Weight	500 lbs. (226.8 kg)	698 lbs. (316.7 kg)	896 lbs. (406.4 kg)	912 lbs. (413.7 kg)
Height	51.5" (130.8 cm)	48" (121.9 cm)	50" (127.0 cm)	50" (127.0 cm)
Width	35.5" (90.2 cm)	36" (91.4 cm)	46" (116.8 cm)	52" (132.1 cm)
Length	67.5" (171.5 cm)	70.5" (179.1 cm)	73" (185.4 cm)	72" (182.9 cm)

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature



FILL UP HOPPER. Maintenance is a breeze with the flip up hopper that provides easy access to the engine.



LARGE CAPACITY. Maximize ground coverage and reduce fill-up stops with two spray tanks that hold up to 60 gallons, 250-pound hopper capacity, and a 5-gallon fuel tank.



RIDE IN STYLE. The new design allows for increase balance and stability and features larger wheels, improved hopper cover, and custom-stitched knee pad.