

Z MASTER®

2000 SERIES

SEE PAGE 2 FOR BATTERY

REVOLUTION SERIES OPTIONS



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

WORK FAST. WORK RIGHT.

QUICK CARRY SYSTEM



TRIPLE THREAT UTILITY KIT

Attach tools and accessories directly to the mower with innovative tool-mounting brackets. Includes Bucket Holder Kit, Universal Mount and Trimmer Mount.

Sold separately.

4.6–6.1

Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency (MPH x width of cut). Actual productivity dependent upon conditions.



POWERFUL PROOF

The perfect cut starts with a high-strength steel deck with tip speeds up to 18,500 feet per minute. The heavy-duty rubber discharge chute and dual capture anti-scalp rollers ensure the most even cut.



TURBO FORCE DECK

With heavy-duty cast aluminum spindle housings and the bullnose bumper, you get the master of all-conditions mowing muscle. Pro models available with flat-free semi-pneumatic caster tires.



CONFIDENTLY COMFORTABLE

Easily adjust the seat and ideal seat suspension to your preference. Customize your ride: Lights, Bucket holder, Trimmer mount, Baggers, Mounts, and top 20 attachments.



MyRIDE® SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.

The commercial-grade yet civilian-friendly Z Master 2000 gives you plenty of time and energy back with superbly capable, get-it-done-right productivity. Z Master 2000 is constructed to work and work and work, while not working you over. Using top-grade materials and engineering for both all-job toughness and all-rider ease, you will go fast, powerfully, comfortably, and be the master of your domain.

WORK FAST, WORK RIGHT

Step on it with speeds up to 10 MPH (miles per hour), and sacrifice nothing in quality. Power-packed engines deliver 25 HP* for clear-cut efficiency. Productivity rolls on traction-happy 24" rear tires. Our high-strength steel TURBO FORCE® cutting deck stands up to every challenge, pass after pass, day after day, year after year.

HIGHLY ENGINEERED BRUTE FORCE

This machine is built on a full tubular frame of 7-Gauge high-strength steel for rock-solid durability. Strong, tough cast aluminum forms our spindle housing for long-flying service. Our bullnose bumper is engineered with no-BS toughness.

SMOOTH OPERATOR

Our suspension seats are fully adjustable forward and backward, and customizable to your weight. Save your back and bones with MyRIDE® Suspension System (upgrade). Enjoy human-friendly seats with lumbar support, and perks like a USB port, cup holder and phone holder.

	HD					HDX MyRIDE® SUSPENSION SYSTEM				PRO		
	77281	77283	77285	77291 HDX	77294 HDX	77288						
POWER SYSTEM												
Commercial Engines at 3600 RPM*	Toro® 24.5 hp w/ HDAC					23.5 hp Kawasaki FX (726cc)				▶ 28 hp Briggs & Stratton® Vanguard EFI (810cc)		
Starter	Electric					Electric				Electric		
Heavy-Duty Donaldson® Canister-Style Air Cleaner	Standard					Standard				Standard		
Drive Tires	Voodoo Trac 24" x 9.5" – 12" (61 x 24.1 – 30.5 cm)	▶ Voodoo Trac 24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)	▶ Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)	Voodoo Trac 24" x 10.5" – 12" (61 x 26.7 – 30.5 cm)	▶ Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)	Voodoo Trac 24" x 12" – 12" (61 x 30.5 – 30.5 cm)						
Caster Tires	13" x 6.5" – 6" Pneumatic (33 x 16.5 – 15.2 cm)					13" x 6.5" – 6" Pneumatic (33 x 16.5 – 15.2 cm)				▶ 13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)		
Fuel/Capacity	Gas/7-Gal (26.5 L)					Gas/7-Gal (26.5 L)				Gas/7-Gal (26.5 L)		
Digital Hour Meter	Standard					Standard				Standard		
Hydraulic Drive System	ZT-3400 Integrated Pumps & Wheel Motors					ZT-3400 Integrated Pumps & Wheel Motors				ZT-3400 Integrated Pumps & Wheel Motors		
Maximum Forward Speed	10 mph (16.1 km/h)					10 mph (16.1 km/h)				10 mph (16.1 km/h)		
Clutch	Electromagnetic					Electromagnetic				Electromagnetic		
MOWING DECKS												
Deck Size	48" (121.9 cm)	▶ 52" (132.1 cm)	▶ 60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)						
Cutting Deck	7-Gauge TURBO FORCE®					7-Gauge TURBO FORCE®				7-Gauge TURBO FORCE®		
Bullnose Bumper	Standard					Standard				Standard		
Rubber Discharge Chute	Standard					Standard				Standard		
Deck Lift Design	Standard		▶ Lift Assist Spring			Standard		▶ Lift Assist Spring			Lift Assist Spring	
Spindle Housings	8" (20.3 cm) Dia. Aluminum					8" (20.3 cm) Dia. Aluminum				8" (20.3 cm) Dia. Aluminum		
1" (2.5 cm) Spindle Shaft	Standard					Standard				Standard		
Spindle Bearings	Maintenance-Free					Maintenance-Free				Maintenance-Free		
Adjustable Height of Cut Foot Pedal	Standard, 1.5" – 5" in .25" increments (3.8 – 12.7 cm in .6 cm increments)					Standard, 1.5" – 5" in .25" increments (3.8 – 12.7 cm in .6 cm increments)				Standard, 1.5" – 5" in .25" increments (3.8 – 12.7 cm in .6 cm increments)		
Deck Depth	5.5" (14.0 cm)					5.5" (14.0 cm)				5" (12.7 cm)		
Blades	.204" (.5 cm) Heat-Treated Steel					.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel		
Blade Tip Speed	18,500+ ft/min					18,500+ ft/min				18,500+ ft/min		
Belt Construction	Aramid Fiber V-Belt					Aramid Fiber V-Belt				Aramid Fiber V-Belt		
FEATURES												
MyRIDE® Suspension System												
Comfort Platform	N/A	N/A	N/A	▶ MyRIDE Suspension System				N/A				
Platform Travel	N/A	N/A	N/A	3.0" (7.6 cm)				N/A				
Shocks	N/A	N/A	N/A	1 center / 2 rear				N/A				
Seat	N/A	N/A	N/A	Deluxe Comfort				N/A				
Adjustability	N/A	N/A	N/A	5 Detents, Infinite Adjustability				N/A				
2" Hitch Receiver	Standard	Standard	Standard	Standard				Standard				
Steering Controls	1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened					1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened				1.4" (3.6 cm) Dia. Grips; Adjustable, Dampened		
Operator Seat	Deluxe Suspension					Deluxe Comfort				Deluxe Suspension		
Folding ROPS	Standard					Standard				Standard		
Tool-Mounting Capability												
Side Console / Rear Guard Ready												
LED Lights	Standard					Standard				Optional		
USB Port	N/A					▶ Standard				N/A		
Step Through Floorpan	Standard					Standard				Standard		
Electric Deck Lift Assist	Optional					Optional				Optional		
Warranty**	4-Year 1000-Hour Limited					4-Year 1000-Hour Limited				4-Year 1000-Hour Limited		
WEIGHTS AND MEASUREMENTS												
Weight	870 lbs.	394.6 kg	890 lbs.	403.7 kg	920 lbs.	417.3 kg	1,012 lbs.	459 kg	1,036 lbs.	470 kg	920 lbs.	417.3 kg
ROPS Height (Folded)	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm	49"	124.5 cm
ROPS Height (Upright)	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm	70.5"	179.1 cm
Deck Clearance Width	53"	134.6 cm	56.75"	144.1 cm	63.5"	161.3 cm	66"	167.6 cm	53"	134.6 cm	63.5"	161.3 cm
Deflector Width	63.25"	160.7 cm	67.25"	170.8 cm	75.25"	191.1 cm	75.25"	191.1 cm	63.25"	160.7 cm	75.25"	191.1 cm
Length	82"	208.3 cm	82"	208.3 cm	83"	210.8 cm	84.25"	214 cm	82"	208.3 cm	83"	210.8 cm

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

**See your local Toro dealer or consult owners manual for complete warranty details.

▶ = Step Up Feature