



# TORO® DINGO® TXL 2000

COMPACT UTILITY LOADERS



## OUTSTANDING REACH & LIFT HEIGHT

Thanks to the telescoping loader arm technology, operators are able to backfill behind a retaining wall, dump material into the center of a full-size dump truck or dumpster and offload both rows of a trailer from one side with ease.

HINGE PIN HEIGHT  
OF JUST OVER

**10 FT**



## OUTSTANDING VISIBILITY

With a stand-on operator platform instead of a cab, the TXL 2000 provides 360° visibility. No need for a back-up camera — just turn and look.



## OUTSTANDING CAPACITY

With up to 2,000 lbs (907 kg) of operating capacity, the TXL 2000 has the muscle for demanding jobs.



## EASE OF USE

TXL 2000 control interface is easy to use and master — no special equipment licensing required.

## OTHER FEATURES & BENEFITS

- Kubota D1803 49.6 hp Tier 4 Final with DOC (diesel oxidation catalyst) minimizes downtime with no regeneration required.
- Smart Power technology automatically adjusts traction speed to maximize engine, auxiliary, and traction torque for greater operation efficiency - a selectable option through the info center.
- Selectable traction speed allows operators to customize machine speed based on operator preference and project application.
- Proportional auxiliary control allows the operator to run attachments at their desired speed.



## OUTSTANDING ACCESS

Easy for operators of different sizes to jump on and off the machine instead of getting into and out of a cab.



## OUTSTANDING MANEUVERABILITY

Maneuver in and out of small spaces where other machines just can't go.



		DINGO TXL 2000 WITH TELESCOPING ARMS (MODEL 22530)	DINGO TXL 2000 WITHOUT TELESCOPING ARMS (MODEL 22531)
<b>ENGINE</b>	Engine	49.6 hp (37 kW) Kubota D1803 Diesel	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid Cooled	
	Fuel Tank	18.3 gallons (69.3 liters)	
	Oil Capacity	7.4 quarts (7 liters)	
<b>HYDRAULIC SYSTEM</b>	Hydraulic Pressure	Auxiliary: 3,000 PSI Traction: 4,350 PSI	
	Hydraulic Flow	Auxiliary: 21.4 gpm Traction: 21.5 gpm (81.4 lpm) each pump	
	Reservoir Capacity	15.25 gallons (57.7 liters)	
<b>TRACKS</b>	Standard	Sprocket-drive, 6 road wheels per side	
	Traction	Dual hydrostatic pump	
<b>DIMENSIONS</b>	Track Dimensions	162.2" x 11.8" (413 cm x 30 cm)	
	Wheelbase	53.7" (136.4 cm)	
	Ground Clearance	6.3" (16 cm)	
	Overall Dimensions (WxLxH) With Bucket	54" x 136.9" x 67.8" (137 x 348 x 172 cm)	
	Overall Dimensions (WxLxH) Without Bucket	54" x 98.8" x 67.8" (137 x 251 x 172 cm)	
	Maximum Operating Height	Telescoping 67.8" (172cm)	Non-Telescoping 63.9" (162 cm)
	Hinge Pin Height	123.4" (313 cm)	98.6" (250 cm)
Dump Height	88.9" (226 cm)	64.1" (163 cm)	
Dump Angle	46.3 degrees		
Reach - Fully Raised	45.2" (114.8 cm)	26.1" (66.3 cm)	
Ground Speed	5.4 mph (8.6 km/h)		
Weight	6,655 lbs (3,019 kg)	6,235 lbs (2,828 kg)	
Tip Capacity	5,715 lbs (2,592 kg) retr, 2,620 lbs (1,188 kg) ext.	5,715 lbs (2,592 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	2,000 lbs (907 kg) retr, 920 lbs (417 kg) ext.	2,000 lbs (907 kg)	
Ground Pressure	5.3 PSI		

\*Per ISO 14397-1

