



Reelmaster® 3100-D

SMALL AREA REEL MOWER

FEATURES

- **Productivity** – *Triplex chassis design is highly maneuverable for quick, end-of-row turn arounds. 72" or 85" (183 or 216 cm) cutting widths in combination with up to a 6 mph (10 km/h) mowing speed make the Reelmaster 3100-D fast and effective.*
- **Superior Traction** – *The Series/Parallel 3-wheel drive system provides power to at least two wheels at all times. The result is impressive traction in hilly and wet conditions with minimal wheel slip so it's also gentle on the turf.*
- **Efficiency** – *Powered by a fuel efficient 21.5 hp (16 kW) Kubota® diesel engine, this Reelmaster model provides plenty of power for those challenging cutting conditions, even while operating groomers, rear roller brushes and veritcutters.*
- **Simplicity** – *The Reelmaster 3100-D utilizes a common platform design with other Toro mowers which can improve operator and technician efficiency.*
- **Lightweight Design** – *An ideal combination for turf friendliness, the lightweight and balanced chassis avoids unnecessary weight on your sensitive turf.*
- **Outstanding Quality of Cut** – *Dual Precision Adjustment (DPA) cutting units – featuring Toro's exclusive EdgeSeries™ reels combine to deliver a consistent, high quality cut and superior after-cut appearance, while reducing maintenance with improved reel edge retention.*

An essential trim reel mower for any course.

When you need a reel trim mower whose versatility, performance and after-cut appearance is second to none, the Toro® Reelmaster® 3100-D is the clear choice. With Sidewinder® technology, Toro pioneered the ability to shift cutting units on the fly from side-to-side, reaching turf areas that other mowers simply cannot. It's ideal for mowing around greens and bunkers where conditions can be challenging but when precision control is an absolute must. Add a triplex chassis configuration and Toro's exclusive EdgeSeries™ cutting units and you get an exceptional performing, highly maneuverable reel trim mower that consistently delivers a superior after-cut appearance, day after day.



EdgeSeries™ Reels

©2020 The Toro Company. All rights reserved. Rev. 12/20

Call your Toro distributor at 800-803-8676



Reelmaster® 3100-D Specifications

	REELMASTER 3100-D, MODEL 03170	REELMASTER 3100-D, MODEL 03171 w/SIDEWINDER®
ENGINE	Kubota® liquid-cooled diesel, 3-cylinder, 21.5 hp (16 kW) net @ 2500 RPM. High idle: 2,600 rpm, Low idle: 1,400 rpm (+/- 50 rpm). 68.5 cu. in. (1123 cm) displacement. Tier 4 and Stage V compliant. Pressurized lubrication system with 3.5 U.S. qt. (3.3 liter) capacity. Heavy-duty, radial seal air cleaner. Fuel/water separator with visible bowl.	
CONFIGURATION	Rear mounted engine, front operator position. Rear mounted radiator. Two post ROPS and seat belt standard.	
FUEL CAPACITY	7.5 gallons (28 liters). Biodiesel-Ready for use up to B-20 (20% biodiesel and 80% petroleum blend).	
TRACTION DRIVE	Series/Parallel hydraulic traction circuit provides continuous 3-wheel drive, in mow and transport. Hydrostatic traction drive provides infinitely variable speed in forward and reverse. 6 gallon (23 liter) hydraulic system capacity.	
GROUND SPEED	Mow: 0-6 mph (0-10 km/h); Transport: 0-9 mph (0-14 km/h). Reverse: 0-4 mph. (0-6 km/h).	
CONTROLS	Forward and reverse traction control pedals, mow/transport lever, hand activated park brake, ignition key switch, tilt steering wheel lock, PTO switch, throttle, joystick control for cutting unit raise and lower (and for moving cutting units side-to-side on Sidewinder equipped models), cutting unit transport lock, reel speed and backlap control knob.	
GAUGES	Hour meter, fuel gauge, cluster gauge with glow plug and charge indicator lights, and low engine oil pressure and high coolant temperature warning lights (high temperature safety shut off).	
ELECTRICAL & INTERLOCKS	12-volt, 585 cold cranking amps at 0° F (-18° C), 40 amps with regulator/rectifier. Traction pedal, operator presence in seat, PTO engage or disengage, and cutting unit mow or transport safety interlock switches.	
TIRES	Front: 20 x 12-10, 4-ply Turf Tread. Rear: 20 x 10-10, 4-ply Turf Tread	
FRAME	Formed steel, welded steel and steel tubing.	
BRAKES	Hydrostatic service brake, hand-operated parking brake.	
STEERING	Power steering with tilt steering wheel.	
OVERALL DIMENSIONS	Track Width: 55" (140 cm) Overall Height: 76" (193 cm) with ROPS Wheel Base: 56" (142 cm) Transport Width: 80" (203 cm) in 72" (183 cm) WOC, 92" (234 cm) in 85" (216 cm) WOC Overall Length: 93" (248 cm)	
WEIGHT	Approx. Weight with 27-inch Cutting Units: 1,860 lbs. (844 kg)	Approx. Weight with 27-inch Cutting Units: 1,950 lbs. (885 kg)
CUTTING UNIT CONFIGURATION	Fixed position cutting units.	Operator controlled moveable cutting units travel ±12" (30 cm) left or right from center; total of 24" (61 cm) of infinite variability.
CUTTING UNIT OFFSET	3" (7.6 cm) in 72" (183 cm) width of cut 10" (25 cm) in 85" (216 cm) width of cut	Maximum 15" (38 cm) in 72" (183 cm) width of cut. Maximum 22" (56 cm) in 85" (216 cm) width of cut.
CERTIFICATION	This product complies with the American National Standards Institute (ANSI B71-4 – 2017) and European Community specifications (CE Certified). EN ISO 5395.	
WARRANTY	Two-year limited warranty, refer to operators manual for details.	

	27" CUTTING UNITS (03189, 03190) / 32" CUTTING UNITS (03191)
TYPE	Three hydraulically-driven, balanced, 7" (17.8 cm) diameter reels. Cutting units interchangeable to all three positions.
REEL BLADE OPTIONS	8 and 11-blade reels available for 27" (68.6 cm) cutting unit. 8-blade reels available for 32" (81.3 cm) cutting unit.
HOC RANGE	Height of cut ranges 0.25"-2" (6.4-50.8 mm) standard in floating position, 1.5" to 2.5" (3.8-6.4 cm) in fixed position.
CUTTING WIDTH	72" (183 cm), or 85" (216 cm) width of cut dependent on cutting unit selection.
CLIP FREQUENCY/BACKLAPPING	Manually controlled variable reel speed for adjustment of clip frequency. Standard on-board backlapping.
BEDKNIFE-TO-REEL ADJUSTMENT	Dual point adjustment (DPA) of bedknife to reel.
ROLLERS	Full roller standard on rear of cutting unit and plastic front Wiehle roller.

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.





Reelmaster® 3100-D Accessories*

TRACTION UNIT ACCESSORIES	
115-4754	myTurf® Wireless Hour Meter Assembly
30629	Premium Seat
127-2796	Smooth Tire (front only)
03614	Golf Ball Guard
31696	LED Light Kit

TRACTION UNIT SUNSHADE	
30669	Universal Sunshade - White
30671	Universal Sunshade - Red
30358	Bimini Canvas Sunshade
03248	Switch Panel
03247	Operator Cooling Fan
138-2700	Worklights
138-2699	Beacon
138-2993	Wire Harness
136-3315	Required Wheel Weight Kit

CUTTING UNIT OPTIONS	
03189	27" (69 cm) 8-Blade DPA Cutting Unit
03190	27" (69 cm) 11-Blade DPA Cutting Unit
03191	32" (81 cm) 8-Blade DPA Cutting Unit
03203	27" (69 cm) Verticutter Cutting Unit

27" (69 CM) DPA CUTTING UNIT ACCESSORIES	
03240	Universal Groomer
03778	27" (69 cm) Groomer Cartridge
03242	27" (69 cm) Universal RRB Kit
03243	Rear Roller Brush Kit
132-7125	Broomer Kit
03185	Grass Basket Kit
114-9368	Rear Roller Scraper Kit
114-9372-03	Wiehle Roller Scraper
114-9376	Comb/Scraper Kit
119-0630	Shoulder Roller Asm
114-9381-03	Shoulder Roller Scraper
114-9383	Full Front Roller
114-9386-03	Full Front Roller Scraper
119-4286	Short Rear Roller Asm
140-5514	HD High HOC Brush

32" (81 CM) DPA CUTTING UNIT ACCESSORIES	
03246	Rear Roller Brush Kit
133-0193	5-Blade Service Reel
114-9369	Rear Roller Scraper Kit
114-9373-03	Wiehle Roller Scraper
114-9377	Comb/Scraper Kit
140-5513	HD High HOC Brush
114-9384	Full Front Roller
114-9387-03	Full Front Roller Scraper
119-0640	Shoulder Roller Asm
114-9382-03	Shoulder Roller Scraper
119-4288	Short Rear Roller Asm

BEDKNIFE OPTIONS	
114-9388	Standard (27") - (03189, 03190)
114-9390	Heavy-Duty (27") (03192)
120-1641	Extended Low-Cut (27")
112-8910	EdgeMax™ (27")
114-9389	Standard (32") - (03191)
114-9391	Heavy-Duty (32")
120-1642	Extended Low-Cut (32")

CUTTING UNIT OPTIONS (27"/32")	
03244	End Weight Kit
119-0649	Trim/HD Collar Kit (6 per roller)
119-0635	RM3100 Tipper Roller Kit
98-1852	Gauge Bar
04399	Turf Evaluator
136-3635	High HOC Turf Evaluator

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

