

TORO. Turf Pro[™] 500/300 & Range Pro[™] 100

AUTONOMOUS MOWERS & RANGE PICKER

F EATURES

Turf Pro: Cutting Performance

- Mow up to 18.5 acres (75,000 m2)*
- Increased mowing frequency removes less leaf tissue and produces shorter clippings
- Adjustable mowing patterns can be utilized to achieve multiple aesthetics
- Multiple floating cutting heads with anti-friction discs and retractable blades at high rotation speed

Packed with Technology

- Self-charging
- Ultra-precise navigation via GNSS RTK technology – no boundary wires required
- Customize settings at your fingertips working perimeters, no-go zones, mowing pattern, cutting height, transport paths, etc.

Range Pro: Labor Savings

- Collects up to 12.500 balls in 24 hours
- Automatically returns to charging station/ball drop area
- Works simultaneously with Turf Pro
- Operates in pattern and ability to define and schedule high density areas

Fleet Management

• Wireless monitoring and control of your units through a computer or mobile phone

Intelligent productivity.

From performance and cost savings to more time to focus on the bottom line, the Toro Turf Pro and Range Pro put innovation and efficiency at your command.

With GNSS RTK technology, the Turf Pro navigates with precision, enabling it to mow a consistent pattern with minimal overlap.

The Range Pro 100 autonomous golf ball picking robot enables you to give your staff other tasks, to extend your opening hours and even to lose fewer balls.

The mobile app allows you to remotely control your robot or fleet of robots. Start or stop your machines at any time from anywhere, receive alerts, create schedules, and automate certain processes.



Call your Toro distributor at 800-803-8676



Turf Pro[®] & Range Pro[®] Specifications[®]

	TURF PRO 500, MODEL 30921 (US or CAN)	 TURF PRO 300, MODEL 30923 (US or CAN)	RANGE PRO 100, MODEL 30931 (US or CA
	LiFeP04		
NOMINAL VOLTAGE	25.6 V		
NOMINAL CAPACITY	19.2 Ah		
	491.5 Wh		
WORKING TEMPERATURE Range	23°F to 140°F (-5°C to 60°C)		Discharge: 23°F to 140°F (-5°C to 60°C) Charge: 37.4°F to 134.6°F (3°C to 57°C)
AVERAGE WORKING TIME	110 minutes	280 minutes	110 minutes
VERAGE TIME TO FULL CHARGE	90 minutes		
SECURITY PIN CODE	Yes		
GPS LOCATION	RTK Base Station – Model 30915		
ROBOT MANAGEMENT VIA SERVER & APP	Standard		
MAXIMUM WORKING AREA**	18.5 acres (74,867 m²)	11.1 acres (44,920 m²)	11.1 acres (44,920 m²)
ECOMMENDED WORKING AREA	13.6 acres (55,037 m²)	8.6 acres (34,803 m²)	7.4 acres (29,947 m²)
MOWING/PICKING WIDTH	40.7" (103.3 cm)	25" (63.3 cm)	37.6" (95.6 cm)
WORKING SPEED	2.2 mph (3.6 km/h)	1.7 mph (2.8 km/h)	2.2 mph (3.6 km/h)
MAXIMUM SLOPE	Turf Pro 500: 30% (17°) Turf Pro 500S: 45% (24°)	35% (19.5°)	30% (17°)
NUMBER OF CUTTING HEADS	5	3	N/A
NUMBER OF CUTTING BLADES	15	9	N/A
1INIMUM CUT HEIGHT (STANDARD DISC / LOW HEIGHT DISC)	0.75" / 0.6" (20 mm / 15 mm)		N/A
MAXIMUM CUT HEIGHT (STANDARD DISC / LOW HEIGHT DISC)	3.9" / 3.5" (100 mm / 90 mm)		N/A
ADJUSTMENT OF CUTTING HEADS	Electronic		
MAXIMUM NOISE LEVEL	52 dB		
WEIGHT	Turf Pro 500: 156.5 lbs (71 kg) Turf Pro 500S: 158.7 lbs (72 kg)	105.8 lbs (48 kg)	187.4 lbs (85 kg)
DIMENSIONS (LxWxH)	43.7 x 50.3 x 20.3" (111 x 127.8 x 51.5 cm)	39.4 x 41.1 x 18.3" (100.2 x 104.4 x 46.6 cm)	46.5 x 52.8 x 21.3" (118 x 134 x 54 cm)
ONAR FOR OBSTACLE DETECTION	5 4		4
RESISTIVE BUMPER FOR COLLISION DETECTION	1		
FRONT LIFT SENSORS	2 N/A		
REAR LIFT SENSORS	2		
REAR COLLISION SENSORS	2		
ROLL OVER / TILT SENSORS	1		
CUTTING HEAD DEFLECTORS	(2) 1 on each outer cutting head	N	I/A
		RANGE PRO 100 BALL PICKER	
BASKET CAPACITY	320–350 balls		
IEAN BALL COLLECTION CAPACITY	15,600 balls/day		
MAXIMUM BALL COLLECTION CAPACITY	19,500 balls/day		
PICK UP DISKS	16, anti-friction pick-up discs		
WARRANTY	Limited 2-year Warranty. 1-Year Warranty: Front wheels, front wheel pivots, axles, bearings, cutting head bearings, pantographs, lift jack		

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.

Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

**Mowing capacity and maximum working area may vary depending on the quality and layout of the terrain and the presence of obstacles.

