



DINGO® TX 550

COMPACT UTILITY LOADERS

The Dingo® TX 550 delivers consistent power to take on landscaping jobs quickly and efficiently. Combining high-level performance with exceptional reliability, the compact size and cutting-edge hydraulic system ensure its ultimate tool carrier title. For tackling landscaping, digging, and trenching jobs, the TX 550 offers a faster solution, lightweight maneuverability and minimal impact on turf.

KEY FEATURES

Diesel Power: Provides long-lasting, reliable power for increased productivity and reduced downtime.

Hydraulic Performance: Offers power similar to larger machines without the added bulk.

Compact Size: The Dingo TX 550 is the right size for jobs that require more than handheld tools, in spaces that don't allow for bulky machinery.

Turf Friendly: The lightweight, narrow design produces minimal turf disturbance.

Easy Operation: Intuitive controls allow both first-time users and experienced operators to work quickly and efficiently.

Walk-Behind: The only walk-behind loader in its class, the Dingo TX 550 is designed for simple maneuverability and unbeatable precision in tight spaces.

Built on Success: The Dingo TX 550 is built on a 20-year foundation of durability, longevity and dependability.



TORO® DINGO® TX 550

SPECIFICATIONS

		DINGO TX 550 NARROW TRACK (MODEL 22374)	DINGO TX 550 WIDE TRACK (MODEL 22377)
ENGINE	Engine	Kubota® D902 diesel 24.8 HP* (18.5kw)	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid Cooled	
	Fuel Tank	6.0 gallons (23 liters)	
	Oil Capacity	3.84 quarts (3.63 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI (20,684 kPa)	
	Hydraulic Flow	Traction: 16.9 gpm (each pump) Auxiliary: 13.8 gpm	
	Reservoir Capacity	10 gallons (37.8 liters)	
TRACKS	Standard	Sprocket-drive, 10 road wheels per side	
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Dimensions	96.6" x 5.9" (245.3 cm x 14.9 cm)	96.6" x 9.5" (245.3 cm x 24.1 cm)
	Wheelbase	31.2" (79.2 cm)	
	Ground Clearance	4.6" (11.6 cm)	
	Overall Dimensions (WxLxH) With Bucket	33.7" x 92" x 46.1" (86.5 x 233.6 x 117.0 cm)	41" x 92" x 46.1" (104.1 x 233.6 x 117.0 cm cm)
	Overall Dimensions (WxLxH) Without Bucket	33.7" x 70.7" x 46.1" (86.5 x 179.5 x 117.0 cm)	41" x 70.7" x 46.1" (104.1 x 179.5 x 117.0 cm cm)
	Maximum Operating Height	90.1" (228.8 cm)	
	Hinge Pin Height	65.8" (167.1 cm)	
	Dump Height	46.1" (117.0 cm)	
	Dump Angle	38-degrees	
	Reach - Fully Raised	21.8" (55.3 cm)	
	Ground Speed	Fwd: 0-4.5 mph (0-7.2 km/h) Rev: 0-2.0 mph (0-3.2 km/h)	
	Weight	1,904 lbs (863.6 kg)	2,013 lbs (913.0 kg)
	Tip Capacity	1,580 lbs. (716.6 kg)	1,530 lbs. (693.9 kg)
	Rated Operating Capacity (35% of Tip Capacity)*		553 lbs. (250.8 kg)
	Ground Pressure	5.2 PSI	3.4 PSI

*Per ISO 14397-1



Count on it.