

TORO

STX-26 STUMP GRINDER

TREE CARE

The Toro® STX-26 stump grinder brings simple control and serious power to tree care maintenance. The STX-26 stump grinder features Toro's patented Dingo® TX-style control system that is intuitive and easy to operate. The Intelli-Sweep® cutter head control feature automatically slows the sweep speed of the cutting head based on the load of the wheel, so heavy cutting loads won't bog down the engine. And, with a powerful Kawasaki® engine, tracks and transport speeds exceeding 4 mph (6.4 km/h), the STX-26 provides ample power with a light footprint for exactly what you need to get in and get to work fast.

FEATURES

HYDRAULICALLY DRIVEN CUTTER HEAD

13.5 gpm of hydraulic flow directly to the cutter head to maximize performance.

HI-DRIVE TRACK SYSTEM

Low center of gravity increases stability on side hills or uneven terrain and the track design allows for zero turn capability for those difficult to access stumps.

USER-FRIENDLY DESIGN

All-hydraulic sweep control valve facilitates side-to-side feathering, plus the offset cutting head results in excellent visibility, regardless of stump size and the innovative grinder teeth can be rotated for added longevity and are easily replaceable.



PATENTED TX-STYLE CONTROL SYSTEM, INTUITIVE & EASY TO OPERATE

Easy-to-use control system offers smooth operation and fewer levers/knobs than conventional stump grinders. An armrest near the joystick also reduces operator fatigue.

- 1 Steering System (forward, reverse, turn) allows for zero turn capability
- 2 Sweep, lift/lower and engagement of grinder head



TORO® STX-26 STUMP GRINDER

SPECIFICATIONS

STX-26 (MODEL 23208)

Engine Kawasaki® FX-730V
26 HP 4-cycle gasoline air-cooled engine

Hydraulic Flow 13.5 gpm hydraulic flow to cutter head;
10 gpm of hydraulic flow to each track

Hydraulic Pressure 2,750 psi (18,960.8 kPa)

Wheel 19" (48.2 cm) diameter to tooth;
0.75" (1.9 cm) thick; 12 grinder teeth

Cutter Depth 12.5" (31.7 cm) below grade

Cutter Height 33" (83.8 cm) above grade

Head Swing 47" (119.3 cm) arc x 90° sweep arc

Dimensions (WXLXH)
34" x 78" x 46"
(86.3 x 198.1 x 116.8 cm)

Weight 1,200 lbs (544.3 kg)

Max. Travel Speed 4.2 mph (6.7 km/h) forward;
1.6 mph (2.5 km/h) reverse



Intelli-Sweep® Cutter Head Control

Automatically adjusts sweep speed based on load on wheel to maintain optimal operation and minimize stress on the machine - adding up to increased productivity and minimized maintenance.

A custom Toro trailer for the STX-26 makes it easy to load, transport, and unload your machine to maximize jobsite efficiency.

