

TURF RENOVATION

SPRAYMASTER



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

Get the job done better, faster and easier with the stand-on SprayMaster. The updated design creates more stability and balance resulting in less turf tear up and the flip up hopper allows for easy maintenance. Maximize ground coverage and reduce fill-up stops with two spray tanks with up to 60-gallon capacity, 250-pound hopper and 5-gallon fuel tank.

MAXIMUM OF
4.0 Acres
COVERED PER HOUR



FILL UP HOPPER

Maintenance is a breeze with the flip up hopper that provides easy access to the engine.



LARGE CAPACITY

Maximize ground coverage and reduce fill-up stops with two spray tanks that hold up to 60 gallons, 250-pound hopper capacity, and a 5-gallon fuel tank.



RIDE IN STYLE

The new design allows for increase balance and stability and features larger wheels, improved hopper cover, and custom-stitched knee pad.

| | LEAN-TO-STEER SPREADER/SPRAYER | SPRAYMASTER 24 GALLON STAND-ON | SPRAYMASTER 40 GALLON STAND-ON | SPRAYMASTER 60 GALLON STAND-ON | SPRAYMASTER 60 GALLON STAND-ON |
|--------------------------|---|---|-----------------------------------|--|-----------------------------------|
| | 34230 | 34246 | 34242 | 34240 | 34243 |
| POWER AND DRIVE SYSTEM | | | | | |
| Engine* | Kohler® 9.5 hp | 16 hp Twin Vanguard | ▶ 21 hp Twin Vanguard | | ▶ 23 hp Twin Vanguard |
| Engine Orientation | Horizontal | | | | |
| Fuel Capacity | Gas/1.85 Gal (7 L) | 5 Gal (18.9 L) w/fuel gauge | | | |
| Electric Start | Yes | Yes | Yes | Yes | Yes |
| Transmission | Hydrostatic | | | | |
| Maximum Forward Speed | 5.5 mph (8.6 km/h) | 7 mph (11.3 km/h) | ▶ 10 mph (16.1 mph) | 10 mph (16.1 mph) | 10 mph (16.1 mph) |
| SPREADER SYSTEM | | | | | |
| Hopper Size | 175 lbs (79.4 kg) | 150 lbs (68.0 kg) | ▶ 250 lbs (113.4 kg) | 250 lbs (113.4 kg) | 250 lbs (113.4 kg) |
| Fertilizer Capacity | 225 lbs (102.1 kg) | 2 Rear Boxes - 50 lbs (22.7 kg) each | | | |
| Spread Width | Adjustable from 4'-22" (1.2 - 6.7 m) | Adjustable up to 25' (0.9 - 7.6 m) | | | |
| Deflector Shield | Molded Plastic | Molded Plastic | Molded Plastic | Molded Plastic | Molded Plastic |
| Spinner Motor | Electric | Electric | Electric | Electric | Electric |
| SPRAY SYSTEM | | | | | |
| Pump Capacity | 5 GPM | 5.3 GPM | | | |
| Spray Capacity | 20 Gal | 24 Gal (2 - 12 Gal) | ▶ 40 Gal (2 - 20 Gal) | ▶ 60 Gal (2 - 30 Gal) | |
| Spray Width | 4 or 10 ft (1.2 or 3.0 m) | 2, 4, 6 or 8 ft (0.6, 1.2, 1.8 or 2.4 m) | | ▶ 2, 4, 6, 8 or 10 ft (0.6, 1.2, 1.8, 2.4 or 3.0 m) | |
| Boom | N/A | 3-Section, Bi-Directional Breakaway Wings | | | |
| Spot Spray Hose | 15 ft (4.6 m) Coil Hose | 15 ft (4.6 m) Coil Hose | ▶ 75 ft (22.9 m) Hose Reel | | ▶ 75 ft (22.9 m) Hose Reel |
| WEIGHTS AND MEASUREMENTS | | | | | |
| Weight | 500 lbs. (226.8 kg) | 698 lbs. (316.7 kg) | 896 lbs. (406.4 kg) | 912 lbs. (413.7 kg) | 912 lbs. (413.7 kg) |
| Height | 51.5" (130.8 cm) | 48" (121.9 cm) | 50" (127.0 cm) | 50" (127.0 cm) | 50" (127.0 cm) |
| Width | 35.5" (90.2 cm) | 36" (91.4 cm) | 46" (116.8 cm) | 52" (132.1 cm) | 52" (132.1 cm) |
| Length | 67.5" (171.5 cm) | 70.5" (179.1 cm) | 73" (185.4 cm) | 72" (182.9 cm) | 72" (182.9 cm) |

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.