

GRANDSTAND®

STAND-ON MOWERS

SEE PAGE 2 FOR BATTERY
REVOLUTION® SERIES OPTIONS



STAND UP TO ANY TERRAIN.

Bumpy patches and challenging terrain are all in a day's work—but feeling them doesn't need to be. GrandStand® combines the speed and comfort of a zero-turn rider with the on-and-off ease of a walk-behind for speed and maneuverability.

IMPROVE PRODUCTIVITY

With easy access on and off the machine—up to 10.5 gallons of fuel capacity on 48", 52", 60" and 72" models—to mow longer with fewer stops.

INDUSTRY LEADING WARRANTY

Toro stands by you years after you purchase your mower.

GAIN SPEED AND PERFORMANCE

With a new max forward ground speed of up to 12 mph and responsive solid drive linkage. *(Select models only.)*

SAVE MAINTENANCE AND TIME

With no hydraulic hoses, no daily/weekly grease points and a new engine design that allows extra room for service access. The fuel tank can also be removed without draining for easy service access to the transmission and controls.



TRACTION AND HANDLING

A wide stance and optimal balance enhance hillside stability and control. Operators can shift weight as needed to further enhance performance.



CUSHIONED SUSPENSION

Flex-Ride operator platform suspension self-compensates for operators of all sizes, resulting in less fatigue and higher productivity throughout the day.



POWERED BAGGER

Compact side-mounted soft twin bagger and vertically mounted blower allow maneuverability in tight spaces and maximum visibility.



HIGHER HORSEPOWER

Effortlessly tackle demanding jobs with an upgraded 35 hp* Kawasaki FX1000 999cc engine. *(Models 72507 and 72512)*



2-IN-1 VERSATILITY

Foldable operator platform instantly converts the machine to a walk-behind. It easily lowers back down when it's time to ride, saving time and trailer space.

GrandStand® Series helps you save time, money and trailer space with multi-season flexibility and a foldable operator platform.

2.6–5.5

Maximum Acres/Hour

Based on 90% efficiency (MPH x width of cut).
Actual productivity dependent upon conditions.

	GRANDSTAND®																	
	72504		72518		72505		72519		72513		72509		72520 <i>LIMITED QUANTITY</i>		HDX 72506			
POWER SYSTEM																		
Commercial Engines at 3600 RPM*	22 hp Kawasaki FX (726cc)		▶ 23 hp Kohler® Command PRO® EFI (747cc)		22 hp Kawasaki FX (726cc)		▶ 25 hp Kohler Command PRO EFI (747cc)				23.5 hp Kawasaki FX730V (726cc)		Briggs 28 HP (883cc)		31 hp Kawasaki FX921 (999cc)			
Starter	Electric															Electric		
Heavy-Duty Canister Air Cleaner	▶ Standard															▶ Standard		
Drive Tires	▶ 20" x 10.5" – 8" (50.8 x 26.7 – 20.3 cm)															▶ 24" x 9.5" – 12" Turf (61 x 24.1 – 30.5 cm)		
Caster Tires	11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)															13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)		
Fuel/Capacity	Gas/10.5-Gal (39.7 L)															Gas/10.5-Gal (39.7 L)		
Digital Hour Meter	Standard															Standard		
Hydraulic Drive System	▶ Unitized Pumps & Wheel Motors															▶ Unitized Pumps & Wheel Motors		
Pump	10cc/rev															13cc/rev		
Wheel Motor	10 cir															13cc/rev		
Maximum Forward Speed	▶ 10 mph (16.1 km/h)															▶ 12 mph (19.3 km/h)		
Throttle Control	Manual															▶ Electronic		
Clutch	Electromagnetic															Electromagnetic		
MOWING DECKS																		
Deck Size	▶ 48" (121.9 cm)		48" (121.9 cm)		▶ 52" (132.1 cm)		52" (132.1 cm)		▶ 60" (152.4 cm)		60" (152.4 cm)		60" (152.4 cm)		52" (132.1 cm)			
Cutting Deck	7-Gauge TURBO FORCE®															7-Gauge TURBO FORCE®		
Bullnose Bumper	Standard															Standard		
Adjustable Discharge Baffle	Standard															Standard		
Rubber Discharge Chute	Standard															Standard		
Deck Lift Design	▶ Extension Spring															▶ Extension Spring		
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum															9 3/8" (23.8 cm) Diameter Cast Aluminum		
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard															Standard		
Spindle Bearings	Maintenance-Free															Maintenance-Free		
Cutting Height	▶ 1.5" – 5.5" (3.8 – 14 cm)															▶ 1.5" – 5.0" (3.8 – 12.7 cm)		
Blades	.204" (.5 cm) Heat-Treated Steel															.204" (.5 cm) Heat-Treated Steel		
Blade Tip Speed	18,500+ ft/min															18,500+ ft/min		
Belt Construction	Aramid Fiber V-Belt															Aramid Fiber V-Belt		
Anti-Scalp Rollers	▶ Optional								▶ Standard								Standard	
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)															3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		
FEATURES																		
Steering Controls	Twin Lever															Twin Lever		
Operator Platform	Foldable Operator Platform with Suspension															Foldable Operator Platform with Suspension		
WEIGHTS AND MEASUREMENTS																		
Weight	890 lbs.	403.7 kg	881 lbs.	399.6 kg	898 lbs.	407.3 kg	895 lbs.	406 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	941 lbs.	426.8 kg	1061 lbs.	481.3 kg		
Height	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	48"	121.9 cm	50.25"	127.6 cm		
Deck Clearance Width	49.5"	125.7 cm	49.5"	125.7 cm	53.5"	135.9 cm	53.5"	135.9 cm	61.5"	156.2 cm	61.5"	156.2 cm	61.5"	156.2 cm	N/A	N/A		
Deflector Width	63.5"	161.3 cm	63.5"	161.3 cm	67.5"	171.5 cm	67.5"	171.5 cm	75.5"	191.8 cm	75.5"	191.8 cm	75.5"	191.8 cm	53.5"	135.9 cm		
Length (Platform Up)	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	61"	154.9 cm	65"	165.1 cm	65"	165.1 cm	65"	165.1 cm	71"	180.3 cm		
Length (Platform Down)	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	75"	190.5 cm	79"	200.7 cm	79"	200.7 cm	79"	200.7 cm	85.5"	217.2 cm		

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.

As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

▶ = Step Up Feature

	GRANDSTAND®															
	HDX 72510		HDX 72514		HDX 72517		HD+ 72507		HD+ 72512		HDM 74534		HDM 74532		HDM 74535	
POWER SYSTEM																
Commercial Engines at 3600 RPM*	31 hp Kawasaki FX921 (999cc)		37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		37 hp Briggs & Stratton® Vanguard® EFI w/Oil Guard (993cc)		35 hp Kawasaki FX1000 (999 cc)				15 hp Kawasaki® FS (603cc)		18.5 hp Kawasaki FS600V (603 cc)			
Starter	Electric						Electric				Electric		Electric			
Heavy-Duty Canister Air Cleaner	▶ Standard						▶ Standard				N/A		▶ Standard			
Drive Tires	▶ 24" x 12" – 12" Turf (61 x 30.5 – 30.5 cm)						20 in. x 10.5 in. - 8 in. (50.8 cm x 26.7 cm - 20.3 cm)				18" x 8.5" – 8" (45.7 x 21.6 – 20.3 cm)		21 in. x 7 in. - 10 in. (53.3 cm x 17.7 cm - 25.4 cm)			
Caster Tires	13" x 6.5" – 6" Flat-Free Semi-Pneumatic (33 x 16.5 – 15.2 cm)						11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)				11" x 4" – 5" Flat-Free Semi-Pneumatic (27.9 x 10.2 – 12.7 cm)		9 in. x 4.5 in. - 5 in. Semi-Pneumatic (22.8 cm x 11.4 cm - 12.7 cm)			
Fuel/Capacity	Gas/10.5-Gal (39.7 L)						Gas/10.5-Gal (39.7 L)				Gas/7.8-Gal (29.5 L)		Gas/5-Gal (18.9 L)			
Digital Hour Meter	Standard						Standard				Standard		Standard			
Hydraulic Drive System	▶ Unitized Pumps & Wheel Motors						▶ Unitized Pumps & Wheel Motors				Pumps & Wheel Motors		▶ Unitized Pumps & Wheel Motors			
Pump	13cc/rev						10 cc/rev				10cc/rev		13cc/rev			
Wheel Motor	13cc/rev						10 cc/rev				10 cir		13cc/rev			
Maximum Forward Speed	▶ 12 mph (19.3 km/h)						▶ 12 mph (19.3 km/h)				8 mph (12.9 km/h)		7.5 mph (12.0 km/h)			
Throttle Control	▶ Electronic						▶ Electronic				Manual		▶ Electronic			
Clutch	Electromagnetic						Electromagnetic				Electromagnetic		Electromagnetic			
MOWING DECKS																
Deck Size	60" (152.4 cm)		60" (152.4 cm)		▶ 72" (182.9 cm)		52" (132.1 cm)		60" (152.4 cm)		36" (91.4 cm)		32" (81.2cm)		36" (91.4 cm)	
Cutting Deck	7-Gauge TURBO FORCE®						7-Gauge TURBO FORCE®				7-Gauge TURBO FORCE®		7-Gauge TURBO FORCE®			
Bullnose Bumper	Standard						Standard				Standard		Standard			
Adjustable Discharge Baffle	Standard						Standard				Standard		Standard			
Rubber Discharge Chute	Standard						Standard				Standard		Standard			
Deck Lift Design	▶ Extension Spring						▶ Extension Spring				Compression Spring		▶ Extension Spring			
Spindle Housings	9 3/8" (23.8 cm) Diameter Cast Aluminum						9 in / 22.9 cm Diameter Cast Aluminum				Cast Iron		7/75 in/19.7cm Dia Cast Aluminum			
1" (2.5 cm) Heavy-Duty Spindle Shaft	Standard						Standard				Standard		Standard			
Spindle Bearings	Maintenance-Free						Maintenance-Free				Maintenance-Free		Maintenance-Free			
Cutting Height	▶ 1.5" – 5.0" (3.8 – 12.7 cm)						▶ 1.5" – 5.0" (3.8 – 12.7 cm)				1.0" – 5.0" (2.5 – 12.7 cm)		1.0" - 4.5" (2.54 - 11.4 cm)			
Blades	.204" (.5 cm) Heat-Treated Steel						.204" (.5 cm) Heat-Treated Steel				.25" (.6 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel			
Blade Tip Speed	18,500+ ft/min						18,500+ ft/min				18,500+ ft/min		18,500+ ft/min			
Belt Construction	Aramid Fiber V-Belt						Aramid Fiber V-Belt				Aramid Fiber V-Belt		Aramid Fiber V-Belt			
Anti-Scalp Rollers	Standard						Optional		Standard		N/A		Rear Only - Standard			
Carrier Frame Construction	3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)						3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)				3" x 1.5" x 12-Gauge (7.6 cm x 3.8 cm x 12-Gauge)		3"x1.5"x10-Gauge (7.6cmx3.8cmx10-Gauge)			
FEATURES																
Steering Controls	Twin Lever						Twin Lever				Twin Lever		Twin Lever			
Operator Platform	Foldable Operator Platform with Suspension						Foldable Operator Platform with Suspension				Foldable Operator Platform with Suspension		Foldable Operator Platform with Suspension			
WEIGHTS AND MEASUREMENT																
Weight	1091 lbs.	494.9 kg	1100 lbs.	499.0 kg	1193 lbs.	541.1 kg	949 lb	430 kg	1004 lb	455 kg	833 lbs.	377.8 kg	702 lbs	318.4 kg	779 lbs	353.3 kg
Height	50.25"	127.6 cm	50.25"	127.6 cm	50.25"	127.6 cm	48"	122 cm	48"	122 cm	48"	121.9 cm	47.3"	120.1 cm	47.3"	120.1 cm
Deck Clearance Width	N/A	N/A	N/A	N/A	N/A	N/A	54"	137 cm	62"	158 cm	37.6"	95.5 cm	N/A	N/A	N/A	N/A
Deflector Width	61.5"	156.2 cm	61.5"	156.2 cm	73.75"	187.3 cm	68"	172 cm	76"	193 cm	51.6"	131.1 cm	44.9"	114 cm	48.0"	122 cm
Length (Platform Up)	73.5"	186.7 cm	61.5"	156.2 cm	73.75"	187.3 cm	61"	145 cm	65"	164 cm	61"	154.9 cm	58.1"	147.5 cm	58.1"	147.5 cm
Length (Platform Down)	88.0"	223.5 cm	75.25"	190.5 cm	87.75"	222.9 cm	75"	191 cm	79"	201 cm	74"	188 cm	N/A	N/A	N/A	N/A

* The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995.
As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower.

► = Step Up Feature