

TORO

TORO® MAXI SNEAKER® 370

VIBRATORY PLOW

The Toro Maxi Sneaker® 370 delivers powerful plowing in a compact, maneuverable package. The Yanmar® 1.6L, liquid cooled engine, provides reliable power while plowing or trenching while the hydraulic steering allows articulation to a centerline turning radius for maximum maneuverability. It all adds up to reliable performance job after job.

PRECISE CONTROL

Low-effort, dual-lever ground drive controls for creep and transport modes.

EASE OF OPERATION

Optimized operator's position allows operator to see all 4 tires while trenching, plowing or transporting. Foldable ROPS allows for easier transportation and accessibility.



EASY ACCESS

With optional 23" (58 cm) tires mounted narrow and inward, allows easy access to tight spaces.

comes standard with 26" tires



EASY-TO-READ DISPLAY

Digital display allows operator to view system gauges and indicators for easier visibility and use.



CONSISTENT PLOWING

Optimized plow design provides down pressure to maintain consistent plowing up to 24" deep in a variety of conditions.



TRACTION AND STABILITY

Minimize impact on turf with optional dual wheel configuration. Dual wheels available in two sizes (23" and 26").

SPECIFICATIONS

MODEL CONFIGURATION	25545T 26" tires, vibratory plow, hydra-borer	25546T 26" tires, vibratory plow, hydra-borer, trencher
POWER		
Engine	Yanmar® 3TNV88C-DTR4	
Fuel Type	Diesel	
Fuel Tank Capacity	7.1 gal (26.9 L)	
Coolant Capacity	10.8 qt (10.2 L)	
Oil Capacity	5.5 qt (5.2 L)	
Displacement	100.2 cubic inches (1.642 L)	
Rated Speed (Idle)	1,400	
Net Power Rating per SAE J1349	36.8 hp (27.5 kW)	
Rated Speed	3,030 rpm	
Battery	12-Volt, 55 amp, 775 CCA	
PERFORMANCE		
Ground Drive Pressure	Hydrastatic, Closed Loop	
Ground Drive Pump Flow Rate	24.8 gpm (94 L/m)	
Attachment Pump Flow Rate	15.6 gpm (59 L/m)	
Ground Drive Speed; Forward & Reverse	0 to 4.0 mph (0 to 6.4 km/h)	
DIMENSIONS		
Width (with 26x12x12 tires)	40.8" (103.6 cm) mounted narrow 46.7" (118.6 cm) mounted wide 66.0" (167.6 cm) dual	
Wheelbase	48.0" (122 cm)	
Overall Height (with ROPS extended)	87.0" (221.0 cm)	
Overall Height (with ROPS folded)	67.2" (170.7 cm)	
Overall Length	118.0" (299.7 cm)	135.4" (343.9 cm)
Ground Clearance	7.9" (20.1 cm)	
Operating Weight	3,172 lbs (1,439 kg)	3,514 lbs (1,593 kg)
VIBRATORY PLOW		
Maximum Plow Depth	24" (61 cm)	
TRENCHER		
Boom Options		
36" (91 cm) Boom	36" (91 cm) trench depth	
24" (61 cm) Boom	24" (61 cm) trench depth	
HYDRA-BORE		
Max Torque	342 ft-lb (464 N-m)	

OPTIONAL EQUIPMENT

23" Tires (set of 4): 25536T | 23" Dual Tire Kit: 25539T
 26" Dual Tire Kit: 25540T
 Wheel Weights: 25541T
 Reel Carrier 22", 200 lbs cap: 25538T

Crumbler Kit: 25533T
 Booms: 24" Dig 25534T | 36" Dig 25535T
 Plow Shoe: 25543T