



DINGO® TXL 2000 COMPACT UTILITY LOADERS





OUTSTANDING CAPACITY

With up to 2,000 lbs (907 kg) of operating capacity, the TXL 2000 has the muscle for demanding jobs. Powered by a 49.6 hp* T4F Kubota® engine, it can handle pallets of sod, concrete blocks, landscaping boulders, large trees and much more. Plus, the universal mounting plate accepts most skid steer and compact track loader attachments, so you can use accessories you already own.



OUTSTANDING REACH AND LIFT HEIGHT

Exclusive INTELESCOPE™ arms allow the TXL 2000 to dig below grade, reach over obstacles and extend your working range. Backfill behind a retaining wall. Dump material into the center of a full-size dump truck or dumpster. Offload both rows of a trailer or flatbed from the curb without repositioning to reach the other side. Fully extended, the boom has a hinge pin height of just over 10 ft (313 cm), opening up countless possibilities.

HINGE PIN HEIGHT
OF JUST OVER
10 ft

OUT. STANDING.

THE TORO® DINGO® TXL 2000 DOES THE WORK OF SEVERAL MACHINES IN ONE.

Excavating. Material handling. Grading. The TXL 2000 has you covered. No need for separate machines to unload, haul, dig and place material; the TXL 2000 can do it all. With the benefits of a compact utility loader, mini excavator and compact track loader rolled into one piece of equipment, it's a smart solution that's in a category of its own.



*As configured to meet safety, emission and operating requirements, the actual engine horsepower on this product may be significantly lower.

DINGO[®] TXL 2000



OUTSTANDING VISIBILITY

With a stand-on operator platform instead of a cab, the TXL 2000 provides 360° visibility. No need for a back-up camera — just turn and look.



OUTSTANDING EASE OF USE

The simple TXL 2000 control interface is easy to use and master.



OUTSTANDING ACCESSIBILITY

Operators of different sizes can easily jump on and off the platform instead of getting into and out of a cab. It's also perfect for those looking to spend less time sitting. Flexible platform suspension and cushioned front and side rests enhance comfort for maximum productivity.



OUTSTANDING MANEUVERABILITY

The TXL 2000 is approximately 12 in (5.08 cm) narrower than a compact track loader, so you can maneuver in and out of small spaces where other units just can't go. You get the traction you need with a footprint that minimizes damage to turf.



SMART FEATURES GIVE YOU ADDED PEACE OF MIND

SMARTPOWER™

OPTIMIZE POWER FOR THE TASK WITH SMART POWER™ TECHNOLOGY

Get the most efficiency out of your machine by selecting the Smart Power™ option on the Info Center. This feature automatically adjusts the traction speed to maximize engine, auxiliary and traction torque. Smart Power senses engine load and optimizes performance to prevent stalling, while helping ensure less experienced operators use the machine correctly.

SMARTLOAD™

SMART LOAD™ ADJUSTS TRACTION SPEED BASED ON LOAD HEIGHT

The Smart Load™ feature senses when the machine arms have raised the load beyond set limits and reduces the traction speed to 50 percent during transport. When the arms are lowered to within set limits, Smart Load turns off the speed reduction, allowing the traction speed to ramp back up to 100 percent. This feature is a protective precaution to encourage operation within recommended parameters.





DIG, TRENCH, HAUL, GRADE, PREP AND MORE WITH TORO DINGO ATTACHMENTS

Toro's tough, powerful attachments are specifically designed for the Dingo TXL 2000 line and are easy to put on or take off in seconds. Just mount the accessory to the attachment plate on the unit, push the pins to the locked position and connect hydraulic lines (for powered attachments).

Add versatility to your machine with these and other genuine Toro Dingo TXL 2000 attachments:

- High-Volume Bucket
- Standard Bucket
- Grading Bucket
- Stump Bucket
- Adjustable Forks
- Leveler
- U-Blade
- Grapple
- Power Rake
- Angle Broom
- Skeleton Grapple
- Tiller
- Pick-Up Broom
- Brush Cutter
- Auger Drive Head with Multiple Standard and Rock Auger Bit Sizes
- Trencher Drive Head with Multiple Boom Sizes, Chain Combinations and Crumber Options

SPECIFICATIONS

		DINGO® TXL 2000 WITH TELESCOPING ARMS (MODEL 22530)	DINGO® TXL 2000 WITHOUT TELESCOPING ARMS (MODEL 22531)
ENGINE	Model	49.6 hp (37 kW) Kubota® D1803 diesel	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid cooled	
	Fuel Tank	18.3 gallons (69.3 liters)	
	Oil Capacity	7 quarts (6.6 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	Traction: 4,350 PSI (29,992.1 kPa) Auxiliary: 3,000 PSI (20,684.2 kPa)	
	Hydraulic Flow	Traction: 21.5 gpm (81.4 lpm) each pump Auxiliary: 21.44 gpm	
	Reservoir Capacity	15.25 gallons (57.7 liters)	
TRACKS	Standard	Sprocket-drive, 6 road wheels per side	
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Width	162.2" x 11.8" (411.9 x 29.9 cm)	
	Wheelbase	53.7" (136.4 cm)	
	Ground Clearance	6.3" (16.0 mm)	
	Overall Dimensions With Bucket (WxLxH)	55" x 136.9" x 67.8" (137 x 348 x 172 cm)	
	Overall Dimensions Without Bucket (WxLxH)	55" x 98.8" x 67.8" (139.7 x 250.9 x 172.2 cm)	
	Maximum Operating Height	67.8" (172 cm)	
	Hinge Pin Height	123.4" (313.4 cm)	98.6" (250.4 cm)
	Dump Height	88.9" (225.8 cm)	64.1" (162.8 cm)
	Dump Angle	46.3 degrees	
	Reach – Fully Raised	26.1" (66.2 cm) retracted, 45.2" (114.8 cm) extended	26.1" (66.2 cm)
Ground Speed	5.4 mph (8.6 km/h)		
Weight	6,690 lbs (3,034 kg)	6,270 lbs (2,844 kg)	
Tip Capacity	5,715 lbs (2,592 kg) retracted, 2,620 lbs (1,188 kg) extended	5,715 lbs (2,592 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	2,000 lbs (907 kg) retracted, 920 lbs (417 kg) extended	2,000 lbs (907 kg)	
Ground Pressure	5.3 PSI (36.5 kPa)		



facebook.com/toro.company



twitter.com/TheToroCompany



instagram.com/thetorocompany



youtube.com/toro



toro.com / toro.ca

© 2023 The Toro Company. 490-0186_rev2
All rights reserved. Printed in the USA.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, design and standard equipment without notice and without incurring obligation. See your dealer for details on all our warranties.



Count on it.