


TORO®

eProStripe™ 560 / ProStripe® 560

STRIPING MOWER

FEATURES

- **High definition stripes** – precisely formulated roller leaves crisp, visually striking stripe while keeping overall weight of machine low to nurture grass blade health and avoid compaction
- **One pass operation** – mow, remove divots and debris, and smooth in one wide pass
- **Fine turf performance** – low cutting height ability designed for sports fields and high impact settings
- **Powered transport** – use traction drive independent of the cutting blade for easy no-mow travel between sites
- **Toro Flex-Force Power System™** – electric power version of the eProStripe 560 uses two Toro-designed 60V* lithium batteries to ensure long, quiet run time, while maintaining compatibility with over 50 Flex-Force tools



- **Agility & Mobility** – two piece, ribbed roller allows zero-turn ability to prevent wheel tear while giving superior traction



- **MatchDrive™** – Variable speed electric transmission system provides three preset speeds, consistent with the mechanical drive on the ProStripe, plus an additional variable speed option

providing a greater speed range and fine tuning to suit conditions and consistent operation of multiple units



- **Grooming ease** – enhance appearance and turf health with optional brush kit that stands up grass blades for a cleaner cut, reduces lateral blade growth and loosens debris for removal

Perfect Pitch.

The lightweight, superb collection and striping performance capabilities are further enhanced on the lithium-ion battery-powered eProStripe by quiet operation, low vibrations levels, and zero engine exhaust emissions. With two of Toro's 60V* Flex-Force Power System™ batteries, the electric version is ensured a long run time as well as compatibility across a wide range of hand tools and machinery.



Call your Toro distributor at **800-803-8676**



eProStripe™ 560 / ProStripe® 560

The lightweight, superb collection and striping performance capabilities are further enhanced on the lithium-ion battery-powered eProStripe by quiet operation, low vibrations levels, and zero engine exhaust emissions. With two of Toro's 60V* Flex-Force Power System™ batteries, the electric version is ensured a long run time as well as compatibility across a wide range of hand tools and machinery.

	ePROSTRIPE 560, MODEL 02660T (TOOL ONLY)*	PROSTRIPE 560, MODEL 02657*
CUTTING WIDTH	22" (56cm)	
ROLLER WIDTH	20.5" (52cm)	
REAR ROLLER	Steel, two-piece. Ribbed for superior traction and perfect striping	
POWER	2kW 60V** Brushless DC	Kawasaki® FJ180VKAI OHV 4-cycle, gasoline, 179cc
AIR FILTER	N/A	Dual Element
FUEL TYPE/CAPACITY	Lithium-Ion	Gasoline/0.45 gal (1.7L)
BATTERY SYSTEM	Flex-Force Power System™ All battery types, minimum recommendation 2x 7.5Ah batteries.	N/A
STARTER	Push-Button	Pull Start
DRIVE SYSTEM	MatchDrive™, electric, operates independent to cutter blade	3-Speed Self Propelled
MOWING SPEED	3-speed 1.9, 2.5 or 3.2mph (3.0, 4.0 & 5.2km/h), or Variable speed 1.0 - 3.5mph (1.6 - 5.6km/h)	3-speed 1.9, 2.5, 3.1 mph (3.05, 4.02, 4.98 km/h)
BLADE ENGAGEMENT	Push button, operates independent to transmission	Blade Brake Clutch (BBC)
BLADE SPEED	2,800 rpm (standard), 2,400 rpm (ECO mode)	2,700 rpm
DECK	Die cast corrosion-resistant aluminum	
HEIGHT OF CUT RANGE	0.5" - 2.36" (13 - 60mm)	
HEIGHT OF CUT INCREMENTS	MatchCut™, 0.5"x .127" (13x 3.25mm) increments	
GRASS BAG CAPACITY	21 gallons (80 liters)	
DRY WEIGHT	116.2 lbs. (52.7 kg) w/optional Groomer Brush (without batteries)	145 lbs (66 kg)
BLADE	1.25" (3.2mm) thick swaged steel blade	
FRONT TIRES	9" (225 mm) smooth shoulder tire	
DIMENSIONS (LxWxH)	69.1" (175.5 cm) x 23" (58.6cm) x 40.9" (103.9cm)	
WARRANTY	Two-Year Limited Warranty (mower). 2-Years (Battery - 7.5Ah or greater & Charger - 5.4A & 6-pod chargers)	Two-year limited warranty. Refer to operator's manual for further details.



134-9600	High-Lift Blade (eProStripe only)
162-1458	Front Bumper Kit (Not available with Groomer Brush kit, 134-3722)



*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

**Battery manufacturer rating = 60V maximum & 54V typical usage. Actual voltage varies with load.

