NEW

Workman® LTX Series

UTILITY VEHICLES

FEATURES

- **Power Your Way** – *Select the Briggs & Stratton® Vanguard® 400 EFI gasoline engine or the advanced Toro HyperCell® Lithium-Ion battery system. Both deliver exceptional power, reliability, and efficiency, so you can tackle every job with confidence.*
- **Endless Ways to Customize** – *The Workman LTX gives you the flexibility to tackle any job with dozens of configuration options. Choose standard height or lifted models, extend the bed for additional hauling, or add an additional row of seats for more passengers. With accessories to match, you can make your office on wheels your own.*
- **Intuitive Dashboard Layout** – *Oversized cup holders and ample storage for tools and gear. Stay in control with easy-to-reach controls and a clear LCD display. Plus, keep your devices powered on the go with integrated USB-A & C charging ports.*



- **Braking You Can Count On** – *Hydraulic disc brakes deliver reliable, consistent stopping power with minimal maintenance, no cable adjustments and less pedal force than traditional mechanical brakes. On lithium-powered models, an electronically controlled parking brake adds an extra layer of convenience.*
- **Suspension** – *Equipped with coil-over shocks on all four tires, the system provides enhanced suspension travel and adjustability. This results in a smoother, more controlled ride while reducing operator fatigue.*
- **Steering** – *An automotive-grade rack and pinion steering system provides more control and lowers steering effort, while operating loaded or empty. This allows operators to focus on the task at hand and nothing else.*

©2026 The Toro Company. All rights reserved. Rev. 10/26

Built for This. Power Meets Purpose.

The next generation of light-duty utility vehicles is here. The new Workman LTX delivers everything you asked for - power, comfort, and elevated design. Powered by either the Briggs & Stratton Vanguard 400 EFI gasoline engine or the Toro HyperCell lithium battery system, the LTX offers standard height, lifted, or extended models to help you tackle your toughest days. With abundant storage, enhanced options, optimal design, and rugged reliability, you don't have to choose between strength and versatility. The Toro Workman LTX provides both because your work deserves the best.

toro.com/ltx



Call your Toro distributor at 800-803-8676

Workman® LTX Series Specifications*

	WORKMAN LTX (GAS EFI), MODELS: 07424, 07424LT, 07424EX	WORKMAN LTX (LITHIUM), MODELS: 07425, 07425LT, 07425EX
ENGINE / POWER SYSTEM	408cc, air-cooled, single cylinder Briggs & Stratton® EFI gasoline engine.	Two HyperCell® Lithium-ion batteries standard, option to add an additional battery.
ENERGY CAPACITY	N/A	4.32 kWh standard, 6.48 kWh optional. 55V nominal; 63V Max
ELECTRIC MOTOR	N/A	Brushless high-torque AC Induction motor with 5.0kW continuous power.
STEERING	Manual rack and pinion steering system with ergonomically positioned column. Steering wheel has 2.75 turns lock-to-lock with 13.75" (35 cm) diameter.	
TURNING RADIUS	**Standard & lifted models:** turning clearance circle: 20.7' (6.3 m), inside turning radius: 60.25" (153 cm). **Extended models:** turning clearance circle: 31' (9.45 m), inside turning radius: 100" (254 cm)	
BRAKES	Front and rear wheel hydraulic disc brakes.	
PARKING BRAKE	Foot pedal with accelerator pedal release.	Automatic parking brake.
SUSPENSION	**FRONT –** Modified MacPherson Strut. **REAR –** Articulating Swing Arm. Adjustable Coil Over Shocks at all four wheels.	
SUSPENSION TRAVEL	**Front Suspension Travel:** 3.5" (8.9 cm) **Rear Suspension Travel:** 4" (10.2 cm).	
FUEL CAPACITY	5 gallons (18.9 liters)	N/A
GROUND SPEED	16 mph (25.6 km/h) governed. Speed reduction kits available.	16 mph (25.6 km/h) standard, adjustable up to 22 mph (35.4 km/h). Setting of 19 mph (30.6 km/h) and greater require ROPs & seatbelt.
TRANSAXLE	11.47:1 Forward, 14.35:1 Reverse	
GROUND CLEARANCE	**Standard height models**: Front: 9" (22.8 cm), Rear: 6" (15.2 cm) **Lifted models:** Front: 12" (30.4 cm), Rear: 7" (17.8 cm)	
TIRES	**Standard & extended models:** 20 x 8-10, 4-ply. Or alternate 4-ply/6-ply. **Lifted models:** 22 x 9.5-12, 4-ply. Or alternate 4-ply/6-ply.	
WHEELS	**Standard & extended models:** 10" (25.4 cm) steel **Lifted models:** 12" (30.5 cm) aluminum	
STARTER BATTERY	One 12-volt starter battery	N/A
CONTROLLER	N/A	375 amps max with regenerative motor braking, roll-away protection, thermal cutback, sealed/waterproof, status light and three power modes.
CHARGER	N/A	On-board high efficiency 900W smart charger. •AC Input Voltage: 100-240 VAC •AC Input Frequency: 50/60 Hz •Max AC Input Current: 13.4 A
INSTRUMENTS/DASH	LCD display, USB A & C power ports, headlight switch, on/off ignition key switch, horn switch, cup holders, radio holder, and large storage compartments throughout dash.	
STARTING	Pedal or key start capability standard.	Pedal start standard.
DIMENSIONS	**Vehicle Configuration** / **Width** / **Length** / **Height:** / **Wheel Base** 2-Seat with Bed (LTX std. ht.) — 47" (119.3 cm) — 119" (302 cm) — 50.2" (127 cm) — 77.8" (197 cm) 2-Seat with Bed (LTX Lifted) — 47" (119.3 cm) — 119" (302 cm) — 53.2" (135 cm) — 77.8" (197 cm) 4-Seat with Bed (LTX extended) — 47" (119.3 cm) — 144" (366 cm) — 50.2" (127 cm) — 114" (290 cm) 2-Seat with 6' Flat Bed (LTX extended) — 47" (119.3 cm) — 156" (396 cm) — 50.2" (127 cm) — 114" (290 cm)	
SEAT	Line installed bolstered bench seat, seat, two-tone gray, with embossed Toro bullhorns on seat backs. **Weight:** 36 lbs. (16 kg)	
CAB DIMENSIONS INSTALLED	**Standard height models:** Height: 79" (201 cm) Width: 56" (142 cm) **Lifted models:** Height: 82" (208 cm) Width: 56" (142 cm)	
WEIGHT (NOT INCLUDING BED)	**Vehicle Configuration** / **Weight** 2-Seat — 835 lbs. (379 kg) 2-Seat Lifted — 860 lbs. (390 kg) 2-Seat Extended — 994 lbs. (451 kg)	**Vehicle Configuration** / **Weight** 2-Seat — 850 lbs. (386 kg) 2-Seat Lifted — 875 lbs. (397 kg) 2-Seat Extended — 1,011 lbs. (459 kg)
BEDS	**Plastic Cargo Bed: Width:** 37" (94 cm) **Length:** 40" (101.6 cm) **Height:** 11" (28 cm) **Weight:** 122 lbs. (55 kg) **Capacity:** 800 lbs (363 kg) **Steel Cargo Bed: Width:** 43" (109 cm) **Length:** 44" (111 cm) **Height:** 11" (28 cm) **Weight:** 196 lbs. (89 kg) **Capacity:** 800 lbs. (363 kg) **6' (1.8 m) Bed w/Sides: Width:** 46" (117 cm) **Length:** 72" (183 cm) **Height:** 11" (28 cm) **Weight:** 295 lbs. (133 kg) **Capacity:** 800 lbs. (363 kg)	
CANOPY DIMENSIONS INSTALLED	**Standard height models:** Height: 75.2" (191 cm) Width: 54.3" (138 cm) **Lifted models:** Height: Height: 78.2" (199 cm) Width: 54.3" (138 cm)	
VEHICLE CAPACITY	2-seat with bed 1,200 lbs. (544 kg)	
TOWING CAPACITY	1,500 lbs. (680 kg) Class 1 – 1.25" receiver standard.	
OPTIONAL ACCESSORIES	Canopy, folding windshield, windshield w/ wiper, seat kit for EX models, steel cargo bed, plastic cargo bed, 6-foot flat bed, bed sides, electric bed lift, bed racking, brush guard, brush guard w/ front receiver, trash can mount, ROPS certified cab, cab doors, light options for cab (work lights and beacon), range cage, canopy with ROPS, mirrors, brake/tail/signal lights, back up alarm, under hood storage kit, ram mount ball, 12V power point kit, all-terrain tire kit, telematics kit. Allied accessories: drop-in beverage cart, Kimtek medical bed, Rahn Groomer	
WARRANTY	Two-year or 1500 hour limited warranty. Engine warranty with Briggs – 3-year limited commercial warranty +1-year after registering engine: vanguardpower.com/registration. 5-year warranty on lithium-ion battery. Refer to the Operator's manual for further details.	

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only.
Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.