



ProCore® 648s

POWERED GREENS AERATOR

FEATURES

- Exclusive wheel placement inside coring head path
- Improved coring head drop and raise results in faster return to pre-aeration conditions
- Delayed mode allows operators to easily lift and lower coring head over obstacles
- Electronically controlled hydrostatic drive maintains consistent hole spacing
- Tine depth and hole spacing set and saved in InfoCenter™
- TrueCore™ ground-following system ensures depth consistency in undulating conditions
- RotaLink™ coring head delivers smooth operation, superior hole quality and unrivaled productivity
- Standard storage box and optional LED light kit

The new gold standard of greens aeration.

The ProCore 648s builds on the tremendous legacy of the ProCore 648 by incorporating proven technology and even more innovative features while preserving the time tested design elements that changed the way you aerate. Revised controls improve ergonomics and allow single handed operation. Hole spacing and true tine depth are now set and saved in the InfoCenter. The onboard controller is continuously monitoring key operating parameters to improve after aeration turf condition and allow the operator to easily target coring head drop and raise. A tighter turning radius with reduced wheel scrubbing and the ability to easily increase speed during turns increases productivity. Proven reliability, improved performance and exciting innovation - that's what makes the ProCore 648s the new superior choice.

NEW

toro.com/648s



Set selector switch to Delayed Mode




Use front tire as indicator to engage aeration



Coring head drops where aeration engaged



PROCORE 648S, MODEL 09960																																				
ENGINE	Kohler®, 2-cylinder, air-cooled, 23 hp (17.1 kW) gross, 19 hp (14.2 kW) net @ 3000 rpm, 41 cu-in. (674 cc) displacement. Dry, large capacity, replaceable element air filter. External spin-on oil filter, 2-quart (1.9-liter).																																			
FUEL CAPACITY	7.5 gallons (28.4 liter), gasoline.																																			
ELECTRICAL	12-volt, 15 amp regulated charging alternator/generator. BCI Group No.: U1 battery, 300 cold cranking amps @ 0°F. Micro-processor logic control.																																			
DRIVETRAIN	Series-Parallel, closed loop, hydrostatic drive. 3WD, except it automatically switches to 2WD while in aeration mode and traveling in forward direction with coring head raised allowing a tighter turning radius. Electronically controlled variable displacement piston type pump. High-torque, low-speed wheel motor drive.																																			
HYDRAULIC SYSTEM	Remote spin-on filter. 3.0- gallon (13.2 liter) capacity, Toro PX Extended Life hydraulic fluid.																																			
CONSTRUCTION	Welded steel frame with cast crank and arm assembly.																																			
TIRES	20 x 10-10, 2-ply rated, smooth tread, tubeless, inflated to 12 psi, de-mountable rims.																																			
BRAKES	Dynamic braking through hydrostatic transmission. Parking brake actuated when steering handle is raised into storage position.																																			
GROUND SPEED	<table border="0"> <tr> <td>Transport Mode:</td> <td>Aeration Mode:</td> <td>Aeration Forward Spacing:</td> </tr> <tr> <td>Forward: 0-4.5 mph (0-7.2 km/h), variable</td> <td>Forward: 0-2.5 mph (0-4.0 km/h), variable</td> <td>1-4.5" (2.5-11.3 cm) in 0.25" (5mm) increments</td> </tr> <tr> <td>Reverse: 0-2.0 mph (0-3.2 km/h), variable</td> <td>Reverse: 0-2.0 mph (0-3.2 km/h), variable</td> <td>1" (2.5 cm) spacing: 0.51 mph (0.8 km/h)</td> </tr> <tr> <td></td> <td></td> <td>2" (5.0 cm) spacing: 1.03 mph (1.65 km/h)</td> </tr> <tr> <td></td> <td></td> <td>3" (7.5 cm) spacing: 1.54 mph (2.46 km/h)</td> </tr> <tr> <td></td> <td></td> <td>4" (10.0 cm) spacing: 2.06 mph (3.30 km/h)</td> </tr> </table>	Transport Mode:	Aeration Mode:	Aeration Forward Spacing:	Forward: 0-4.5 mph (0-7.2 km/h), variable	Forward: 0-2.5 mph (0-4.0 km/h), variable	1-4.5" (2.5-11.3 cm) in 0.25" (5mm) increments	Reverse: 0-2.0 mph (0-3.2 km/h), variable	Reverse: 0-2.0 mph (0-3.2 km/h), variable	1" (2.5 cm) spacing: 0.51 mph (0.8 km/h)			2" (5.0 cm) spacing: 1.03 mph (1.65 km/h)			3" (7.5 cm) spacing: 1.54 mph (2.46 km/h)			4" (10.0 cm) spacing: 2.06 mph (3.30 km/h)																	
Transport Mode:	Aeration Mode:	Aeration Forward Spacing:																																		
Forward: 0-4.5 mph (0-7.2 km/h), variable	Forward: 0-2.5 mph (0-4.0 km/h), variable	1-4.5" (2.5-11.3 cm) in 0.25" (5mm) increments																																		
Reverse: 0-2.0 mph (0-3.2 km/h), variable	Reverse: 0-2.0 mph (0-3.2 km/h), variable	1" (2.5 cm) spacing: 0.51 mph (0.8 km/h)																																		
		2" (5.0 cm) spacing: 1.03 mph (1.65 km/h)																																		
		3" (7.5 cm) spacing: 1.54 mph (2.46 km/h)																																		
		4" (10.0 cm) spacing: 2.06 mph (3.30 km/h)																																		
INSTRUMENTATION	InfoCenter™, tachometer.																																			
CONTROLS	Redundant operator presence bails, aeration start/stop bails and traction speed thumb wheels on handle. Tine length calibration, tine depth and forward hole spacing set and saved in InfoCenter. Bump stop, delayed or immediate drop switch, cruise control on/set/off switch, aerate or transport switch and optional LED light kit switch located on operator console. Ignition, tachometer on side console. Throttle and choke on engine.																																			
INTERLOCKS	Operator presence, clutch latch, traction neutral, coring head raise/lower.																																			
DIMENSIONS	<table border="0"> <thead> <tr> <th>Length</th> <th>Width</th> <th>Height</th> <th>Wheelbase</th> <th>Track Width</th> <th>Weight (dry)</th> <th>Ground Clearance</th> </tr> </thead> <tbody> <tr> <td>Handle Down: 116.3" (293.1 cm)</td> <td>50.12" (127.3 cm)</td> <td>Head Raised 45" (114.3 cm)</td> <td>44.5" (113 cm)</td> <td>38.3" (97.3 cm)</td> <td>1,642 lbs (744.7 kg)</td> <td>4.75" (12.1 cm)</td> </tr> <tr> <td>Handle Raised: 91.8" (231.3 cm)</td> <td></td> <td>Head Lowered 36.5" (92.7 cm)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Handle Raised: 60.7" (153.0 cm)</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Handle Lowered: 47.5" (119.7 cm)</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Length	Width	Height	Wheelbase	Track Width	Weight (dry)	Ground Clearance	Handle Down: 116.3" (293.1 cm)	50.12" (127.3 cm)	Head Raised 45" (114.3 cm)	44.5" (113 cm)	38.3" (97.3 cm)	1,642 lbs (744.7 kg)	4.75" (12.1 cm)	Handle Raised: 91.8" (231.3 cm)		Head Lowered 36.5" (92.7 cm)							Handle Raised: 60.7" (153.0 cm)							Handle Lowered: 47.5" (119.7 cm)				
Length	Width	Height	Wheelbase	Track Width	Weight (dry)	Ground Clearance																														
Handle Down: 116.3" (293.1 cm)	50.12" (127.3 cm)	Head Raised 45" (114.3 cm)	44.5" (113 cm)	38.3" (97.3 cm)	1,642 lbs (744.7 kg)	4.75" (12.1 cm)																														
Handle Raised: 91.8" (231.3 cm)		Head Lowered 36.5" (92.7 cm)																																		
		Handle Raised: 60.7" (153.0 cm)																																		
		Handle Lowered: 47.5" (119.7 cm)																																		
CERTIFICATION	ANSI B71.4-2017. CE & EU machinery directives.																																			
WARRANTY	Two-year or 500 hour limited warranty. Refer to the Operator's Manual for further details.																																			

TINE HEADS																																	
TINES	<table border="1"> <thead> <tr> <th>Model</th> <th>Description</th> <th>Lateral Spacing</th> <th>Mount Diameter</th> </tr> </thead> <tbody> <tr> <td>09739</td> <td>Needle Tine</td> <td>1.6" (2.8 cm)</td> <td>N/A</td> </tr> <tr> <td>09736</td> <td>Mini-Tine (2 rows of 5)</td> <td>1.6" (2.8 cm)</td> <td>3/8"</td> </tr> <tr> <td>09737</td> <td>Mini-Tine (1 row of 6)</td> <td>1.3" (3.3 cm)</td> <td>3/8"</td> </tr> <tr> <td>09794</td> <td>3 Tine 3/4"</td> <td>2.6" (6.8 cm)</td> <td>3/4"</td> </tr> <tr> <td>09796</td> <td>4 Tine 3/4"</td> <td>2" (5.1 cm)</td> <td>3/4"</td> </tr> <tr> <td>09797</td> <td>3 Tine 7/8"</td> <td>2.6" (6.8 cm)</td> <td>7/8"</td> </tr> <tr> <td>09719</td> <td>QuickChange® 4-Tine</td> <td>2" (5.1 cm)</td> <td>3/4" or 7/8"</td> </tr> </tbody> </table>	Model	Description	Lateral Spacing	Mount Diameter	09739	Needle Tine	1.6" (2.8 cm)	N/A	09736	Mini-Tine (2 rows of 5)	1.6" (2.8 cm)	3/8"	09737	Mini-Tine (1 row of 6)	1.3" (3.3 cm)	3/8"	09794	3 Tine 3/4"	2.6" (6.8 cm)	3/4"	09796	4 Tine 3/4"	2" (5.1 cm)	3/4"	09797	3 Tine 7/8"	2.6" (6.8 cm)	7/8"	09719	QuickChange® 4-Tine	2" (5.1 cm)	3/4" or 7/8"
	Model	Description	Lateral Spacing	Mount Diameter																													
	09739	Needle Tine	1.6" (2.8 cm)	N/A																													
	09736	Mini-Tine (2 rows of 5)	1.6" (2.8 cm)	3/8"																													
	09737	Mini-Tine (1 row of 6)	1.3" (3.3 cm)	3/8"																													
	09794	3 Tine 3/4"	2.6" (6.8 cm)	3/4"																													
	09796	4 Tine 3/4"	2" (5.1 cm)	3/4"																													
	09797	3 Tine 7/8"	2.6" (6.8 cm)	7/8"																													
09719	QuickChange® 4-Tine	2" (5.1 cm)	3/4" or 7/8"																														
ACCESSORIES																																	
	<table border="1"> <thead> <tr> <th>Model</th> <th>Description</th> <th>Part Number</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>09962</td> <td>LED Light Kit, ProCore 648s</td> <td>114-0590-01</td> <td>QuickChange® Tool</td> </tr> <tr> <td>09220</td> <td>Windrower Kit</td> <td>115-4754</td> <td>Wireless Hour Meter</td> </tr> <tr> <td>09225</td> <td>Tire Scrapers</td> <td></td> <td></td> </tr> <tr> <td>09234</td> <td>Rear Roller Kit</td> <td></td> <td></td> </tr> </tbody> </table>	Model	Description	Part Number	Description	09962	LED Light Kit, ProCore 648s	114-0590-01	QuickChange® Tool	09220	Windrower Kit	115-4754	Wireless Hour Meter	09225	Tire Scrapers			09234	Rear Roller Kit														
Model	Description	Part Number	Description																														
09962	LED Light Kit, ProCore 648s	114-0590-01	QuickChange® Tool																														
09220	Windrower Kit	115-4754	Wireless Hour Meter																														
09225	Tire Scrapers																																
09234	Rear Roller Kit																																
TINES																																	
	<div style="display: flex; align-items: flex-start;">  <div style="margin-left: 10px;"> <p>Over 100 Titan Tines in multiple varieties available from Toro. See the Toro Titan Tines Catalog or visit toro.com/titantines</p> </div> </div>																																

*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. See distributor for details on all warranties.

