

**TORO**

# TORO® MAXI SNEAKER™ 370

VIBRATORY PLOW

Toro's Maxi Sneaker 370 delivers powerful plowing in a compact, maneuverable package. The Yanmar® 1.6L, liquid cooled engine, provides reliable power while plowing or trenching while the hydraulic steering allows articulation to a centerline turning radius for maximum maneuverability.

## EASE OF OPERATION

Optimized operator's position allows operator to see all 4 tires while trenching, plowing or transporting. Foldable ROPS allows for easier transportation and accessibility.

## PRECISE CONTROL

Low-effort, dual-lever ground drive controls for creep and transport modes.



## EASY ACCESS

With 23" (58 cm) tires mounted narrow and inward, allows easy access to tight spaces.



## EASY-TO-READ DISPLAY

Digital display allows operator to view system gauges and indicators for easier visibility and use.



## CONSISTENT PLOWING

Optimized plow design provides down pressure to maintain consistent plowing up to 24" deep in a variety of conditions.



## TRACTION AND STABILITY

Minimize impact on turf with optional dual wheel configuration. Dual wheels available in two sizes.

## PRODUCTIVE TRENCHING

Optional front-mounted, hydraulically-driven trencher. Dig depths of 24" or 36" (61 cm or 91 cm).



## ADDED VERSATILITY

The optional equipment adds to the versatility of the Maxi Sneaker

## OPTIONAL EQUIPMENT

- Single Tires: 26x12x12
- Dual Tires: 23x10.5x12 or 26x12x12
- Hydra-borer System
- Wheel Weights
- Reel Carrier
- Trenchers
- Crumber
- Chains (cup, combo or shark teeth)

## SPECIFICATIONS - Model 25530T

### DIMENSIONS

Width (with 23x10.5x12 tires)	36.5" (85.1 cm) mounted narrow 47.0" (119.4 cm) mounted wide 58.0" (147.3 cm) dual
Width (with 26x12x12 tires)	40.8" (103.6 cm) mounted narrow 46.7" (118.6 cm) mounted wide 66.0" (167.6 cm) dual
Wheelbase	48.0" (122 cm)
Overall Height (with ROPS and 23x10.5x12 tires)	85.5" (217.1 cm)
Overall Height (with ROPS folded and 23x10.5x12 tires)	65.7" (166.9 cm)
Overall Height (with ROPS and 26x12x12 tires)	87.0" (221.0 cm)
Overall Height (with ROPS folded and 26x12x12 tires)	67.2" (170.7 cm)
Overall Length (with plow only, transport position)	118.0" (299.7 cm)
Ground Clearance (with 23x10.5x12 tires)	6.4" (16.3 cm)
Ground Clearance (with 26x12x12 tires)	7.9" (20.1 cm)
Operating Weight (with plow, hydrabore, 26x12x12 tires)	3,172 lbs (1,439 kg)

### POWER

Engine	Yanmar® 3TNV88C-DTR4
Fuel Type	Diesel
Fuel Tank Capacity	7.1 gal (26.9 L)
Coolant Capacity	10.8 qt (10.2 L)
Oil Capacity	5.5 qt (5.2 L)
Displacement	100.2 cubic inches (1.642 L)
Rated Speed (Idle)	1,400
Net Power Rating per SAE J1349	36.8 hp (27.5 kW)
Rated Speed	3,030 rpm
Battery	12-Volt, 55 amp, 775 CCA

### PERFORMANCE

Ground Drive Pressure	Hydrastatic, Closed Loop
Ground Drive Pump Flow Rate	24.8 gpm (94 L/m)
Attachment Pump Flow Rate	15.6 gpm (59 L/m)
Ground Drive Speed; Forward & Reverse	
23" tires	0 to 3.6 mph (0 to 5.8 km/h)
26" tires	0 to 4.0 mph (0 to 6.4 km/h)

### VIBRATORY PLOW

Maximum Plow Depth	24" (61 cm)
--------------------	-------------

### TRENCHER

Boom Options	
36" (91 cm) Boom	36" (91 cm) trench depth
24" (61 cm) Boom	24" (61 cm) trench depth

### HYDRABORE

Max Torque	342 ft-lb (464 N-m)
------------	---------------------

[toro.com/professional](http://toro.com/professional)

©2023 The Toro Company 490-0907  
 Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.