



- **Shrub, 50mm (2"), 75mm (3"), 100mm (4"), 150mm (6") and 300mm (12") Pop-up**
- **Radius: 0,6-7,9m (2'-26')**
- **Operating Pressure Range (570Z): 1,4-5,2 Bar (20-75 psi)**
- **Operating Pressure Range (570LP): 1,0-5,2 Bar (15-75 psi)**



Learn more at
toro.com

Versatile. Flexible. Reliable. The Toro® 570Z sprinkler embodies all that is required for residential and service contractors wanting to stock just one sprinkler family.

Features & Benefits

Zero Flush Wiper Seal

Prevents flushing on pop-up, allowing more sprinklers on the same line.

One-Piece Check Valve

Easily installed at the factory or in the field. Maintains up to 3m (10') elevation change.

Low Pressure or Enhanced Retraction Spring


Choose the spring which best meets your site specific needs. New to the family is the low pressure 570ZLP which allows for pop-up and retraction at lower pressures.

Ratcheting Riser

For easy and reliable arc adjustment on pop-up models.

Small 50mm (2") Diameter Cap

Less visible, reducing damage from exposure or vandals.



Enhanced Zero
Flush Seal

Water Management Highlight

No Flushing on Pop-Up!

With a pressure-activated wiper seal that flushes only upon retraction, flow-by is eliminated on pop-up reducing water waste and allowing more heads per valve. This zero-flush seal is what makes the 570Z Series a spray head for those serious about effective water management.



Specifications

Dimensions

- Body diameter:
 - 35mm (1 3/8") on 2P, 3P, 4P, 6P and 6P SI models
 - 41mm (1 5/8") on 12P
 - 45mm (1 3/4") on 12P SI
- Cap diameter: 50mm (2")
- Inlet: 1/2" female-threaded
- Side inlet: 4 3/4" from top of sprinkler to center of side inlet

Operating Specifications

- Radius: 0,6-7,9m (2'-26')
- Operating pressure range (570Z): 1,4-5,2 Bar (20-75 psi)
- Operating pressure range (570ZLP): 1,0-5,2 Bar (15-75 psi)
- Recommended pressure for spray nozzles: 2,1 Bar (30 psi)
- Recommended pressure for rotating nozzles: 2,8-3,5 Bar (40-50 psi)
- Flow rate: 0,2-17,0 LPM (0.05-4.5 GPM)

Additional Features

- Stainless steel retraction spring
- Low pressure sealing on LP models at 1,0 Bar (15 psi) for low pressure pumps and well systems
- All bodies shipped with flush plug in place

Options Available

- Check Valve (570CV): maintains up to 3m (10') elevation change (not for side-inlet models)
- 570SEAL: Serviceable seal for all 570Z models
- Effluent water indicators:
 - Effluent Shrub Adapter (102-0563)
 - Effluent Snap-on Cap Cover (89-9752)
 - Effluent Molded Cap with seal (102-1211)
- 570-6X: 150mm (6") Riser Extender
- 570-SR-6: 150mm (6") Stationary Riser 1/2" male-threaded inlet
- 570-SR-18: 450mm (18") Stationary Riser 1/2" male-threaded inlet
- Riser Pull-up Tool (89-6395)
- Adjustment Key (89-7350)

Warranty

- Two years



570ZLP Series Model List

Model	Description
570Z-2LP	570Z, 50mm (2"), Low Pressure
570Z-3LP	570Z, 75mm (3"), Low Pressure
570Z-4LP	570Z, 100mm (4"), Low Pressure
570Z-6LP	570Z, 150mm (6"), Low Pressure
570Z-6LPSI	570Z, 150mm (6"), Low Pressure, Side Inlet
570Z-12LP	570Z, 300mm (12"), Low Pressure
570Z-12LPSI	570Z, 300mm (12"), Low Pressure, Side Inlet

Note: all w/o Nozzle

570Z Series Model List

Model	Description
570Z-2P	50mm (2") Sprinkler
570Z-3P	75mm (3") Sprinkler
570Z-4P	100mm (4") Sprinkler
570Z-4PCOM	100mm (4") Sprinkler, w/Check Valve
570Z-6P	150mm (6") Sprinkler
570Z-6PSI	150mm (6") Sprinkler, Side inlet Body
570Z-6PCOM	150mm (6") Sprinkler, w/Check Valve
570Z-12P	300mm (12") Sprinkler
570Z-12PSI	300mm (12") Sprinkler, Side inlet Body
570Z-12PCOM	300mm (12") Sprinkler, w/Check Valve
570S	Shrub Adapter

Note: all w/o Nozzle

Specifying Information—570ZLP Series

570X-XXLP-XX-COM-E					
Model	Pop-up Height		Optional	Optional	Optional
570X	XXXL		SI	COM	E
Z—Lawn Pop-up & High Pop	2LP—50mm (2") 3LP—75mm (3") 4LP—100mm (4")	6LP—150mm (6") 12LP—300mm (12")	SI—Side Inlet*	COM—Check-O-Matic™**	E—Effluent

Example: A 570ZLP Series Sprinkler (low pressure) with a pop-up height of 150mm (6") and a check valve, you would specify: 570Z-6LP COM

Specifying Information—570Z Series

570X-XXP-XX-COM-E					
Model	Pop-up Height		Optional	Optional	Optional
570X	XXP		SI	COM	E
S—Shrub Z—Lawn Pop-up & High Pop	2LP—50mm (2") 3LP—75mm (3") 4LP—100mm (4")	6LP—150mm (6") 12LP—300mm (12")	SI—Side Inlet*	COM—Check-O-Matic™**	E—Effluent

Example: A 570Z Series Sprinkler with a pop-up height of 150mm (6") and a check valve, you would specify: 570Z-6P COM

*Available for 150mm (6") and 300mm (12") models. **Available with non-side inlet models except 50mm (2") and 75mm (3").

toro.com

Worldwide Headquarters

The Toro Company

8111 Lyndale Ave. So.

Bloomington, MN 55420 U.S.A.

Phone: (1) 952 888 8801

Fax: (1) 952 887 8258

Printed in U.S.A.

©2016 The Toro Company.

All Rights Reserved.

GB 200-XXXXNA Electronic file only.



facebook.com

twitter.com/TheToroCompany

youtube.com/ToroCompanyEurope



Count on it.