

**TORO****DINGO® TX 450**

COMPACT UTILITY LOADERS

Built for the weekend renter and deadline-driven landscaper, the gas-powered Dingo® TX 450 delivers efficient, budget-friendly versatility for tackling outdoor jobs with ease. This compact walk-behind loader features intuitive controls for both novice and experienced operators to maneuver confidently in tight spaces. Whether you're planting trees or hauling dirt, the Dingo TX 450 supports a wide range of attachments to navigate those tough tasks.

## KEY FEATURES

**Compact Size:** The Dingo TX 450 is the right size for jobs that require more than handheld tools, in spaces that don't allow for bulky machinery.

**Turf Friendly Power:** The lightweight, narrow design produces minimal turf disturbance.

**Easy Handling:** Intuitive controls allow both first-time users and experienced operators to work quickly and efficiently.

**Walk-Behind:** The only walk-behind loader in its class, the Dingo TX 450 is designed for simple maneuverability and unbeatable precision in tight spaces - including backyards residential properties.

**Built on Success:** The Dingo TX 450 is built on a 20-year foundation of durability, longevity and dependability.



# TORO® DINGO® TX 450

## SPECIFICATIONS

DINGO TX 450 NARROW TRACK (MODEL 22371)		
<b>ENGINE</b>	Engine	Kohler® Command Pro® 25 HP* (18.6 kw)
	Air Filter	Two-stage, heavy-duty, remote
	Cooling System	Air Cooled
	Fuel Tank	6.0 gallons (23 liters)
	Oil Capacity	2.0 quarts (2.95 liters)
<b>HYDRAULIC SYSTEM</b>	Hydraulic Pressure	3,000 PSI (20,684 kPa)
	Hydraulic Flow	Traction: 16.9 gpm (each pump) Auxiliary: 11.4 gpm
	Reservoir Capacity	10 gallons (37.8 liters)
<b>TRACKS</b>	Standard	Sprocket-drive, 10 road wheels per side
	Traction	Dual hydrostatic pump
<b>DIMENSIONS</b>	Track Dimensions	96.6" x 5.9" (245.3 cm x 14.9 cm)
	Wheelbase	31.2" (79.2 cm)
	Ground Clearance	4.6" (11.6 cm)
	Overall Dimensions (WxLxH) With Bucket	33.7" x 92" x 46.1" (85.5 x 233.6 x 117.0 cm)
	Overall Dimensions (WxLxH) Without Bucket	33.7" x 70.7" x 46.1" (86.5 x 179.5 x 117.0 cm)
	Maximum Operating Height	90.1" (228.8 cm)
	Hinge Pin Height	65.8" (167.1 cm)
	Dump Height	46.1" (117.0 cm)
	Dump Angle	38-degrees
	Reach - Fully Raised	21.8" (55.3 cm)
	Ground Speed	Fwd: 0–4.5 mph (0–7.2 km/h) Rev: 0–2.0 mph (0–3.2 km/h)
	Weight	1,882 lbs (853.6 kg)
	Rated Operating Capacity (35% of Tip Capacity)*	535 lbs. (242.6 kg)
	Ground Pressure	5.1 PSI

\*Per ISO 14397-1